

TOOELE ARMY DEPOT Tooele, Utah

Monitoring Well D-12 Completion Report Phase II RFI Groundwater Investigation

Contract Number: GS-10F-0179J



Submitted to:

U.S. Army Corps of Engineers Sacramento District

December 2005



KLEINFELDER

Prepared by:

PARSONS and KLEINFELDER
Salt Lake City, Utah

MONITORING WELL D-12 COMPLETION REPORT PHASE II RFI GROUNDWATER INVESTIGATION TOOELE ARMY DEPOT TOOELE, UTAH

Contract Number: GS-10F-0179J

Prepared for:



December 2005

A Report Prepared for:

Ms. Maryellen Mackenzie CESPK-ED-EB USACE Sacramento District Environmental Section 1325 J Street Sacramento, California 95814-2922

MONITORING WELL D-12 COMPLETION REPORT PHASE II RFI GROUNDWATER INVESTIGATION TOOELE ARMY DEPOT TOOELE, UTAH

Contract No.: GS-10F-0179J Kleinfelder File No.: 48743.1B Parsons Job No.: 744139

Prepared by:

Matt Ivers, P.G. Staff Geologist

KLEINFELDER

Wall law

Reviewed by:

Richard Jirik, P.G. Senior Hydrogeologist



KLEINFELDER, INC.

849 West Levoy Dr., Ste 200 Salt Lake City, UT 84123 (801) 261-3336 Ed Staes, P.G. Project Manager



PARSONS

406 West South Jordan Pkwy, Ste 300 South Jordan, UT 84095 (801) 572-5999

December 2005

TABLE OF CONTENTS

SEC	ΓΙΟΝ	<u>PA</u>	<u>GE</u>
1.	INTR 1.1 1.2	ODUCTIONBackground InformationProject Purpose and Scope	1
2.	DRIL 2.1 2.2 2.3	LING, SAMPLING, AND LOGGING METHODS	4 4
3.	SUM I 3.1 3.2 3.3	MARY OF SUBSURFACE CONDITIONS Geologic Log Geophysical Log Hydrostratigraphic Section	6 7
4.	WEL I 4.1 4.2	L CONSTRUCTION SUMMARY Construction Techniques and Materials Surface Completion and Survey Coordinates	. 11
5.	WEL I 5.1 5.2	L DEVELOPMENT	. 13
6.	GRO 6.1 6.2	UNDWATER SAMPLINGSampling MethodologyGroundwater Analytical Results	. 14
7.	7.1 7.2 7.3	ALLATION RESTORATION WASTE Decontamination Methods Dispospal of Drill Cuttings Disposal of Wastewater	. 15 . 15
8	RFFF	FRENCES	17

FIGURES

1.1 Site Location Map

TABLE OF CONTENTS (continued)

APPENDICES

A PERMITTING:

Right of Entry Permit, Request and Authorization Letter for Well Construction, Applicant Start Card, Driller Start Card, and Well Driller's Report

B FIELD DOCUMENTATION FOR WELL DRILLING AND CONSTRUCTION:

Daily Field Logs, Field Activity Reports, Health and Safety Briefings, Rig Inspection Logs, and Equipment Calibration Logs

- C GEOLOGIC AND GEOPHYSICAL DATA:
 Geologic Log, Geophysical Log, Cross Section Location Diagram, and
 Hydrostratigraphic Cross Section
- D WELL CONSTRUCTION DATA:Well Construction Diagram and Survey Data Report
- E WELL DEVELOPMENT DOCUMENTATION:
 Well Development Logs and Developer's Daily Logs
- F GROUNDWATER SAMPLING DOCUMENTATION:
 PDB Monitoring Well Sample Log, Groundwater Well Sampler's Daily
 Logs, Analytical Quality Control Summary, Groundwater Sample Analytical
 Report with Chain-of-Custody, and Data Review Summary
- G IRW MANAGEMENT OF SATURATED DRILL CUTTINGS:
 Disposal Recommendation Letter, Drill Cuttings Sample Analytical Report
 with Chain-of-Custody, Waste Profile, and Uniform Hazardous Waste
 Manifests
- H IRW MANAGEMENT OF DEVELOPMENT AND DECONTAMINATION WATER:

Disposal Recommendation Letter, TEAD Denial Letter, Waste Water Sample Analytical Report with Chain-of-Custody, Waste Profile, and Uniform Hazardous Waste Manifests

ABBREVIATIONS AND ACRONYMS

	micrograms per liter
ASC	Analytical Services Center
	American Society for Testing Materials
bgs	below ground surface
	below top of casing
EPA	Environmental Protection Agency
gpm	gallon per minute
IWL	Industrial Wastewater Lagoon
	North American Datum
NEB	Northeastern Boundary Plume
NGVD	National Geodetic Vertical Datum
	nephelometric turbidity unit
NPL	National Priorities List
	tetrachloroethylene
PDB	passive diffusion bag
PID	photoionization detector
	parts per million
	polyvinyl chloride
	Resource Conservation and Recovery Act
RFI	RCRA Facility Investigation
RL	reporting limit
SWMU	Solid Waste Management Unit
TCE	trichloroethene
	Tooele Army Depot
UAC	Utah Administrative Code
	Utah Department of Environmental Quality
UID	Utah Industrial Depot
USACE	United States Army Corps of Engineers
	Unified Soil Classification System
VOA	volatile organic analysis
VOC	volatile organic compound

1. INTRODUCTION

This report contains detailed information regarding the drilling, construction, development, and sampling of groundwater monitoring well D-12, located on private property northeast of the Tooele Army Depot, Utah (TEAD). This report was prepared for the U.S. Army Corps of Engineers (USACE), Sacramento District, under Contract GS-10F-0179J, on behalf of TEAD by Kleinfelder, Inc., (Kleinfelder) and Parsons in Salt Lake City, Utah.

TEAD is an active military facility located approximately 35 miles southwest of Salt Lake City, Utah (Figure 1.1) and it has been in operation since 1942. TEAD has been a primary storage, maintenance, and disposal facility for conventional munitions since its inception. Due to impacts to groundwater quality resulting from this activity, TEAD was added to the National Priorities List (NPL) under the federal Superfund program in October 1990.

1.1 BACKGROUND INFORMATION

Historical wastewater discharges to the unlined Industrial Wastewater Lagoon (IWL) at TEAD resulted in a large impacted groundwater plume beneath the eastern portion of the Depot. A large number of monitoring wells, piezometers, extraction wells, and injection wells have defined a trichloroethene (TCE) plume along downgradient, northern, and western extremes of the Depot. This occurrence of impacted groundwater was designated the Main Plume.

In 1986, TCE was detected in an offsite production well located north of the Industrial Area, approximately 5,000 feet northeast of the IWL. In 1994, well C-10 was installed at the northeastern boundary of the Depot. TCE was detected at a concentration of approximately 240 micrograms per liter (μ g/L) in groundwater sampled from well C-10, located directly across the road from the impacted offsite production well (Kleinfelder, 1998).

Additional groundwater investigations were conducted to further assess the nature and extent of groundwater contamination at the northeastern boundary of TEAD. These additional investigations indicated that the contamination in well C-10 and the adjacent offsite production well had likely originated from a different source than that attributed to the Main TCE plume. Thus, two distinct plumes of groundwater contamination were indicated. This second, more easterly plume, was designated the Northeastern Boundary (NEB) Plume. The oil-water separator at Building 679 in the former industrial area (now the privately owned Utah Industrial Depot [UID]) was identified as a major source of this plume (Kleinfelder, 2002).

A subsequent investigation was designed to define the approximate offsite extent of the NEB Plume. The plume, which is relatively narrow beneath the former industrial area, extends

approximately 16,000 feet downgradient (to the north) from the identified source at Building 679 (Parsons, 2003a). The installation of groundwater monitoring well D-12 was conducted in accordance with the Phase II Resource Conservation and Recovery Act (RCRA) Facility Investigation (RFI) Solid Waste Management Unit (SWMU) 58 Work Plan (Parsons, 2003b) and Work Plan Sampling and Analysis Plan Addendum 1 (Parsons, 2004) that were approved by the USACE and the State of Utah Department of Environmental Quality (UDEQ) prior to initiating fieldwork.

1.2 PROJECT PURPOSE AND SCOPE

Monitoring well D-12 is one of eight groundwater monitoring wells installed between September 2004 and January 2005 during the Phase II RFI at SWMU 58. SWMU 58 encompasses the source areas and the areas impacted by the Main and NEB TCE Plumes. Objectives of the groundwater investigative component of the Phase II RFI are to:

- Refine the vertical limits and lateral extent of the Main and NEB chlorinated solvent plumes;
- Further characterize the distribution of contaminants within the plumes;
- Ascertain whether there are additional contaminant sources to the NEB Plume and assess their impacts to groundwater;
- Assess the risks to human health associated with the unmanaged (offsite) portion of the NEB Plume; and
- Refine the existing numerical groundwater flow and solute transport models with respect to fate and transport, in order to better predict the potential extent (stability) of the plume in the future.

Investigative efforts described in this completion report were supervised by a Kleinfelder State of Utah-registered geologist who was present for critical on-site activities. Before drilling began, a Right-of-Entry Permit was obtained from Tooele County, and a permit for well construction was obtained from the State of Utah Division of Water Rights. Copies of the Right-of-Entry Permit, the Request and Authorization letters, Applicant Start Card, and Driller Start Card are included in Appendix A. Underground utility clearance was obtained through the Blue Stakes Location Center.

Monitoring well D-12 was drilled, constructed, developed, and sampled between September 2, 2004, and November 23, 2004. Drilling and construction activities were conducted by Layne Geoconstruction (Layne) of Salt Lake City, Utah. Following completion of the well, Layne issued a Well Driller's Report, which is also included in Appendix A. Well development and groundwater sampling were completed by Veolia Water North American Operating Services, LLC, which operates the groundwater treatment plant at TEAD. Passive diffusion bag (PDB)

samplers were installed in monitoring well D-12 on November 4, 2004, and retrieved on November 23, 2004. Laboratory analyses were provided by Analytical Services Center (ASC) of Lancaster, New York, a division of Ecology and Environmental, Inc. (E and E), a State of Utah and a USACE-certified analytical laboratory. Down-hole geophysical logging was performed by RAS, Inc., of Golden, Colorado.

Monitoring well D-12 is located about one mile east of the northeast boundary of TEAD in the NE ¼ of Section 19, T3S, R4W, Salt Lake Base and Meridian. The well is accessed via the abandoned railroad grade from Rogers Road. The primary purpose of monitoring well D-12 is to serve as a sentinel well that will detect lateral spreading of the NEB groundwater plume to the east and/or northeast in this area. A secondary objective of this and other sentinel wells that are being installed along the eastern margin of the NEB plume is to better define groundwater flow (Parsons, 2003b).

2.1 DRILLING

Groundwater monitoring well D-12 was drilled by Layne Geoconstruction of Salt Lake City, Utah between September 2nd and September 21st, 2004 using a Becker AP-1000 percussion hammer drilling rig manufactured by Drill Systems. The AP-1000 advances a dual-walled 10-inch diameter drill pipe into the subsurface by means of a diesel-powered pile hammer. Circulating air supplied by an onboard and auxiliary compressor is pumped down the space between the inner and outer walls of the drill rod to the drill bit, where drill cuttings are picked up and carried back through the center of the drill rod and out of the borehole as the air returns to the ground surface. Cuttings are separated from the discharging air by a cyclone. The dry cuttings were collected and spread on the ground around the well site whereas saturated cuttings were contained in 55-gallon drums pending analytical results.

Consolidated bedrock was unexpectedly encountered in the borehole at a depth of 346 feet below ground surface (bgs). The Becker Hammer rig was not able to penetrate the bedrock and a Schramm rotary drill was mobilized to the site. A 5 ¾-inch diameter down-hole hammer was lowered through the 6-inch ID dual wall drill rod to the bottom of the boring using the Schramm. The borehole was then advanced without casing an additional 24 feet into the bedrock to a depth of 370 feet bgs. Broken rock and caving at 365 feet bgs prevented further penetration without risking loss of the drillstring.

2.2 SAMPLING OF DRILL CUTTINGS

Drill cuttings were observed continuously as they discharged from the cyclone and were collected in 1-quart bags and chip trays. The cuttings were logged at 5-foot intervals or when significant changes in lithology occurred. Drive sampling, used in previous boreholes drilled as part of this program, was rarely successful due to refusal in coarse sediments and an inability to anticipate encountering thin fine-grained layers. Thus, a more accurate and complete borehole log resulted from continuous observation of cuttings from the cyclone.

Drill cuttings were logged using the American Society for Testing Materials (ASTM) Method D2488-00. The Unified Soil Classification System (USCS) was used for designating the various types of unconsolidated material encountered. Where a conflict between the two methods was identified, the ASTM convention took precedence. Color of the drill cuttings (when wetted) was noted by referencing the Munsell color chart system. Estimated percentages of gravel, sands, and fines; degree of roundness and lithology/mineralogy of any gravel clasts; moisture content; degree of cementation; and any other notable attributes were routinely recorded in the sample description.

While the degree of roundness ranged from angular to round, the borehole was assumed to have encountered bedrock if the majority of clasts were angular and not observed to be water-worn over several feet. Given that the Becker Hammer method allows a maximum clast size of 6 inches to be delivered to the surface, the percentage of any clasts (cobbles and/or boulders) exceeding that dimension could not be determined.

Grab samples of drill cuttings from below the saturated zone were logged and screened for volatile organic compounds (VOCs) using an Environmental Instruments photoionization detector (PID). PID readings were also recorded on the boring log. PID readings of the grab samples collected from this boring ranged from 0.0 to 0.6 parts per million (ppm). A composite of these samples was submitted for VOC analysis, and was used to determine the proper means of disposal for all saturated cuttings from this borehole. Saturated drill cuttings were containerized in 55-gallon drums and transported to the UID 90-day yard while awaiting analytical results.

2.3 RECORD KEEPING

While on site, Kleinfelder's geologist maintained records of all activities in a bound field log book, on Field Activity Reports, Safety Meeting Logs, Drill Rig Inspection Logs, and Equipment Calibration Logs. Copies are presented in Appendix B.

3.1 GEOLOGIC LOG

A Kleinfelder geologist was on site during drilling to collect samples of drill cuttings in order to maintain a continuous geologic log of the subsurface conditions that were encountered. Lithologic descriptions and geologist's observations were entered onto the geologic log. The geologic log of the cuttings that were sampled during drilling of the monitoring well D-12 borehole is included in Appendix C as Plate C-1.

The geologic log indicates that the boring was drilled in unconsolidated valley fill sediments from the surface to a depth of 346 feet bgs and in bedrock from 346 to 370 feet bgs. Most of the subsurface sediments above the bedrock can be described as poorly graded sand and gravel with varying amounts of boulders, cobbles, silt, and clay. The coarser-grained sediments (i.e., gravels) are interpreted to have been deposited in a dynamic high energy depositional environment of coalescing alluvial fans. They are interpreted to represent one or more of several types of alluvial fan deposits, including debris flow, stream channel, sheetflood, and sieve, that have been defined (Collinson, 1978) based on depositional process, location on the fan, deposit morphology, degree of sorting and bedding, etc. The coarser sediments consisted mostly of sub-angular to subrounded clasts of tan to gray quartzite, and gray to black limestone, and dolomites. Other rock types observed in the sediment in minor amounts included soft red to green extrusive volcanics, tan sandstones, grey granitic intrusives, and white calcedony minerals (quartz). While some angular clasts were observed, these are likely products of the mechanical breaking caused by the drilling method. Once bedrock was encountered, the cuttings became angular and of a single rock type. A graphic log was created to aid the reader in attaining a quick overview of the borehole stratigraphy and is included as part of the borehole log (Appendix C) and Well Construction Diagram (Appendix D).

Horizons of less permeable fine-grained sediments were encountered at depths of 46-55, 64-69, 88-90, 97-99, 114-122, 182-184, 261-264, 274-276, 290-293, and 310-334 feet bgs. While some of the finer-grained clay- and/or silt-rich sediment occurrences may be of lacustrine or floodplain origin, others may represent debris flows (Collinson,1978) and/or possibly stream overbank deposits.

Cemented horizons were noted at depths of 207-208, 276-284, 313-314, and 334-343 feet bgs. Bedrock is slightly weathered, light yellow-brown sandstone.

Free water from the cyclone was first observed at 336 feet bgs during drilling. Depth to water was measured at 339.61 feet below top of casing (btoc) once the well was constructed and developed. A perched water zone was encountered around 260 feet bgs and likely accounts for

the production of free water prior to penetrating the water table. The source of the perched groundwater may be the irrigated field located immediately east of the well.

3.2 GEOPHYSICAL LOG

As a secondary interpretive tool, down-hole geophysical logging of monitoring well D-12 was completed within the polyvinyl chloride (PVC) cased well following construction. Natural gamma ray (gamma) and induction electric (induction) logs were run simultaneously by RAS on December 7, 2004 using a combination gamma ray-induction tool manufactured by Century Geophysical Corporation of Tulsa, Oklahoma. The gamma and induction logs for this well are contained in Appendix C. Data validation was attained via a repeat logging run of a selected stratigraphic interval within the well. On a separate log printout in Appendix C the borehole geology has been added, and an attempt has been made to correlate pronounced gamma and induction electric highs and lows with fine-grained, generally clay-rich units and calichecemented zones. The reader should refer to that multipage printout when reviewing the comments presented below concerning the description and interpretation of the geophysical logs.

The former logging technique measures the natural gamma emissions emanating from the formation surrounding the borehole. This radiation is released from nuclei of an unstable element decaying to a more stable element. Potassium 40 is the element responsible for most of the gamma radiation detected by the gamma ray probe. This element is very abundant in a number of rock-forming minerals, such as potassium feldspar, that weather to clays. Thorium- and uraniumbearing minerals also produce a gamma ray response, but in most geologic environments, including the unconsolidated valley fill deposits at the project site, the potassium-40 isotope is most abundant. Hence, as the clay content of the sediment increases the gamma ray response also increases. Conversely, the gamma response becomes progressively weaker as the quartz content of the sediment increases. A comparison of this and other monitor well boring logs with their respective gamma ray logs shows a very strong correlation between finer-grained, clay-rich units and gamma ray peaks. Slight offsets between a gamma peak and the location of the fine-grained interval are attributed to an inability to exactly define the depths of unit contacts owing to the time required for the cuttings to travel up the borehole and reach the surface. The measurement scale of the gamma-ray log is in API (American Petroleum Institute) units, accepted as the international reference standard that allows consistent comparisons to be made between a wide variety of gamma-ray counting devices.

The gamma ray response for this well is typically below ~ 35 API units, except for clay and silty clay units, which typically peak between 50 and 56 API units. Elevated gamma readings were obtained for virtually all of the approximately one-half dozen clay-rich units logged in this well. The strongest gamma response, a peak of approximately 100 API units located at 337 - 340 ft bgs, does not correlate with any identified clay-rich units, but rather appears to correspond to a

cemented gravel interval from about 334 to 343 ft. It is posited that the cemented gravel zone may contain some clasts of Tertiary intrusive or dike rocks containing elevated amounts of potassium-bearing minerals such as feldspar and biotite. Notably, even within an individual fine-grained unit, the gamma response was variable. For example, the gravelly fat clay zone overlying the aforementioned cemented gravel zone exhibits a pronounced decline in gamma radiation between 323 and 325 ft. The inconsistency in gamma ray response is thought to reflect a change in the gravel content of this unit, and may also be a function of clay mineralogy.

The induction log measures the conductivity from high frequency alternating currents that are induced into the geologic formation, and is best suited where the formation is characterized by low to medium (less than 50 ohm-meters) resistivity values, the geologic medium exhibits medium to high porosity, and the open borehole was advanced using mud or air as the drilling fluid. Induction logging can be performed in boreholes cased with PVC, but not with steel pipe. Although the induction device measures conductivity, by convention the conductivity readings are converted to a resistivity curve when plotted on a down-hole log via a simple inverse relationship.

Three curves are shown on the induction logs that were run by RAS. They represent the direct conductivity (millimhos/meter) readings as designated by a dashed ("cond") curve on the plot, a conductivity ("ap-cond") curve designated by a dotted line that has been corrected for the temperature of the induction probe, and resistivity (ohm-meters) measurements derived from a conversion of the temperature-corrected conductivity readings that are depicted as a solid ("res") line on the induction log plot.

Resistivity and conductivity responses are highly variable, even within individual boring log units, and cover ranges from 0-80 ohm-meters and 0-120 millimhos/meter, respectively. Such variation is interpreted to reflect differences in porosity, moisture and clay content of the various sediment units identified. As might be expected, clay-rich units identified in the geologic log generally correlate with low resistivity and high conductivity readings. However, the responses are not always sufficiently higher than background to allow one to identify the interval as a fine-grained clay-rich zone on the basis of the induction log alone. The few caliche-cemented zones identified during logging show a diverse response to the induction logging. Occurrences at approximately 313 ft and 334 to 339 ft do not appear to correlate with elevated resistivity readings. Moreover, the resistivity response of the cemented gravel interval at 334–343 ft appears to be masked by that of the quartzite boulders (?) and bedrock below 343 ft bgs.

In summary, the induction electric and gamma logs appear consistent with the subsurface conditions as interpreted from the drilling response and geologic logging of the drill cuttings.

3.3 HYDROSTRATIGRAPHIC SECTION

To aid in understanding the subsurface geology and water table configuration in the vicinity of this monitoring well boring, the geologic log for this well was plotted on a straight line cross section trending largely north-south over a distance of approximately 9,000 linear feet also defined by monitoring well borings D-13 and D-16 (Plate C-4). Well D-13 was projected onto the section. The projection distance for that well is provided on the cross section. The location of this cross section (B - B') is shown on Plate C-3. Note that only cross section B - B' is provided in this well completion report, since it is the only section that is partially defined by well D-12.

Study of the cross section suggests that the predominantly fine-grained sediment units do not appear to be laterally continuous between the five C-series wells that lie on or have been projected onto Cross Section A - A'. Thus, the correlation of these units from borehole to borehole is poor. This is partially due to the substantial distances between them (up to ½ mile). However, even for boreholes that are relatively close to each other (e.g., C-41 and C-42F are approximately 800 feet apart), little correlation appears to exist between units.

The difficulty in correlating distinct fine-grained units is not surprising, given that the unconsolidated valley fill within SWMU-58 was largely deposited in a dynamic high energy depositional environment of coalescing alluvial fans. Fine-grained units deposited under such conditions are characterized by limited thickness and areal extent, and this also appears to hold true for the project area, in addition to well boring C-41. Many of the fine-grained silt- and/or clay-rich intervals pinch out over a few hundred ft due to a change in the depositional environment.

Another plausible explanation for limited areal extent is post-depositional erosion and sediment reworking. Channel erosion is strongly suspected of causing the substantial difference in the thickness of a clay-rich lacustrine or floodplain deposit encountered in two closely space borings at Building 600 in the Utah Industrial Depot. It almost certainly has been operative elsewhere.

There is another factor that may frustrate correlation of fine-grained units in this and other Phase II RFI groundwater monitoring wells. Most of these fine-grained units, even if they exhibit some lateral extent, were generally deposited on inclined alluvial fan surfaces sloping several degrees or more. Over a distance of just a few hundred feet a dip of even a few degrees translates into a change in elevation of up to ten feet or more. Moreover, for monitoring wells spaced a thousand feet or greater, which is not atypical for the groundwater monitoring array at TEAD, differences in the elevation of a laterally continuous unit could be on the order of several tens of feet.

As per the fine-grained units, little success has been achieved attempting to correlate calichecemented zones that occur primarily in the gravels. The same general comments presented above for fine-grained sediment deposits also apply to correlation of cemented zones. The ability to correlate both fine-grained sediment units and cemented zones between monitoring wells in the project area may be contingent upon the quality of the downhole gamma and induction electric logs for those wells.

There is an elevation drop in water level of the regional unconfined aquifer on the order of about 90 to 100 feet going northeast from wells C-31 (gw elev 4469 ft), C-18 (gw elev 4468 ft), C-13 (gw elev 4463 ft), and C-10 (gw elev 4460 ft) (all of which are located along the northeast boundary of TEAD) into the off-Depot region where monitoring wells D-12 (gw elev 4367 ft), D-02 (gw elev 4374 ft), D-13 (gw elev 4367 ft), D-04 (gw elev 4372 ft), D-06 (gw elev 4372 ft), and D-16 (gw elev 4370 ft) are located. Groundwater elevation data presented here were generated either Fall 2004 or Spring 2005. An early groundwater elevation contour map incorporating initial water level data from the first ten offsite D-series monitoring wells (Parsons, 2003a; Figure 3.8) shows the steep hydraulic gradient between the four C-series wells listed above and four of the D-series monitoring wells due to the substantial difference in the potentiometric surface elevations. This pronounced drop in water level over a sizeable area could be due to a post-depositional fault or faults in the alluvium. The thick gouge-like fat clay layer from 310 to 334 feet bgs recorded on the borehole log of D-12 may be indicative of one such structure, though more data is needed to support this conjecture.

4.1 CONSTRUCTION TECHNIQUES AND MATERIALS

The 10-inch Becker Hammer drive casing was advanced to approximately 9 feet below the water table, and the 6-inch uncased boring was advanced to approximately 33 feet below the water table. The borehole caved to 28 feet below the water table once the drill string was removed. Monitoring well D-12 was constructed inside the 346 feet of drive casing and 19 feet of open hole. Well installation occurred September 22nd through September 24th, 2004. The bottom of the well was tagged at 365 feet bgs. Two 10-foot sections of threaded, 4-inch diameter Schedule 40 PVC well screen with 0.010-inch wide slots were connected to 35 10-foot sections of 4-inch diameter Schedule 40 PVC blank casing and were lowered inside the drive casing to the bottom of the borehole. The screen extends from 345 feet to 365 feet bgs. Approximately 2.5 feet of blank casing were left standing above the ground surface.

Silica sand (16-40) was added to the annulus between the PVC and the borehole in the interval adjacent to the well screen. To help minimize the risk of bridging and to confirm that the correct volume of sand was added, the sand was poured slowly into the annulus from the surface and continuously sounded until the top of the sand interval was approximately 6 feet above the top of the screen. The sand-pack interval was isolated from upper portions of the borehole with a 5-foot thick seal of hydrated bentonite clay pellets. The remaining annulus above the pellets was grouted to approximately 5 feet bgs with 30 percent solids bentonite slurry in accordance with Utah Administrative Code (UAC) R655-4-9.4.2. A well construction diagram is provided in Appendix D.

4.2 SURFACE COMPLETION AND SURVEY COORDINATES

The surface completion was constructed on September 27th, 2004. A locking, 6-foot long, 10-inch diameter steel protective casing was placed around the uppermost part of the monitoring well casing, with approximately 3 feet above and 3 feet below ground. Concrete was used to partially fill and anchor the protective casing, fill the upper 5 feet of the borehole annulus, and build a 3-foot square by 1-foot thick pad (6 inches above ground surface) around the finished well. The concrete pad was finished to slope away from the protective casing and was embedded with a brass survey monument.

Four 4-inch diameter steel bollards were positioned around the pad to protect it from vehicular traffic. The bollards stand approximately 4 feet above the ground surface and extend about 2 feet bgs into concrete-filled post holes.

Ward Engineering Group of Salt Lake City, Utah, surveyed the well on December 10, 2004. Coordinates for the well locations are referenced to the North American Datum (NAD) 1983 Utah State Plane Central Zone and the elevation to the National Geodetic Vertical Datum (NGVD) 1929. Survey data are included in Appendix D.

5. WELL DEVELOPMENT

Groundwater monitoring well D-12 was developed using swabbing, bailing, and pumping methods on October 4, 2004. Development continued for 5 hours and 21 minutes until the turbidity of the water produced was less than five nephelometric units (NTUs). All development water was collected and contained for later disposal pending analytical results (see Section 7.3). Well development records are included in Appendix E.

5.1 SWABBING AND BAILING

Swabbing and bailing took place for 2 hours and 23 minutes. Swabbing was done with a loose fitting surge block with an oversized rubber disk, slightly smaller than the inner diameter of the screen. Periodic measurements of pH, temperature, electrical conductivity, turbidity, and comments regarding the appearance of discharge water were recorded on well development records (Appendix E). Approximately 90 gallons of water were removed from well D-12 by bailing during development.

5.2 PUMPING

After swabbing and bailing were completed, development was completed using an electric submersible pump. The pump was lowered to the bottom of the screened interval and operated intermittently at a pumping rate between 4.09 and 4.47 gallons per minute (gpm) for 2 hours and 58 minutes. During development pumping, the pump was periodically shut off and the water in the discharge piping was allowed to back-flush (surge) into the well. Pumping and periodic back-flush surging was continued until there was no noticeable increase in the discharge water turbidity. Periodic measurements of pH, temperature, electrical conductivity, turbidity, and comments regarding the appearance of discharge water were recorded on well development records. A total of 572 gallons of groundwater were removed by development pumping. The final turbidity was measured at 3.83 NTU.

6. GROUNDWATER SAMPLING

6.1 SAMPLING METHODOLOGY

Monitoring well D-12 was sampled using passive diffusion bag (PDB) sampling techniques. PDB sampling is performed without purging and involves lowering a polypropylene bag filled with distilled water to a predetermined depth. Once in place, the water within the PDB sampler is allowed to equilibrate with the surrounding groundwater for a minimum of two weeks. During this time, VOCs diffuse into the distilled water. The PDB sampler is then removed from the well and water is transferred into three pre-preserved 40 mL volatile organic analysis (VOA) vials.

Because monitoring well D-12 was installed as a sentinel well, and no detectable VOCs were expected in groundwater, only a single PDB sampler was deployed. The PDB sampler was placed in monitoring well D-12 at 351.5 feet below the top of the well casing on November 4, 2004, and retrieved and sampled on November 23, 2004. The single sample collected from D-12 was assigned sample number D-12GW001.

The groundwater was sampled for analysis of VOCs. After filling, sample containers were placed into ice-chilled coolers and delivered overnight to ASC, a State of Utah and USACE-certified analytical laboratory. Chain-of-custody forms were filled out and used to document the sampling dates, analytical parameters requested, and proper sample handling. Completed chain-of-custody forms and cooler receipt forms are included in Appendix F.

6.2 GROUNDWATER ANALYTICAL RESULTS

VOCs were analyzed by U.S. Environmental Protection Agency (EPA) Method 8260B. No analytes were detected above the reporting limit (RL) in monitoring well D-12, indicating that the eastern margin of the NEB TCE Plume (as defined by the 5 μ g/L TCE isoconcentration contour) in this area lies to the west of this well. Laboratory reports for the groundwater analyses are included in Appendix F. Also included is an analytical quality control summary describing data quality issues.

7. INSTALLATION RESTORATION WASTE

7.1 DECONTAMINATION METHODS

To help minimize the chance that non-dedicated equipment could cross-contaminate groundwater or sediment at well D-12, a rigorous decontamination program was followed. A decontamination station was constructed in the temporary UID RCRA 90-day yard (located south of building 614) that could accommodate the drill rig, drill pipe, and other equipment as needed. Decontamination of equipment was conducted with approved water from TEAD production well WW-3 using a steam cleaner/high-pressure washer. Equipment wash and rinse water was contained in a sump within the decontamination station, pumped to a frac tank labeled as hazardous waste and stored in the UID 90-day yard for later disposal following characterization of the liquid waste stream.

7.2 DISPOSAL OF DRILL CUTTINGS

Drill cuttings in the unsaturated zone were collected below the cyclone in a wheelbarrow and spread evenly on the ground around the well site. Once groundwater was encountered, saturated cuttings were containerized in 55-gallon drums and transported to the UID 90-day yard. A saturated sample was collected every 5 feet and, upon completion of the borehole, these samples were composited to a single sample and submitted for laboratory analysis for VOCs. Lab results indicated the VOCs tetrachloroehtylene (PCE) and benzene were detected as trace amounts below the RL. The drums of cuttings were profiled (#CH80421) and transported to Clean Harbors Aragonite Disposal Facility in Aragonite, Utah. The transportation was conducted under Uniform Hazardous Waste Manifest #P401 on November 11, 2004. Disposal letters, laboratory results, profile, and manifest are included in Appendix G.

7.3 DISPOSAL OF WASTEWATER

Water derived from the development of well D-12, including equipment rinse water generated following development, was transported from the well site to the UID temporary 90-day yard by MP Environmental Services, utilizing a 5,000 gallon capacity tanker truck, and pumped into a 21,000 gallon capacity frac tank.


Subsequently, groundwater extracted and equipment rinse water generated during well development and decontamination activities associated with the installation of monitoring wells D-13 and D-16 were added to that bulk container water was managed as single waste stream pending analysis to determine the most suitable disposal option.


Analysis of the waste characterization sample collected from the frac tank following its closure, i.e., after water associated with the installation and development of wells D-13 and D-16 had been added, revealed the presence of a number of VOCs (0.590 μ g/L benzene, 23.3 μ g/L ethylbenzene, 90.8 μ g/L m,p-xylenes, 45.3 μ g/L o-xylene, 330 μ g/L methylene chloride, 2.22 μ g/L naphthalene, and 2970 μ g/L toluene) that were not detected in the PDB samples of the groundwater taken from these three wells. It was eventually determined that the source of these constituents was a section of previously contaminated hose used on the MP Environmental tanker to pump purge and decontamination water from the tanker during the development of one of the aforementioned monitoring wells.

The water was designated as a F001, F002, and F005 listed hazardous waste based on the VOCs present. As a result, the water could not be processed at the TEAD groundwater treatment facility operated by Veolia Water. Moreover, because the concentrations of methylene chloride and toluene exceeded the permissible limits in wastewater for land disposal, this waste stream was profiled, manifested, and transported to the Clean Harbors Aragonite disposal facility for incineration on December 22, 2004. A copy of the disposal memo is included in Appendix H.

8. REFERENCES

- Collinson, J.D., 1978, Alluvial Sediments, in Reading, H.G., ed., Sedimentary Environments and Faces: Elsevier, New York, pp. 15-60.
- Kansas Geological Survey. 2005. http://www.kgs.ku.edu/PRS/ReadRocks/GRLog.html.
- Kleinfelder. 1998. Northeast Boundary Groundwater Investigation Report of Findings (Vol. I), Tooele Army Depot, Tooele, Utah. Salt Lake City.
- Kleinfelder. 2002. Final Phase I RCRA Facility Investigation Report for SWMU-58 for Tooele Army Depot, Tooele, Utah. Salt Lake City.
- Parsons, 2003a. Final Addendum to Phase I RCRA Facility Investigation Report for SWMU 58: Groundwater Investigation Offsite Portion of Northeast Boundary Area. Tooele Army Depot, Utah. August.
- Parsons. 2003b. Final Phase II RCRA Facility Investigation SWMU-58 Work Plan for Tooele Army Depot, Tooele, Utah.
- Parsons. 2004. Final Phase II RCRA Facility Investigation SWMU-58 Work Plan, Sampling and Analysis Plan, Addendum 1 for Tooele Army Depot, Tooele, Utah.
- Welenco, 1996. Water and Environmental geophysical Well Logs: Volume 1—Technical Information and Data, 8th edition.





AMENDMENT NUMBER TWO

TO

RIGHT-OF-ENTRY FOR CONSTRUCTION

PROJECT: Tooele Army Depot, Utah

CONTRACT NO. DACW05-9-03-0018-02

OWNER: Tooele County

Right of Entry for Construction, Contract Number DACW05-9-03-0018, granting to the Government the right of ingress and egress upon the lands of the Owner located in the State of Utah, County of Tooele to construct and maintain groundwater monitoring wells. Said access was granted for the following property described as as abandoned Warner Branch of the Union Pacific Railroad Company deeded by donation quitclaim deed to Tooele County as recorded in Book 366 on Pages 742 – 746 of the Tooele County Recorder's Office records. This agreement is hereby amended in the following particulars:

- 1. The Owner grants to the Government the right to install the well designated as "D-12". Said well will require a fifty-foot (50') radius area, which allows for equipment access. The approximate location of this well will be between the parcels described as Assessor Parcel Numbers 2-87-8 and 2-87-12, further delineated in the attached map.
- 2. The final location/placement of well "D-12" will be in cooperation with the Tooele County point of contact named as Mr. Ray Johnson, Tooele County Engineer.
- 3. Access to well "D-12" will be along already established routes surveyed in by the Government in order to reach wells "D-6, 10, and 13;" otherwise described as the abandoned railroad alignment, Tooele County right of way.

Said right of entry is amended in the above particulars only, and all other conditions thereof shall remain binding and in full force and effect. This amendment shall henceforth be considered a part of said right of entry as if fully and completely written therein.

WITNESS MY HAND th	is <u>20 th</u> day of <u>April</u> , 20 04.
County of Tooele	(6ignature) Later
47 South Main Street Tooele, Utah 84074	(Print Name)
	(Title) Chairman

D-12/13-1

GOVERNMENT ENTITY ACKNOWLEDGEMENT

I, Dennis O Ewing, certify that I am the Cleek of the
government entity named herein; and that Dennis L. Rachard who signed this
nstrument on behalf of the governmental agency, was then
he governmental agency; and that this instrument was duly signed for and on behalf of
said governmental agency by authority of its governing body and is within the scope of
ts owers.
(Signature) * 4 20 0 4
(Date)

CERTIFICATE OF ACCEPTANCE

This is to certify that the undersigned officer on behalf of the United States of America hereby accepts the rights granted by the foregoing right of entry.

ACCEPTED


(Signature)

MARVIN D. FISHER Chief, Real Estate Division U.S. Army Engineer District, Sacramento

(Date)

D12/13-2

Page 2 of 2



DIVISION OF WATER RIGHTS REQUEST FOR NON-PRODUCTION WELL CONSTRUCTION

(for wells deeper than 30 feet)

					athodic Prote	ction () F	leat Exchange ()
Applicants N	íame:	OOELE	ARMY	DEPOT				
Mailing Add	ress:	IOTE -	EO-EO	(BLDG	8)			
		DOELL AF	mr Defor	<u> </u>	DOELE, L	TAH 8	4074	
	on: MR.	LARRY /	McFARLA.	⁄ው		Phon	e: <u>(435)</u> 83	
				Ant	icipated Comp	oletion Date:	12/31/	04
Well Drillers	License No:	213	•	Pro	oosed No. of V	Wells:	/0	
PROPO	SED LOC	CATION (F WELI	S:	County	1000	51€	
NO./SQ. DISTANCE (Seet)	EAST/WEST DISTANCE (feet)	SECTION CORNER	SECTION	TOWNSHIP	RANGE	BASE	DIAMETER (inches)	DEPTH (feet)
N1000	W1300	W4	15	28	1W	SL	2	100
ļ								
								——
	j							
								
	rm or additione							
	ORY: TE	POPE TO A	CCOMPANY	16 TABLE	FOR 1	NFORM ATTO	JON PROPOS	150
weus.	··-			···········				 .
								 -
	- ·				.		,,,,,,	
	16	M.				~	-14-04	1
Signature of A	pplicant	1.00/	<u> </u>			Date	- / / - 0 /	
<u> </u>			FOR	OFFICE USE ON	LY			
Tate of Request:_				Approvat				
Approved by:		Provi	sional/Monitor W	•••				
Vater Right Numb	er (if available):_		<u> </u>					

LOCATION DATA FOR PROPOSED GROUNDWATER MONITORING WELLS UTAH INDUSTRIAL DEPOT, TOOELE, UTAH

			A STATE OF THE STA		-well location re	-well location relative to section							
	w besodard.	-proposed well location-	-referenced section comer-	ection comer-	מסט	comer-				_			
Well Identifier	State Plane (northing)	State Plane (easting)	State Plane (northing)	State Płane (easting)	North/South Distance (feet)	East/West Distance (feet)	Section Comer	Section	Township	Range	Ваѕе	Diameter (inches)	Depth (feet)
C-41	7364702	1407022	7385112	1409429	South 413	West 2406	ZE	30	30 38	4W	SL	4	390
	4 - 6 - 7 - 6	-						Í					
C-42	7365715	1406276	/36506/	1404092	North 649	E851 2187	SW	P	19 35	AW	36.	4	322
C-43	7367012	1405964	7365067	1404092	North 1946	East 1863	SW	19	19 35	4W	St.	4	320
	31,31,001	0307077	1005001	4 40 40 40	17 14	П	1	R					
\$	0/0/00/	000#0#1	/oncor)	7804041	/nez uton	West 34	00	\$3	33	MC	75	4	730
C.45	7370246	1405151	7370371	1404071	South 125	East 1076	Α×	19	38	4W	SL	4	310
C-48	7370246	1405151	7370371	1404071	South 125	East 1076	ΝŃ	19	19 38	4W	SL	4	550
	0.00												
21-0	32/916	1000141	73/0415	1409392	South 1731	East 433	ž	48	19 35	4W	35	4	400
4.5	7274874	4440608	7070446	COCOOK .	Mindle 4450	Т		*				ļ	
2	1301011	02001#1	0340707	780804	OC#1 UDON	C821 1393	200	-	3	400	7	4	300
	CONT. LOW	000000	0111111	27.27		1							
*	13/4/23	1403738	8/00/8	1404047	South 817	West 258	밀	13	13 35	5w	20	4	240
9,0	0001101	4 4004 00	******	0000077	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	-1]	ï					
91-10	B067767	1409130	/3/300//	1409370	North 1544	West 234	SE	/	7135	4W	SL	4	250



State of Utah DEPARTMENT OF NATURAL RESOURCES Division of Water Rights

ROBERT L. MORGAN Exacutive Director

JERRY D. OLDS State Engineer/Division Director

TOOELE ARMY DEPOT SIOTE-EO-EO (BLDG 8) TOOELE ARMY DEPOT TOOELE, UT 84074

July 28, 2004

Dear Applicant:

RE: MONITOR WELL#: 0415004M00

Reference is made to your request to drill 10 MONITOR WELL(S). The anticipated drilling depths will exceed the minumum regulated and reporting depth of 30 feet. thereby requiring permission from the Division of Water Rights to proceed with this project.

The specifications outlined in your well project request dated July 28, 2004. State Engineer's requirements and permission is HEREBY GRANTED. Therefore, this letter is your authorization to proceed with the construction of the well(s) in accordance with those specifications and with respect to the following provisions:

- Small diameter casing is to be used in the construction of the well(s) and no more water is to be diverted than is necessary to determine the quality of the ground water by obtaining representative samples as required by the project.
- 2) The well(s) must be drilled by a currently licensed Utah driller and must be drilled in a manner consistent with the recommended construction standards cited in the Utah State Administrative Rules for Well Drillers.
- The enclosed Driller (START) Card form must be given to the licensed driller for his submittal prior to commencing well construction. The other enclosed form is the Applicant Card. It is YOUR RESPONSIBILITY to sign and return this Applicant Card form to our office upon well completion
- 4) If complete information is not available in the initial application, it is the APPLICANT'S RESPONSIBILITY to provide, upon completion, descriptive locations of the wells referenced by course and distance from established section corners. e.g. North 565 feet and West 1096 feet from the SE corner of Section 35, T25, R5W, SEB&M.
- At such time as the well(s) are no longer utilized to monitor ground water, and the intent of the project is terminated, the well(s) must be temporarily or permanently abandoned in a manner consistent with the Administrative Rules.

NOTE: Please be aware that your permission to proceed with the drilling under this authorization expires January 28, 2005.

Sincerely

Regional Engineer 1994 West North Troupe, Suite 220, Po Box 146/90, Sait Lake City, UT 841 14-6369 telephone (801) 538-240 - Gesmale (801) 538-7467 - were waterrights with gas

luintana, for

APPLICANT CARD for Monitor WELL#: 0415004M00

IMPORTANT: THIS CARD MUST BE COMPLETED, S	IGNED AND RETURNED BY THE WELL
OWNER/APPLICANT AS SOON AS THE WELL IS DR	ILLED BY A LICENSED UTAH WATER
IWELL ORILLER.	i
OWNER/APPLICANT NAME: TOOELE A	RMY DEPOT
MAILING ADDRESS: SIOTE-EO-EO (BLOG 8), TOOELE ARMY DEPOT, TOOFLE, UT 84074
PHONE NUMBER: 435-833-	3504
WELL LOCATION: You are	authorized to drill 10 Monitor Wells. SEE BELOW.
WELL UIM COORDINATES:	
WELL ACTIVITY: NEW REPAIR	() REPLACE () ABANDON ()
CLEAN () DEEPEN	()
WELL COMPLETION DATE:	
NAME OF DRILLING COMPANY/LICEN	SEE:
Owner/Applicant Signature	<u> </u>
Owner/Applicant Signature	Date
SAACOMOLETE SIGN AND DETUDN THIS CONTIAN	INONE CTUAL MELL COURS CTYON
****COMPLETE, SIGN AND RETURN THIS PORTION	THEO WAS MUCH DEFINAL AT
<u> DO NOT GIVE THIS CARD TO LICENSED WELL DR</u> STATE OF UTAH DIVISION OF WATER RIGHTS Ph	OND NO. 901 E29 7416
	Fax No. 801-538-7467
	F 6X 110. 001-330-7407
COMMENTS:	
	· · · · · · · · · · · · · · · · · · ·
MONITOR MEN LOCATIONS	
MONITOR WELL LOCATIONS:	
(1) N 1644 W 234 from the SE	corner, SO7 T 3S R 4W SLBM
(2) N 1456 E 1355 from the SW	corner, \$17 T 3S R 4W SLBM
(3) N 649 E 218/ from the SW	corner, S19 T 3S R 4W SLBM
(1) N 1644 W 234 from the SE (2) N 1456 E 1355 from the SW (3) N 649 E 2187 from the SW (4) N 1946 E 1863 from the SW	corner. <u>\$19 T 3S R 4W SLBM</u>
	59 (A)
(6) S 125 E 1076 from the NW (7) S 125 E 1076 from the NW (8) S 413 W 2406 from the NE (9) S 817 W 256 from the NE	corner, S19 T 3S R 4W SLBM
(/) S 125 E 10/6 Trom the NW	corner, S19 T 3S R 4W SLBM
(O) S 413 W 2400 Trom the NE	corner, S30 T 3S R 4W SLBM
(10) N 2507 W 34 from the SE	corner, S13 T 3S R 5W SLBM
(10) N 2507 W 34 from the SE	corner, S24 T 3S R 5W SLBM

DRILLER (START) CARD for Monitor WELL#: 0415004M00

IMPORTANT: THIS CARD MUST BE R	ECEIVED BY THE DIVISION OF W	ATER RIGHTS PRIOR TO
THE BEGINNING OF WELL CONSTRUCT!	ON REQUIRED ONLY FOR WEL	LS DEEPER THAN 30 FT.
OWNER/APPLICANT NAME:	TOOELE ARMY DEPOT	
MAILING ADDRESS: SIOTE-EO-E	O (BLDG 8), TOOELE ARMY DEPO	T. 100ELE. UT 84074
PHONE NUMBER:	435-833-3504	
WELL LOCATION:	You are authorized to drill	10 Monitor Wells. SEE BELOW.
WELL UTM COORDINATES:	DEDATE / DEDUTE	() ABANDON ()
WELL ACTIVITY: NEW CLEAN	DEEPEN ()	() ADANOUN ()
PROPOSED START DATE:	9-1-04	
PROJECTED COMPLETION DA	TE: 8-1-05	
LICENSE #: 626	LICENSEE/COMPANY: LA	YOR Epristenten Co
T X	•	3-29-04
	<u> </u>	
Licensee Signat	ure	Date
NOTICE TO APPLICANT: THIS CAR	IS TO BE GIVEN TO A LICENS	ED UTAH WATER WELL
DRILLER FOR HIS SUBMITTAL PRIOR	TO WELL CONSTRUCTION.	36
STATE OF UTAH DIVISION OF WATER	Fax No. 801-538-74	4D
	F4X NO. 801-336-74	
MONITOR WELL LOCATIONS:		
7 33 N 16/4 W 23/ from	the SE corner SO7	T 3S R 4W SLBM
-/ 2\ N 1456 E 1355 from	i the SW corner. SL/	1 35 R 4W 5LBM
(3) N 649 E 2187 from (4) N 1946 E 1863 from	the SW corner, S19	T 3S R 4W SLBM
(4) N 1946 E 1863 from	the SW corner, \$19	T 3S R 4W SLBM
≯(5) S 1731 E 433 from	the NE corner, \$19	T 3S R 4W SLBM
(6) S 125 E 1076 from	the NW corner, \$19	T 3S R 4W SLBM
(7) S 125 E 1076 from	n the NW corner. 519	I 3S R 4W SLBM
(8) \$ 413 W 2406 from	the NE corner, \$30	3S R 4W SLBM
(4) N 1946 E 1863 From (5) S 1731 E 433 from (6) S 125 E 1076 from (7) S 125 E 1076 from (8) S 413 W 2406 from (9) S 817 W 256 from	the NE corner, SI3	T 35 K 5W SEBM
(10) N 2507 W 34 from	n the St corner, 524	T 3S R 5W SLBM

Well Log


WELL DRILLER'S REPORT State of Utah

Division of Water Rights

For additional space, use "Additional Well Data Form" and arrach

Well Iden	tification	īŢ	VI -										
	Non-	Pr	ođuc	ti	On	1 9	Мe	11	:	0415004M00			WIN: 30271
Owner	TOO! SIO! TOO!	ELE CE- ELE	eo-e arm	TY O	DE	BLI EPC	DG DT	: 8	;)	G P	Palaca Ri	ichard A	lirik / Parsons
Owner Note to be because TOOBLE ARMY DEPOT STOTE - PO - DO (BLDG 8) TOOBLE ARMY DEPOT STOTE - PO - DO (BLDG 8) TOOBLE ARMY DEPOT TOOBLE TOO ARMY DEPOT TOO TOO													
\$ 1731	E 43	3 £	rom	th									
		on: (, ground elev	ration, local w	ell#) D-12
Drillers A	ctivity] _											
Check all di If a replace	nat apply: ment well	, 610 (1)	≦ New vide lo	cati	JR ion	of	nc	w w	De ell.	epen L Clean L R	eplace Pul	south and	N/A feet east/west of the existing well.
		I	ORE	HC ET)LE	E L Gir	n)	:		DRILLING	METHOD		DRILLING FLUID
						- ,-			Рe	rcussion H	ammer		N/A
							-						
DEPTH FROM	(feet)	1]		CLAY	S L T	SAZO	GRAVEL	COBBLES	TOTHER COLUMN	CONSOLIDATED ROCK TYPE	COLOR	grain com consistant	tive %, grain size, sorting, angularity, bedding, aposition density, plasticity, shape, cementation, by, water bearing, order, fracturing, minerology.
	 	Х		┿	Н	\vdash	Н	H				BEDROCI	C (SANDSTONE) FROM 346 to 370
·····				-									
				-			_		+				
												•	
Methor	of Water	r Le Wate	vel M	/el l	Ма	:45	urd	t	nt v	Loyel 336 WLI was Referenced G	If Flo	Flowing? Distributions of the National State Flowing, Capped Flowing, Capped Flowing Flowing? Distribution Flowing Flowing	Pressure_N/APSI Elevation_N/A

Construc	tion Info	emation									
DEPTH	(fect)			CASING			DEPTH	(feet)			OPEN BOTTOM
FROM	то	M	ASING TYP AND TERIALIGE	B LADE	WALL THICK (ip)	NOMINAL DIAM. (m)	FROM	TO	SCREEN SLOT SIZE OR PERF SIZE (in)	SCREEN DIAM. OR PERFLENGTH (18)	SCREEN TYPE OR NUMBER PERF (per found/interval)
0	313	4" Sch	. 40	PVC	40	4	343	363	-010	4	Factory
				<u> </u>				ļ	ļ		
		ļ <u></u> -	•								
											1
	т Турс:	Flush 1					_ Perforator		N/A	Pon Provided? 🖺 Yes	i ∐No
		stalled? X Ye Placement Me		Tremie	-	Surface Seal:_ onite I				oe? ∰Yes □No te Grount	
DEPTH	(feet)						RVAL SEA			ACKER INFORM	ATION
FROM	то			MATERIAL CKER TYPE			<u> </u>		y of Material Used if applicable)		DENSITY mix, gal/sack etc.)
0	334	Bento	nite	Grout				102	Bags	50 lbs	each
334	339	Bento	nite	Pelle	ts			6	Buckets	50 lbs	each
339	363	16-46	Sil	ica Sa	nd	.	·	16	Bags	50 lbs	each
	-	-		· 		<u> </u>				•	
								1			
Wall Day	elonme:	nt and Well	VAL T	act Inform	ation	<u> </u>		<u>.</u>			
THE ENGLISHE	Cropine	at and 11 cm	71010 1	Cot Hindi Mi					Units	DRAWDOWN	TIME
DA				METHOD	<u> </u>			YTELD	Check One GPM CPS	(ft)	PUMPED (hrs & min)
	^N	/ A									
		<u> </u>	<u></u>								
Pump (P	ermana.	ne)		,							
Pump De				· 			Horsep	ower:	P	ump Intake Depth:	fæ
Approxi	nate Ma	ximum Pum	ping Rat	c:			_ Well	Disinfec	ted upon Com	pletion? □Ycs □	No
Commer	nts	Descripti Circums	on of con- ances, abo	struction activ indonment pro	ity, addition ocedures. (nal materials o Use additional	sed, problem well data for	s encounte m for more	red, extraordinar) r space.	,	
Well Dr	iller Sta					a under my sug ct to the best o			applicable rules as	nd regulations,	
Name_I	AYNE	CHRISTEN		-				•		626	
Signatur	ė	(<u> </u>	1				_ r	oate Februa	ry 4, 2005	<u>; </u>
				(1- Mind Well II	nDer:						



	1
	Wednesday, September 1, 2004 weather: clears 750 work
8:00	The state of the s
8:30	Richard Jurik (Passous PM) arrives. They have readed
	part of Building 614 for an ourite office. We discuss
	'' ' '' '' '' '' '' '' '' '' '' '' '' '
10:00	We begin the project kickoff needing. Attending
	parties are de microt meeting. Attending
_ 	Richard Junk)
	7 00 77 /
	Jill Thomas
_ <u></u>	Kurt Alloway
· · · · · · · · · · · · · · · · · · ·	
· · · · · · · · · · · · · · · · · · ·	/ I
	Larry Mcfalono TEAD
	DefenRay notes 11
	Double Sablin UID
	Don Yea 11
	Tom Kearn
	Mike Wyumill > Layre Note Solazon
	D C T
	Richard Turk conducts the meeting and goes over
10120	worker and the sile therether single Plant
	The two was Discusses taken the till a Call
	The party of the second policy of This is
 - i	THE CHECKING CHECKING THE
	mechanism promised ine took and
	carrying Diet att site and min
•••	
<u> 10:30 </u>	Jest Bigelow Disquises utility clearances
	The contract of the contract o
	The state of the s
	The state of the s
	project for the tevent vensetter Lavry of farlance
	The state of the s
10:40	
	and pirections to the hospital for creas or
<u></u>	- Cocas or

9/1/04 Donesanny September 1, 1901 B i statt lurry, arvive at 20 MP to prop for bickets tredible, dead Bigalows Cassons consight. 2720 Richard Jurik Parsons PM arrives, They have vertich part of Bornaing with the one section office. It because the more plan amo will health our salety plan. Directions to site for five per or ampulances Jessie says to give them Bavenue out Jape Street as an appress. Larry says use northeast of the old city lambfill. 11:20 Meeting abjourns we walk over to the venty constructes 90-Day area cut inspect locations of the yel to be constructed D-con pas. Crew is waiting for the plastic liver for the Decon pap to arrive in shipping 13:30 Crew returns to SLC to prepare vig for mob to site. Some muon repairs are ongoing. I hear to SLC for another project untill I hear other wise 15:30 Tour Kearn calls to say mob will occurre
tourorrow. They hope to be ready to prell by 8:00 - I will need them at the ving

Wat (....)

weather: overcast ~65° was Thursday 9/2/04 8:00 lawruse at site Rigis ousde mad is up Crew is reasy We call TEAD public works and avoninge to orect Gary Polaski is Water Well 3 ad 8:30 to full towles. We port veer water to pull by Pichaso thinks it vessicary for fire protection 8:30 At well 3 Jest Hannamy (U.S. Filter now Veolia 9:00 We are full, We has Health and Satisfy tangote while waiting for water, Several topics overes See signip sheet Borehole vame is D-12 9:30 Back et vig Begin Dulling Richard Junik ousile 9:40 Jest Bigelow onsite l'explain how I believe Carl Cole wants logging to occur. I have callers time and he will be auside shortly 10:30 @ 35' bys Carl arrives. We shull Down wig briefly to pisques logging soils. It is agreed we will collect sample every 5' in a bucket lay piles on plastic, archive a qual baggie. from each to retain moisture contest Crew (Note Salazar) will collect buckets Richard and Jeff will log Details accombing to ASTM methos so Data is easily transferred to squelies Dalabase The cyclone because this gives the most across interpretation of soil horizons as they are excountered. When Richard, or Jest are vol onsite I will log ASTM Detail from bags after Drilling or as role of penelvation slows.

11:02 Resume Drilling Carl returns with USACE borns log paper to use

11:47 Larry Mertanlan and Dean Reynolos avsile

12:05 @ 90 a rock is logged in anolus of brill pipe 12:35 Resoure Doulling 12:43 @ 100' Crew shorts Down to go construct D-con Pap. Jell take them over. Picharos & 1 continue 13:15 Jell vetures. He and I and Richard go to look

at site of vext hole - D13.

14:05 We redune to site. Richard will go observe construction of Decon pap. I will continue logging

16:10 1 prive to Decon pap. Crew is vearing

16:30 / Drive to topele to get a room and work at a Desk. Richard is off over the vext week. Tell is off tomorrow. I will meet even at 7:00 am

With law glason

Wallung 9/3/04

	F.
7	Car (5-13)
Tuesday Sept 7,2004 weather: patly downy cool, wwo words	and market
07:00 1 wrowe of D-12	de la company
07:10 Crew (Tom and Node) arrive, Carl Cole arrives also	NAGGS - No.
07:15 Mike corrues with oven truck	
07:20 We have His Stanlgale Topic: PPE in the saturales zoup	Total of the Baseline
Pruchpoints moring Drums.	₩.ZZCV**
07:15 Carl asks about Big INSpection Checklist I have a	مات مواد ، المراد
for Tom hors laynes for We look at both I will use	A SA SALANIA
mine. We inspect Live extinguishers. Rig's Steam	Sales for
cleaner are good. Duillers Truck ove veens charge	and substitutes
I vote this on low is tell Tom We check other	in a Structure
Items, I will check peapman ovce rig is warm	47.67.67A
7:45 Beque Drilling Carl leaves sile. I enech exclusion	the Court Court
zone and begin logging soil (@ 210 ft bgs)	essent to
9:45 @ 230' bgs. Jeft Bigelow ousite	TATION AND A
9:35 Carl cole back ovside I have gotten most recent	enischen Wit
water (evels from Jeff Haramann () ans	скаран
Carl has brould the ground water monel report	A) SERVICE
so we are able to pisques likely water level	ราชเลกมู่แห้
- Long en	NATIONAL PROPERTY.
10:45 @ 250 ft we are out of casing. Tom has asked layue to believe by 10:00 bit they are late	(a)-endState
layure to beliver by 10:00 box they are late	S. Recognitive A.S.
11:10 While waiting crew is servicing rigs and	desired and
Discover a crack in the rapiator overflow	one transfer
(1 thought I has smelles glycal) They Dissasemble	Paragine Ma
replator and Tom heads to shop. I go to	THE PROPERTY.
Building 614 to Do loggs and farms	
13:10 Tou calle to let me know he will repair	
rapiator and return and install it but	
thinks it unlikely he will ovill more to may	
I call Carl ? let him know. He is bringing an	
excavation permit to me here I will bo other	
work here we case though go well and porling	2,000
can commence to Day.	
- HILL Carl cole visits Bularay 614	Ů,
14:30 Carl leaves	1
15:30 1 go to D-12 to check progress	100

9/7/04

16:10 Tom has returned with vapidlov and is beginning wistallation. I hear back to building 614 then to SLC

What welg/s/on

•	Wennesday Sept 8, 2004 weather clear (4500)			
	:			
7:00	Laverue at sive Luce is just arriving			
	Jell Thomas is onside			
7:10	We have His Topic Cyclore Kazaros			
	We no sie were Very Fre en Very			
	Techanos suce select will chem I'll			
	the everceuse elitate for the mis			
7:30	We so rig inspection. Five extinguisher is recharges since yester say We show Jey He every shotoff for the rig. Begin soulling @ 250			
8:45	Jeff Bigalow ousde. @ 276' we hit /mestone bouldan			
9.02	Most shot Down - the hammer head is too hot			
9:14	Drilling Cacin			
1 0:38	The metal sleve to which the pischarge hose			
	attaches to the hommer hear has broken off.			
	We are @ 274 1/2 w concerter gravele and moving			
	very showly I am priving back to Park City to			
	to some water sampling. Crew will call when			
	viq is ve paived and can only again.			
01-1H	Tom Kern calls. He has part repaired and is			
	heading to TEAD			
15:00	1 arrive at D-12. Coeus begins porthing			
16:10	Carl Cole ousigui			
<u>(6:30</u>	Henr & Rig too hot. We guil for Day of 279 bgs			
	Hear & Rig too hot. We guit for Day all 279' bgs - still sulling come step gravel-mostly limestone-very hors			
16:48	All homos leave side			
	\			
	<u> </u>			
				
	<u> </u>			
 	Man July 9/8/04			
				
	<u> </u>			
				
				
				

```
weather Glear (40-75°)
am: No WIND PM: 15 mph to S
      Thurs Sept 9, 2004
7:03 / aurive d' sile
7:05 Crew arrives. We have His Harlgare
      Topic: Issues vaised by Jell Thomas at her
7:20 (vew fills fluins i warms vig. 1 00 paper
       work and exect an exclusion boursey to
       the south so even can can and Drivk somewhere
7:35 Begin pouroing 6 279
8:35 Carl Cole owsight. We visques option (1.e. changing
      bit or Drill) Crew toes not have a spare but avoite
      We have make some progress v4" since 7:35. Must
      remain patient.
 8:50 Hear is hot. Hugh shot rows to cool. (and leaves
       Duilling again
       Head hot @ 280
10:15
       Begin Drilling
10:45
       Fuel live broken at 280'8" -
11:35
       Begin Drilling again
12:10
      Head Hot
12:35
       Begin Again & 282.5
12:44
       @ 283.7' coment ends - Speed increases Dramodicolly
12:56
      Jeff Bigelow onsight
       290! Slight moisture on sand around cobbles - Will
13:20
       watch closely for water
       € 310 we enter clay layer - No water
15:00
       & 321 still in growdly day Carl Cole onside - cuttings
16:05
       of clay have many angular fraquents and possible
        Slickenscoes. Structure in clay is very convolutes.
        Possible fault gouge ou turbindy current deposit
       Carl is going buck to office for some w. c. into
       Injector on my is shooting small flame. We shot Down
16-30
       for repairs,
          leave sole. Even working on viq
10
       Carl Calle with these w. L. elevations D-2 4374'
         C-18 4465.12, C-13 4460.42
                                        atalland 4/4/04
```

	i	
	<u> </u>	Friday Sep 10, 2004 weather Clear (450-
	- 	au: wind to s (smple) pur:
	6:45	1 arrive at Building 614 to got PID & chip trang
		Jeff Bigelow arriver. I hear to D-12
		Come is ouside we so vehicle inspedious (Jeff
		Does checklist) and have His tailgale. Topic : Haraus
<u>-</u>		w the solvedes zove
	1:35	1 go to calabrate PID but it weeps charging. Jell
		rous it to 614 (vew is working on injectors on
		homover hear aux Dowg gasolive run to Toole
	\$:00	I call Christian Davie (Layor) and Disgues well
		oraberial (010 sloteseveen, 16-40 sano, scheoule 40 PVC
		as all specifies in the SOP) He is also severing
	···	out 100 ft more pipe. We have only 24' left
	9:00	Begin or Ming of 323 ft. 1 checker water level - bove Dry
		330 ft. Carl Côle calls for an uprode i leaves message
	11:35	@3364 Carl calle 1 tell him the story - Perhaps
. —· —		we are puilling Down Dip on a fault gauge
		Shear zone? Barry Pober conwer with more pipe
	13:30	@ 347 Jell Bigelow ovsight with borny logs to fill
		in pullers report
·		Crew has been poorning on a quantzite since 348! Crew has been poorning on a quantzite since 348! Crew has been poorning on a quantzite since 348!
		has become around the poul string. They pull back over 30 feel befor it is a bil looser
		has become around the poul string. They pull
		back over 30 feel befor it is a bil looser
_		This is just above the clay layers upper contact. It must be swelling in the borchole
		contact. It must be swelling in the borohole
<u>-</u>	6:05	I take a water level from the open hole
		W. L = 340, 0 ft bas 1 sours bottom at 344.2
		It bgs. I have felt we may be in saluraters
		zone but formation was too tight to create
		enough water to make it to surface in the
·	···· · · · · · · · · · · · · · · · · ·	heater high velocity airstreams, we seeme to
-		rises significantly over the weekens. The
		rises significantly over the weekens. The
<u></u>		formation has became so harm to penduate
Ā. Notaras		

That either a new bit or a change of Drilling systems has become vessisary so we will hope water comes up enough to set well in the existing hole lower heapon rasing to secure 16:20 As I leave site I phone (and (ale to pass on this into. We will take a new w.l. on tronpay worning to before how to proceed.

Walf burg

. .

31

Monday 9/13/04. weather clear (2400)-(450) WIND 5-10 mps to NW 700 I awwwe of site. Crew calls-they will be Kehrlide 7:35 (vous arrivec. Begins finding vic, We have His Topic:back yours. 7:45 Toff Bigelow ousle - He lables owns 8:00 Carl cole ousigled. Even lives up vig aus lists hammer off od pipe so we can take w.l. Water savarer at 336.4 ft bgs. Bottom or hole 15 344. Z. We have 7.8 ft of water Just 3.6 appitional feet Since Friday night at 16:00. We will go back some hole with 30' of casing removes 8:50 Begu repulling the last 30 ft of bole in hopes of reasuring out some of the clay's comed. We are us solvales zone (=) I calibrate PID at 1026ppm on 100pp Back on bottom howmen, eg. Cuttings lifting from 388! 11:50 Crew shorts rown to eat & let hear cool. We have Durles only 6 males since 9:20 (2.5 hours) Some cuttings collectes monde fractures quartele with well healer tractures with aithbrevic calcite (Seems like benrock). We have generated about 1/3 55 gallow orm of cutting, and water. Begon onling again, Jell is going back to Forsons office as por Richard Jurik who is back from vacation He leaves me har waste lables and who and cooler's ke far waste charederization composite sample. SOP alls for I sample per 5/H in sodurates. zone compostes one hale reches total depty. He also leaves lock ikeys for prom Evenstrute Down vig Ue have vouler au appillonel 8 souce 12:40 (2.5 nos) Tou calle back to Layare, Tim Stein (cayne) asts that I call how. Tim suys so more havemeres . It Is how or equipment we should ODEX this hole when a vig is available mo more to a new hole with the hammer

15:30 Can Cole ousite We look at cottings and take a water level after even pulls
30 feel of casine to simulate same condition as early en water Level measurents
WL = 337.2 We monthar rise. First inch of recovery we saw so see the series

we will so we know well is recharging though slowly. I call Richard Junk and explain the situation. He believes I can leave site & westructorillers to pull casing out of hole to inspect bit consitions.

of hole to inspect bit consitions.

16:05 Crew 18 having to hammer & stocke casing to get it out — very tight. Tom went phose me at the end of shift with progress report

Wallaus 9/19/04

TuesDay 9/14/04 weather - clear (40°-70°) am: wind 5-10 mph to the S 7:00 I call Tom on my way to Depot. He says they we able to get only 60 feet of orll pipe out of hole. It is requireful hammering and stroking because it is too tight. 7:35 1 avrive & D-12. We have His tackgode. Topic Vehicle movement and savety 7:50 1 DO vies inspection and hear to building 614 8:00 Jell Thomas arrived while I was gove . She suggests asourne exclusion zone in and purllers vehicle She also wants out house moved out of exclusion zone. I call "outback Shack" to move RON Brewit 0-913-4926 Cell 274-0074 She is also wanting a separate vehicle inspedior checklist for each vehicle and to to some autro pecible mondoring to see it a secous self of head phones is messissing proms to be replaced with prime without 9:30 1: 90 back to 614 to make copies 10:05 Back of she Crow has pulled all but 60 H of casing I have them wash cuttings from cattle tank who Down and put Down on a pallate and steam clean origina Jell back 11:10 Last section of casing out of hole. Bit is pull Crew was another bif on the way. They go to got luck 1150 1 take a wither level at 263.5 11:55 1 check again - 263.5 Crow is here to pour out to let aux move it 12:03. I go to get well Jill Thomas well stay onside to secure open borchale 12:40 Back at site layare guy has pelivered new bit I give he and July todays His Stopic

9/14/04 (00) 13:50 1 again take a worler level - 263.8 Abqs I call Richard and Carl with this info Is if pearches layer confined layer or regional weder fable? We will lower vew bit and casing pownhole to evacuale aux check recovery Carl will be overte with group around 230 and woold like a goick sketch to show us dows, I get to brancing 14:30 Drawing complete. Crew is having to hammer in which of casing. They have 100 ft soon hole. 14:50 Carl Cole orsite with Many Ellew Mckerzie, April Fortuine, Larry Mctarland, and Helge Gebeurt (UDSHW) are overle. We disquise the lithology and hydrology of D-12. Helge uspects drum; labeling. 15:35 Visitors offsile quew is bown to 140 ft 16:00 Jell Thomas offsite 16:20 Carl back to returne boring logs and sompléties praving to fax to Richar Jurice 16:40 Crew is Down to 200 ft. We guil here we sound water at 258.3 ft by s. Hole 15 causes to 263.0 ft. HOS All homes offede

Waxland

	1	ŧ	
· .	Wenvesnay 9/15/04 weather clear (35°-70°)		
	wino suph to ww		
6:30	1 curvive at bulbing 614 for 100 ; copies		
	I arrive at D-12. Richas Juvit calls		
ţ	Mike would arrives with well anotherials truck		
	Tour calle and says they are running late as they	•	
	are loaning pipe truck for the Scrawing		
4,50	for actives, they warm the and the thirds while		
	I so vig cospection We will so His Stackede		
	once vale avvives with pipe truck.		
1:20	We lift hear of pipe and take a water		
_,	level. 258.03 H. Crew lowers remaining		
	Pipe Down hole This fills or we from gestioned PARENZO42570	<u>) [</u>	
9,40	260 ++ W. wele. Even sels up cattle tank		
	& Drum to collect cuttings		
10:00	Hammer wont start. I calibrate PID while		
<u>.</u>	crew tries to effect repairs. PID weaps 1016 ou		
	100.0 ppur isobitelyne		
10:50	(ven can't get hammer going Tom calle shop, We		
	have His targete while waiting topic: Drum litting		
11:00	Hammes ouvering. @ 263' making cuttings		
11,21	+ ***		
	280 1st Drum town full PARSNZ042590;		
	295 200 02		
•			
_	300 1310 3 rd 11 11 11 03		
	- 270 th		
	- th	•	
	9 330 5 11 11 11 11 10 06		
	345 7 11 " partially full " 07		
<u></u>	We lock and label all overing The Schron ODEX		
	Dorl has arrivers. Carl Cole also overle Crew		
	moves Becker Hammer off hole		
15:2	Carl Cole leaves sile		

William 9/15/04

9/15/04 (cont)

16:10 Crew is moving the Schraum overhole. We are using this ODEX DULL because it is vioce likely able to penetrate the boulder of quarterte! or bedrock layer at 346 At b.g.s. While N appears we are neep evough into the sobrates zone to set a well, the internation as to the Depth of the beprock is posines by USACE. We will prell 10-15 feet and it all cultures appear to be augular fragments of the same rock type we will assume this to be bedrock. Because the hole manc so little water while reentering the wride of the Drill casing is coaled in sticky mud and we have been mable to get the water level mèter Down the ho'le so no information has been available since receivering. Because the ODEX system is a Down hole however at the end of casing that fits tight water levels until it is removed and the 10. casing is pulled off bother some Distance 16:30 1 leave site. Coen will secure open hole with steel plate

It at hur gliston

	19
	Thurspay 9/16/04 weather clear (40-750)
	4 W : AM 10 M
07:03	Larrive at site Schraum vic is over halo
	Bob Hypelman (lave) will be fill we in for
	Mike Wound topas so I do over the SSHSP
	Bobty selvan (layre) will be filling in for Mike Winnell topay so I go over the SSHSP with him and have him sign the plan acceptance
02.40	This Schramm is new to site D-17 so I Do the Darley une suspection on it. Emergency shotoff switch is opperational We have tailed His Topic: Schramm Harrards Carl Cole onside
	the Darley one wspedion on it. Emergency sholl
	switch is opperational
08:00	We have tacked His Topic: Schraum Hararos
	Carl Cole ousile
08:10	Jeff Bigelow ousde with IRW manifests and instrudious
	for Drum removal expedes to occur later
	Tell Bigelow ousde with IRW manifests and instrudious for Drum removal expedies to occur later topay (~4:00 pm)
8:20	Crew has to reposition vig to get hammer. Down hole Carl leaves site to get government truck i handled
	Down hole Carl leaves site to get government truck & hundred
<u>9: 65</u>	Degra lowertug haven and roos Down hate 20 ft
	sections of vos. The hammer O.D. is 53/4" The
	ros O.D. is 4/2". The 10 of the inner wall of the
	Becker casing is 6" The o.D of the Becker:
	casing is 9 inches
-9:15	Carl is back overalt Richard Jury & calls to
	Disques how peep we plan to proll to belenning
	It hale is in beauact.
10:20	Drow #7 back who cattlestoning
	Drow #7 back wto cattlestward
0:25	Begin Dvilling 6 346
10:50	356 - all cuttings were angular class of samps your with
*** · · · · · · · · · · · · · · · · · ·	wear lete surfaces showing from oxide and some managuese
*	Land is satisfied we are w bedvock
11:10	Crew breaks for wade I call Richard with uppale
	Carl Makes some calls. I cover & bolt Drum PARSNZ0425907
11:40	Can has indicated we interest to pull open system out
	of hole then back fell beprock zone with sour
	and then make a bentonde seal in the decimant
	that goes from 310 to 346 feet Crew has 7 buckers
100	A second of the

of time released bentovite pellets ousite This will make about 10 feet of seal in a 9" hole

11:45 Craw begins pulling ODEX out. Cont goes for

1338 ODEX out of hole. We try to take W.L.

but to sounder sticks to must on sidewall

egain. Crew suggests that once we stail

pouring sand down hole the problem will

go away. Crew stails disassembling cyclone

§ toolog to more Schramm of hole and

put Becker back on.

14:20 'Crew unable to get sufficient air pressure to the roo truck to move it. They Discover bose has detatched under the bed. Crew effects repairs

15:40 (all Cole onsite Hose repairer, Bob moves Schramm off hole and leaves sele with vig.

16:50 | Drue to UID office to escourt
MP truck to site to load Drums
for transport to 90-Day yard

16:00 Back at D-12 c rew has briver Drum truck to the eage of Roogers Road where the will boom Drums onto lift galling MP truck. Nale handles clamp Tom operates boom. Darrel (MP Driver) unclamps on truck and Dolly's them inside Larry Mafarland and Dean Reynolos (TEAD) are onsile to will ness and sign manifests. There are 8 Drums total. I estimate weight at 4800 lbs. All are soil cuttings with a trace of free wider PARSNZO425701. and PARSNZO425701 thro of I Direct trattic on narrow roadway while crew operates. Larry looks over Manifest and signs.

9/16/04 (cont) 16:45 Truck is loaded Daniel Clayer signs manifest # P4006 our takes it with him surrive transport He placeups truck & we hear to 90 pay 2 per pallate, seperating pallates by 3 ft and facing lables to the outside Dollying Divines Difficult on the unever olo asphall brug buillers boom true unloading Danel has me sign loading ticket # 5/6824
14:20 All parties take copy of signed mandest and
we leave 90 day yard and lock gale. I go
to 614 to complete paper work for an uppate we will set well tomorrow

What lung

9/17/04 Friday weather (rear (40°-75°) an wwo completo ww 7:04 I arrive at D-12. Tom call's to say they are vouving late as they has to loss appitional maderial to backful the hole bottom. Richard, Carl and Mary Eller and have agreed to some well from bottom up to 320 ft where we are is appear fat clay zone and they set a 10 foot seal of time realeses bewlowthe pellets to cover 320 to 310 bgs. We then will screen gravel soves from 310 to 290. 7:45 Crew ownwes, Patrick 6 Mc Gamon is Lilling in for Mike Winnell to Day so I go ylur the SSHSP (Appendix 6 of the workplan) with him and have him sign plane acceptance form. We also have tailget His S. Topic: litting basards from Sand bags. Over borehole. I try w. L. bit it is still sticking 8:30 Carl bole ousigled. He asks about a beorack W.L. lexplain the problem but orllers believe a few bags of sano power hole will allow for it. Carl is concerned the same well slug the water and cause some displacement So we should give it some time to equilibrate Comes is struggeling to get oug back over hole They have no room for error sipe to sipe and ground is very unleave. Cal leaves site. I do rig inspection of Becker Hammer ours anxillary compressor while they try Rig is finally liver up on bovelola. Com 9:20 prepures to sows backful to 320' bgs

After apping I bay of colorabo silica (16-40) 50lb by we are able to get the tape Down. W.L is 336. 2 bys 19:50 Crew sets to pull some casing

9/14/04 (cout) 10:30 15-50 16 bags in hole, Sound top of soun @ 332' 10' of 6" hole 14' of 9" hole 10:45 9 - more bag . Sound top of sand @ 320.5 10:58 We are I bucket of Time releases (TR30-5016) Bentouse pellets. They bridge 6" above bit! We hammer and blow air and hammer and blow 11:20 Carl Cole ousde. We app 4 more puchels of pellets which bring top of seal to 310.5° We have pulled bit up to 307 bgs. We sound for water bit there is none
17:05 We hyporale pellets with 30 gallans of approved source water (WW III) and have which and allow to hyporale 1272 I take w. I. Still 17' of water colour but going Down slowly. Richard Junit calls
to check be progress.

[340 We have fulled by up to 298' bgs Widen is all 295. 1 bgs and going Downswerry & bourge This is water me apper de ligpuale hole aux not groves water. We are pulling 5 feel of casing at a time to try to expose a producing layer 13:40 We have puller up to 285 and WL has come up to 292 but no more 14:40 We have puller up to 265 aux WL is 291.5 14:55 We 11 11 11 255 " " 1291, 3 bas This should have put bit above last substantial five grained layer and leaves little like (ylong of substantial producing well as we have soullos Il be are going to lock lifting plug on well hear so Préhans Jurick con mondes recharge over weekens 15:20 Carl Cole has suggestes we pull 5 more feet out aux remové 10' section so Richard Down his we get a W.L of 283 to top of

9/17/04 (cov)

Casing or 281.6 bys which is substantially
viour recharge. I pecipe to go back
to building 614 for an hour and then
return & take mother reading layre
crew leaves sile for weekerd. Richard
is exploring the possibility of getting the
Schramm back to deepen well into
Sedrack

16:37 Back of D-12. W.L=279.6 TOC. I lock well how and leave indicatorin the body truck for Richard over the weekend.
17:07 I leave site

Waxlur 1/14/04

	9/20/04 Marray weather; Overcast i colo (+300)		
	an wind (10 mph to U.W)		
6:40	I arrive at side and Richard calls		
He took a will on salurpay and recorded the full			
	9/18/04 15:38 261.53 TOC		
	15:52 261.52 11		
	16:03 261.50 1,		
	16:15 261.48		
6:55	1 take w. L. Now 261.48 11		
	which is ~ 258.66 q.s. which is seemingly where		
	woken was last time we pulled and of hole and		
	several feet below our bit at = 248 bgs		
	I speak with Carl Cole he is pringing out		
	a topo map so we can per our vearby W.L.		
4:50	Carl ouste We determine grown surface to		
De approx 4815 H. This would place our exist			
	W. L ex (4815-258.66) 4556.34 W. L'S from		
Fall 2003 in picale the following elevations			
	Well elevation		
	B-02 (P6-5) 4466,51		
	C-18 4465.12		
	C-13 4460.42		
	C-3) 4466.95 C-15 4464.43		
:			
15.	D-02 4374.85		
*· · ·	If D-12 is similar to B-02 thru C-12 we should see walker		
	at about 350 ft		
	15 D-12 is sumplar to D-02 we should see water.		
	at about 440 ft		
- In either event this water appears to be meanly Perchep zone and it is decided we will with bedrock beepen to find regional quantities of the state of the section of t			
	will who beprock peeper to fine recional amount		
—·································	water table		
8:25	I call Richard and he will alest Ton to burne		
	out the Schramm with him when he		
267	comes I souro hole bottom al 290.4' bgs		
E Alexander			

9/20/04 (con+)

9:10 Nate Salazar arower with the Schrawn

9:20 Tom arrives with vent hours David Kyle I give Dave the SSHSP (Apperdix Col W.P) to read thro. He reads while Tom & Nation warm up rig & fuel I do vig waspection at this time.

9:45 Dave has read and signed plan acceptance

10:05 We have a tailgale His sueding on rig morning harans.

to bottom of 9" hole at 346'. We set up secompany containment and Has waste prum.

10:45 Down to 290 bgs. Carl leaves site.

11:00 @ 295 Prom Suil PARSNZ0426401

11:40 Come is stoggeting to keep the hammer rowing it needs resistance to operate well so recovering an open or loosly filled hole is Difficult.

12:10 Hammer is working but have hit something hard at 299

12:15 Cvew takes food break

12:30 Crew hammermy again.

12:35 @ 300 200 Drum LUI PATENZO42640Z

12:49 @ 315 3rd Drum full 11 03 - welves bevlowite play

13:00 Carl Cole ousde

13:15 @ 325 4th Drom full " 04 - mostly bestante i 16-40 sans

13:50 @331 5th Drum full 4 05

14:20 P342 6th boun LUN "06
Crew moves backer off hole and Shrammon
Carl leaves site. I go to 90 day years to change
bolts on drows to non-locking bolts.

16:10 Back at site com is just getting Schromm aligner

17:10 Craw has postrepped to feet of voo into hole All hours offsete

Walling Ilrolog

9/21/04 Tuespay wether: overcast (N30°) 6:50 lavoure at site and replace thining caution tape that sevotes exclusion zone and pick up bebos scattered by high wows 7:20 Doll com avoures Tou hus an emergency needing with his sons poctor of avours 13:00 and will have to short power. They warmy up 7:38 We have failgable His Sucoling Topics Do not hovery the job! but be efficient & effectibe. 8:00 Crew lowers remaining vors sown hole while lable some proms 8:25 Roos are on hole bottom at ~ 345. Crew books boom do exand hose for cyclone 8:40 Begin Dulling at 345. 9:10 Unable to get cultings to surface after in Vial sans and water are parger from boreloge at 356. I calibrate PID 103.6 ppm an 100ppm 150bilelyng Crew is hooking up secound compression 9:20 Still No cuttings at the cyclone 9:40 Crew reverses flow & Blew out plug at surface 10:05 Dvilling at 356
10:15 154 Dvom Lull PARSNZ0426501 356-361
10:41 200 " " 02 361-365 300 (1 3/3 (1) A = ---U:05 Hole is cause at 365 making it sufficely to back hammer out of hole Tom dears going oceper with vesoft in shock Drill string. I consoft with Carl aus Richard. Tom open this end of o" Pipe aus Seud souver bours Wiler level in pipe is 336. 7' bas just as it was last Frimy when we por has ledt bottom of hole open overing it before samping and sealing off beprock. We pull of hole but are unable to get source past 6" bit

9/21/04 thermoral of Tuestay
12:05 Crew leaves sile for SLC. I lock partially
fillers Down and call Richard
12:30 I leave site 4:11 tomorrow where we will
attempt to screen the water table from
365 to 345; logs assuming hole stays open

relation gleson

	9/22/04 Theorsony weather dear (~30°)		
	No winty		
	Larrue al builonne 614		
4:02	1 avrive at site (Dt 12)		
4:72	Crew arrives - late because they were loading pallates. We have His Stangele inquispection		
7.4.	1000 inc parates. We have His tailegale ing inspection		
	(a) (0) (e) (b) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c		
800 800	Jeff Bigelow onste		
_0:\0	Com lowers 6" to 345 and I take water level throw 6" pipe 336. 2' bgs Crew is able to lower pipe to 365 without		
8:30	Crew is ship to laws Dine to 365 without		
	brilling		
8:40	Crew trops out 6"		
9:00	Jest Bigelow leaves site Crew has 6" out		
	of hole We sound bottom at 364 bgs. We take		
	W.L. al 336.2' bgs. Crew will won pismantle Schrame		
	and remove of Iron hole, get Becker back on		
	hole nove has waste Drums & Drum truck, clean		
	up or thry materials drow site and then		
	set well in borehole		
9:50	Carl Cole onsile Dave Shank & Jeu Coman call		
	to see whats going on out here		
	(rew moves schramme von druck from sile		
	Crew mores Becker over hole		
11:00	Crew begins lowering well maderial town hole		
	1-6" bottom cap, 2-90' sections of 010 slot schepule		
	40 casing 34 -10' sections of Blank schepule 40 casing		
	1-5' solion of scheoole 40 casing		
——(13.2)——	Well touches bottom with 3° stickup - 362.5' bgs We lift well 6" off bottom which places bottom of the screen at 361.5' bgs, top of screen at 341.5'		
	the corres of 3615' bas ton of sources of 341.5'		
12:02	Crew breats for foon. Carl Cole leaves site. I call		
	Polaro with the appale		
12:20	Crow removes 5' of 9" casing on 12 begins sanding		
	well		
13: 35	Carl Cole ous de, 16-5016 bags of 16-40 sans		
	Coal Cole ous de. 16-50 16 bags of 16-40 sand brings top of samp to 339' bags.		
O : Personal Company			

9/22/04 (cost)

Filter pack volume calculation; Borchole anulus volume - well casing volume (D2 x. 785 (contoles constant) x L) - (D2 x. 485 x L) We have two calculations 9" bovehole from 339 to 346 6" borehole from 346 to 363 [(.75 A) ×. 785 x 7 A] - [(.334)] 85 x 7 A] 3.09 - 0.6 - 2.45 A [(.54)2 x.785 x 174] - [(.334)2 x.785 x 174] ..3,34 1.48 = 1.86 4 (2.45 + 1.86) ft3 = 4.35 ft3 4.35 ft3 + .5 ft3/perbay sours = approx 9 bags We needed to bags to fill this volume so the hole is taking sand in to fractures and the last camed 5 feet of the borehole 13:50 Top of sout has remained at 339 bgs 14110 Crew pulls 10' of casing from stong and we aDD 6 buckets of time released bertonke pelleds to bring top of seal to 334' bgs i hyperde. 14:50 Crew has Deciders to not begin sluving process until to move on mouring so they clean up site and Dave takes the Schramm back to SLC Lole (D-13) in case he mobs to well side while Im not herp. 15:48 I speak with Richard and Jord who have avrançes to have bruns moves tomorrow at 9:00 am. I will coorpinale this as we will need to use prom truck boom to load any unloan ormes pot locks or ormes 16:15 All hours odside Max tues 9/22/01

	51
	9/23/04 Thursday weather clear (250)
	low plante are so to NW
6:30	I avoive at site to polish prome-vare and
	Dust covers then all the last few source
	ans remove locker and locking bolts.
4:02	Even avvives at site and warms up vices
	ille was all all all all all all all all all a
	that well be come to 90-Day was likes
	to unload burnes
7:20	Cuew has brought a new have Richi Smith
	so I have how read Asserva (-5918) of the
	workplan and siew plan acceptance Larry
<i>4.40</i>	We have H&S dadcale Topic bestonte d'Arme
	That well be going to 90-Day yard later to vuloco survey a rew have Ricki Smith so I have how read Appendix (-5945P of the workplan and sign plan acceptance formy we have His dailgate Topic bentonite stipping hazars
8:10	(vew gets equipment in place dor growing We shot pour to move brown to 90 pay
9:00	We shot powe to move prove to 90 pay
	yard
9:05	MP Dower (Darrel) auriles at Porgers Pons
	Crew begins loading Drows.
9:15	Crew begins loading Drums. Lawry Hotarbus and Judy Meon (TEAD) and
9:25	9 Drums loader PARSNZO426401 Hurs 06
	aug PARSUZOY 26501 the 03
	Downs are manufester under # P4007
	We Downe do 90 Day yord
10:05	Droves are unhagen as rellates the standard
	a pallate broken last week unlasting with the
<u> </u>	Down Tolly. We used bour touch this week
	a pollate broken last week unbasing with the Down tolly. We used bour truck this week Loading tickel # 516956 All homos back to D-18 Kurt Alloway and Jest Recelars and a for the Curt Alloway and Jest
_	All hours back to D-12 River Alloway and Jest
	Brigelow ovsile at 90-Day yard
10:12	Brook is being wired in a 55 gellon Down which
-	is Down on the officers and Down Crais
	is using 50 lb bags of Kure Gold Mich Solve Berbute
——·	Clay doub estable Deroughes 20% Saling saling the way
··—·	of 10-10.2 Ibs/gallan and files 2.2 cubic feet.
————	of 10-10.2 lbs/gallan and files 2.2 cubic feet
 	Crew wixes & bags per bakk i v RB gallous weller
Garage Landson Co.	

12:20 Crew is breaking for lough-they have mixed 10 batches (20 bags) of grout which brought slurry to surface in well (only the andus between the 6" was casing and 4" well is siller) They then puller 90 feel of casing. I ask it they have enough water. They have only 13 tank I call Gary Partor to See N' we can reload from WWIII belove TEAD whilety even is gove for the weekens. (They bout work fridays). Gary Polash can meet us there before he knows to DD for the atterwood. We tre Dowe the loan ans hears to well I stop at 614 on the way.

13.35 Crew is back of sile and has mixed an applified 16 bags - 8 batches and pullers a total of 160 feet Crew volices how such water we are very our we call to see it bary can fell us ove more time. He says we can meet at 3:15. Cable has come loose those Dryon (Main Litting cable) It is trayer on the eup authors week usage so come changes it out with

9/23/04 (cont) 18:40 Carl Cole overte 14:00 220 feet out of hole Cast Cole leaves site for the Day 15:00 200 feel out of hole - Nate and I hour back to WWIII to need Gary Polasks and fell truck once more as even will veep make to fouch growing and D-con hover 280 feet out of hole pumping for an I calculate borehole voluve - while is 9" OD. the borehole tenos to be 9.5 to 10" Draweler Due to cobble gravel value I will use 9.5 for calculation [(4.9184)2 x. 785 x 389 (+] - (333 fi)2 x 785 x 389 (+) 161.7 23,308 A3 - 28.6 Ft3 = 133.1 Pt3 - 2.2 Pt3/bag = 60.5 bags 16:50 Crew has last piece of casing out of hole they pump quost to 20 ft bgs. This took a total of 96 bags (2 palates) so the hole up site and will boing surface casing and viore growt and comet L'on complétion His All brands ald side Down gestor

weather clear (~40°-Friday 9/24/04 07:15 l'avrive at site, Crew is late loading moderial 08:10 Crew avoives at site and mixes 6 more bags of bevouve (3 batches) our apps to bovehole This brings good to surface but it will settle some a:40 We have taileste H&S Topic: Powdered bevlante respondony hasars. Coëne mobs equypment to the 90 Day yard for Decouving. Because Toms pump à électric for future we will explan the possability of power ousile with UD 100 rig inspection here.

13:20 Crew has pecoused pipe trucks, pipe ours boild rig generative 125 gallous of work which is prompto into the Baker tank which is attixed with a Haz haste lable We chack generalar to frac tank to gaves again's the It. We hear back to D-12. 14:10 Crew mixes growt to pour in hole and allow to set up over weekend so they can set surface casing on it. 12 bags concrete bring cement from "8" to 2.5" logs. Crew well come toucorow and so the surface completion of well (Casing, bollars cevery pap, survey plug) They use a locking compression plug to secure the well will! Then they are taking the Backer Hammer back to SLC to fit it with a volvey attackment so we soul need to bring, out the Schramme each time we enoughed ordisal or beprock. I will not return ustill Crew is sear ready to begin builting our vext well D-13 14:45 All hours offsite

Wax (me 9/24/04

Tuesnay 9/28/04 weather partly closing (50-75) 15-30 mph from 9 E. gustine 8:00 (speak to Chiris Davis (Layue) He expects

via to be ready to leave shop in a few hours Tow one Dave are at Depot parting completon of D-12, I call Richard Jurik and Jell Bigelow whows 9:10 1 leave for Toocle 1 call Jan Coman w/ uprode 9:45 1 arrive of D-12. Cap is bolten to completion so I call Carl Cole and tell him well is ready for Covernment Issue lock | Drive to 90 Day yard to load generaler to return to Kleintelper 11:10 Tom Kern calls He is back of Layre our 12:50 Tom cells they are leaving shop with vig in la muntes 1405 Coew arrives with rig - Tom and Dave Kyle They lay power visqueen and move vig over stated location and vaise mast 14:30 We have Darley His 5 taigale Topic vow hours associates with votary attach men 121:40 (perform or uspection of Baker house Carl Cole ouside He has locker D-12 ans tor D12 Crew is hooking up assillary compressor and waiting for Nate to Lavoring with level 15:20 Note avoures with lovel Crew fires up ny aux, compressor aux libts bit aux 9"-10 foot carried section into place. I prepare chip tray is - sample bags - 15-45 Begin Duilling [D-13] - 17:10 1 is 40' 599 All hours oddside

Wathland

FIELD ACTIVITY REPORT

Project Number/WBS: 744139/20010	Date: 9/1/04		
SWMU: 58	Arrival Time: 8:00		
Team Leader: Jell Bigelow	Departure Time \Destination: 18:30\SCC		
Team Members: Matt luerc	Weather: clear (~750) windy		
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Gest Pit GPS CPT Other (specify)	Well Installation D-12 Well Development Microwell Sampling Monitor Well Sampling Vertical Boring Angle Boring Hand Auger Surface Soil Sampling		
Protection Level: ☑ D □ C □ B □ A			
Topics Discussed: Site Specific Health: Safty Plan overview			
Logbook Book # Bo71503 M/C Parties Page # 1:2 Notified	☐ TEU Response ☐ Lockheed Monitoring ☐ Range Control/Security (460) ☐ Pillbox Support ☐ Meteorology		
Photos Camera # Roll #	Frame #		
IDW Drums: Purge / Rinse / Soil / Other #ES(s) Closed?: Y/N Current Location: Update DITF?: Y/N			
Notes: 8:00 Meet with Jeff B. & Richard I to piecuse trule of			
10:00 Beque Kickell meeting: 13 people present Geo page 1 logbook) 11:20 Visit gite of 90-Day yarp (ucm) and Decompto location 13:30 Leave site for SIC			
	·		

Project Number/WBS: <u>144139/20010</u>	Date: 9/2/04	
SWMU: 58	Arrival Time: 8.00	
Team Leader: Jeff Bigalow	Departure Time \Destination: 16:30/NHC	
Team Members: Matt luevs	Weather: Overcust (650)	
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Gest Pit Gest Cert Other (specify)	Well InstallationD - 12	
Protection Level: ☑D □C □B □A		
Health and Safety Briefing: Time 8:30 Peo	ple Present 5 (Layne Crew, Ivers, Jurne)	
Topics Discussed: Grass Fires, Cyclone	Proch Points, whatalow Harands, PPE	
Logbook Book # BO71503 M/C Parties Page # 3 ; 4 Notified	☐ TEU Response ☐Lockheed Monitoring ☐ Range Control/Security (460) ☐Pillbox Support ☐ Meteorology	
Photos Camera # Roll #	Frame #	
IDW Drums: Purge / Rinse / Soil / Other #ES(s)		
Notes: 8:00 Acrive al site, procure water	update DITF?: Y/N where this table	
Crect exclusion zone 9:30 Begin Drill logging with Carl Cole - emphasis on following format of ASTM stampano, us 90' rock in pipe analys 12:35 Resume D goes to but De-con pap. Richard to log at Motel.	considercy between geologists and my USACE log poper 12:05 @	

Project Number/WBS: <u>744139/20010</u>	Date: 9/3/04
SWMU: 58	Arrival Time: *100
Team Leader: Jeff Bigelow	Departure Time \Destination: _17:35
Team Members: Matt luevs	Weather: Raw (60°)
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Gest Pit GPS CPT Other (specify)	Well Installation D-17 Well Development Microwell Sampling Monitor Well Sampling Vertical Boring Angle Boring Hand Auger Surface Soil Sampling
Protection Level: D D C DB DA	
Health and Safety Briefing: Time 1:00 Peo	ple Present 4 (Layne Coen, Mat Ivera)
Topics Discussed: Roogens Road Tradt	ic, Hans : Finger Salety
Logbook Book # RO71503 M/C Parties Page # 9. Notified	☐ TEU Response ☐Lockheed Monitoring ☐ Range Control/Security (460) ☐Pillbox Support ☐ Meteorology
Photos Camera # Roll #	Frame #
IDW Drums: Purge/Rinse/Soil/Other #ES(s) Closed?: Y/N Current Location: Update DITF?: Y/N Notes: 7:00 His tarked Frel: warm rig. show lightney break 8:15 Begin Drilling A 9:02 Roos Plugging. Stampby for second compressor to lift cuttings, 13:00 Compressor and le 13:20 Begin Drilling & 120' 16:12 Drilling and 210' 16:40 To Building 614 for paper work 17:35 offside	

Project Number/WBS: 744139/20010	Date: 9/7/2004
swмu:58	Arrival Time: 7:00
Team Leader: Jeff Byelow	Departure Time \Destination: 16:15
Team Members: Matt lvers	Weather: _clear (45 - 85°)
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Gest Pit GPS CPT Other (specify)	Well Installation D-12 Well Development Microwell Sampling Monitor Well Sampling Vertical Boring Angle Boring Hand Auger Surface Soil Sampling
Protection Level: D D C DB DA	
Health and Safety Briefing: Time 1:20 Peo	ple Present 5 (T.K, M.S, M.W, M.J, CC.)
Topics Discussed: PPE in the satural	ed zove, Drum movement hazard
Logbook Book # BO71503 M/C Parties Page # 7 Notified	☐ TEU Response ☐ Lockheed Monitoring ☐ Range Control/Security (460) ☐ Pillbox Support ☐ Meteorology
Photos Camera # Roll #	Frame #
IDW Drums: Purge / Rinse / Soil / Other #ES Closed?: Y/N Current Location:	S(s) Update DITF?: Y/N
Notes: 7:00 Arive 7:20 H&S 7:3	
Drilling @ 210 ft 10:45 @ 250' No more casing onside-we wait 11:10 Durving maintenance crew	
finds crack in radiator. They remove i runto shop	
1 work in Builo 614. 14:30 Car	Il Drops UID excavation permit

at 614. 15:30 1 go to D-12 to check progress 16:10 Crew has repaired variation and are installing. No more drilling. I leave Depot. MCOCHISE/PROJECTS/dpg/dugway_phase_2_734267/Forms and Templates/FORMS/Var2002.doc

•	
Project Number/WBS: 744139/20010	Date: _ 9/8/09
SWMU: 58	Arrival Time: 7:00
Team Leader: Jeff Bigelow	Departure Time \Destination: 16:48
Team Members: Matt Iveus	Weather: (60-80°)
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Test Pit GPS CPT Other (specify) Protection Level: ☑ D ☐ C ☐ B ☐ A Health and Safety Briefing: Time 7:16 Peo	Well Installation D-17 Well Development Microwell Sampling Monitor Well Sampling Vertical Boring Angle Boring Hand Auger Surface Soil Sampling Layre (vew (TK, NS, MW)
Topics Discussed: Lyclove Hazan	
Logbook Book # RO71503 M/C Parties Page # _ 9 Notified	☐ TEU Response ☐Lockheed Monitoring ☐ Range Control/Security (460) ☐Pillbox Support ☐ Meteorology
Photos Camera # Roll #	
IDW Drums: Purge/Rinse/Soil/Other #ES(s) Closed?: Y/N Current Location: Update DITF?: Y/N Notes: 7:00 Arrive of site w/crew. Jell Thomas ansile for inspection 7:10 His Stackate 7:30 Begin Drilling a 250' 8:45 Jeff Bigelow ansile. At 276' we hit a linestone boulder that would break 9:40 & 217' we hit comertee gravel-very hand-almost no penetration 10:36 Discharge hose breaks off head-shit down to repair 15:00 Riq repaired Drilling again 16:10 (axil (ale ansight 6:30 & 279 head is overheading, we shit down for Day 16:48 All hands offsight	

Project Number/WBS: 744139 2000	Date: 9/9/04
SWMU: 58	Arrival Time: 7:00
Team Leader: Jelf Bigelow	Departure Time \Destination: 16:45
Team Members: Matt luers	Weather:
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Test Pit GPS CPT Other (specify)	Well Installation
Protection Level: D C B A	Layre (rew (TK, NS, UW) 4 Kienlelon (MI
Health and Safety Briefing: Time 7:10 Peo	ple Present
Topics Discussed: Items copresses 6	y J. U Thomas at yesternous suspection
Logbook Book # Bo11503 M/C Parties	☐ TEU Response ☐Lockheed Monitoring
Page # 10 Notified	☐ Range Control/Security (460) ☐Pillbox Support ☐ Meteorology
Photos Camera # Roll #	□Pillbox Support □ Meteorology
Photos Camera # Roll # Roll # IDW Drums: Purge / Rinse / Soil / Other #E Closed?: Y/N Current Location: Notes: 7:08 Arrive & sile 7:05 Creater of the Public Park of Table 1988 Public Park of Tabl	Pillbox Support Meteorology Frame # S(s) Update DITF?: Y/N overves 7:10 HiS, flore we @ 279 16:30 Evo Decline
Photos Camera # Roll # IDW Drums: Purge / Rinse / Soil / Other #E Closed?: Y/N Current Location: Notes: 7:08 Arrive & sile 4:05 Crea	Pillbox Support Meteorology Frame # S(s) Update DITF?: Y/N overves 7:10 HiS, flore we @ 279 16:30 Evo Decline
Photos Camera # Roll # Roll # IDW Drums: Purge / Rinse / Soil / Other #E Closed?: Y/N Current Location: Notes: 7:08 Arrive & sile 7:05 Creater of the Public Park of Table 1988 Public Park of Tabl	Pillbox Support Meteorology Frame # S(s) Update DITF?: Y/N overves 7:10 HiS, flore we @ 279 16:30 Evo Decline

Project Number/WBS: 744139 20010	Date: 9/10/04	
SWMU: 58.	Arrival Time: 6:45	
Team Leader: Jeff Bigelow	Departure Time \Destination: 15:40	
Team Members: Matt luers	Weather: clear (40-80°) WIND 10 to 5	
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Test Pit GPS CPT Other (specify) Protection Level: DD C DB DA Health and Safety Briefing: Time 7:15 Peo Topics Discussed: PPE IN Salvaler	Well Installation D-/Z Well Development Microwell Sampling Monitor Well Sampling Vertical Boring Angle Boring Hand Auger Surface Soil Sampling Layue (TIC, NS, MW) KA (MT) The pole Present Parson (TB)	
Page # Notified M/C Parties	☐ TEU Response ☐Lockheed Monitoring ☐ Range Control/Security (460) ☐Pillbox Support ☐ Meteorology	
Photos Camera # Roll #	Frame #	
Closed?: Y/N Current Location: Update DITF?: Y/N Notes: 6:45 Arrive at bulo 614 7:05 Arrive at D-12 7:15 Do His and vehicle inspection 8:00 Call Chris Davis and orner well materials 9:00 Begin prelling at 323 ft 15:10 Stop prelling at 343 where hole is too tight. We sound bottom at 344.2 bys and water at 340.0 bys, We guit now to lest water come in well 15:40 Jest leaves site, I sign Doubler's Dayleys		

	/
Project Number/WBS: 744139 20019	Date: 9/13/04
SWMU: 58	Arrival Time: 7:80
Team Leader: Mett Jeff Bigelow	Departure Time \Destination: 16:05
Team Members: Matt lucrs	Weather: (leas (40-75°) wwo 5-10 mp & to
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Test Pit GPS CPT Other (specify)	Well Installation
Protection Level: D D D D B DA	
Health and Safety Briefing: Time 7:35 People Topics Discussed: Back Layuries Logbook Book # B071503 M/C Parties Page # 15-16 Notified	☐ TEU Response ☐ Lockheed Monitoring ☐ Range Control/Security (460) ☐ Pillbox Support ☐ Meteorology
Photos Camera # Roll #	Frame #
IDW Drums: Purge/Rinse/Soil/Other #ES Closed?: Y/N Current Location: Notes: 7:00 Arrive on ile 4:45; onable we take w. L. 336.4 Sou 3.6 ft new since friday 8:50 Republ bottom 11:50 Drilled 6:00her in 15:10 Shot Down vig - Drilled 8 Soys no more beating up rig. W something Different 15:30 Carl	Update DITF?: Y/N Jeff lables prume \$:00 Carllole as Bottom 344. Z: 7.8 ft H20 last 30' of hole 9:10 Book on 2.5 hrs 12:40 Drilling again u in last 21/2 hours. Layre le will pull out 3: Ing
out of bottom 30' WL = 337.2 com	ing up an indiever few wis.
5:05 I leave site 50 ft aid of loo	la New duly

1	
Project Number/WBS: 744139 2000	Date: 9/19/09
SWMU: 58	Arrival Time: 7:35
Team Leader: Jeff Bigelow	Departure Time \Destination: 17:05
Team Members: Mattluers	Weather: Clear (40°-70°) wwo 5mph
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Test Pit GPS CPT Other (specify)	Well Installation D-/7 Well Development Microwell Sampling Monitor Well Sampling Vertical Boring Angle Boring Hand Auger Surface Soil Sampling
Protection Level: DD DC DB DA	
Health and Safety Briefing: Time 7:35 Per	ople Present Layue crew i I
Topics Discussed: Hover Vehicle	Salety
Logbook Book # Boll Boll M/C Parties Page # 13,14 Notified	☐ TEU Response ☐Lockheed Monitoring ☐ Range Control/Security (460) ☐ Pillbox Support ☐ Meteorology
Photos Camera # Roll #	
TDYY N	S(s) Update DITF?: Y/N
Notes:	
Figo Jul Thomas auxile when I reduce from 614 We real with her concerns 10:05 Crew has pulled all but 60 ft from bore hole 11:10 Bit out at hole-Dull water Level 263.5 11:55 Outhoose serviced 12:30 Begin senoing pipe with new but back down hole 14:50 Carl (ale, Mary Ellen, Helge, Laury public 15:35 Visitors affects 16:40 200' in hole. W.L=258.3	
Botton caused to 263.0 17:05 A	U hangs offects

		
Project Number/WBS: 744139 20010	Date: 9/15/04	
SWMU: 58	Arrival Time: 6: 30	
Team Leader: Jeff Bigelow	Departure Time \Destination: 16-30	
Team Members: Matt Ivers	Weather: clear (35°-75°F)	
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Test Pit GPS CPT Other (specify)	 Well Installation _D-/Z Well Development Microwell Sampling Monitor Well Sampling Vertical Boring Angle Boring Hand Auger Surface Soil Sampling 	
Protection Level: D D C DB DA	Layre (T.K + M.W)	
Health and Safety Briefing: Time 10:50 Peop	ple Present Khewlelner (tuens)	
Topics Discussed: Drow lifting to	vek	
Logbook Book # <u>Ro70563</u> M/C Parties Page # <u>17</u> Notified	☐ TEU Response ☐Lockheed Monitoring ☐ Range Control/Security (460) ☐ Pillbox Support ☐ Meteorology	
Photos Camera # Roll #	Frame #	
IDW Drums: Purge / Rinse / Soil / Other #ES(s) Closed?: Y/N Current Location: Update DITF?: Y/N		
Notes: 6:30 Arrive al 619 705 Arrive at D-12 7:35 Mike arrives with well supplies 7:50 Tam arrives like on rig inspection 8:20 Take water level 258.03 9:40 260 ft at casing in hole - cuttings stat at 263 10:00 Calibrate PID (101.6 an 100 120 bit) 10:50 Consust 155 tartials 11:00 Hammer running at 263 15-10 Dougs to 345' 8 full brung and 1 partial prune collectes 16:30 offsite		

Project Number/WBS: 799/39/20010	Date: 9/17/04	
SWMU: 58	Arrival Time: 7:03	
Team Leader: <u>Jeff Bigelow</u> Team Members: <u>Natt lvers</u>	Departure Time \Destination: 14:04	
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Test Pit GPS CPT Other (specify)	Weather: Clew (35-40°) Well Installation D-12 Well Development Microwell Sampling Monitor Well Sampling Vertical Boring Angle Boring Hand Auger Surface Soil Sampling	
Protection Level: D D D B DA Layre (T.K.N. S. P.M) Health and Safety Briefing: Time 450 People Present Klewledver (M. I) Topics Discussed: 1 ft. 11 Samp bases		
Logbook Book # BO71503 M/C Parties Page # 22, 23,24 Notified	☐ TEU Response ☐Lockheed Monitoring ☐ Range Control/Security (460) ☐Pillbox Support ☐ Meteorology	
Photos Camera # Roll #	Frame #	
Closed?: Y/N Current Location: Notes: 7:03 arrive & site 7:45	Update DITF?: Y/N	
Hole sausers to 320,5 12:00 Hole bearlow to 310.5; hyproden 5:20 Haung backers pipe to 255 bys q mase little wider, but pulling		
pipe to: 250' bys we make 210' a let maler vice over meetern. It is	us viewe stowly, We will "	

Project Number/WBS: 744139 2010	Date: 9/20/09	
SWMU:58	Arrival Time: 6.40	
Team Leader: Jeff Bigelow	Departure Time \Destination: 17:10	
Team Members: Hatt Wes	Weather: overcast (30°-65°)	
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Gest Pit GPS CPT Other (specify)	Well Installation D-17 Well Development Microwell Sampling Monitor Well Sampling Vertical Boring Angle Boring Hand Auger Surface Soil Sampling	
Protection Level: D D C DB DA Health and Safety Briefing: Time 10:05 Peo	ple Present Kleinfelber (MI)	
Topics Discussed: Vehicle Hazar	1	
Logbook Book # BOTISO3 M/C Parties Page # 25,26 Notified	☐ TEU Response ☐Lockheed Monitoring ☐ Range Control/Security (460) ☐ Pillbox Support ☐ Meteorology	
Photos Camera # Roll #	Frame #	
IDW Drums: Purge/Rinse/Soil/Other #ES(s) Closed?: Y/N Current Location: Update DITF?: Y/N Notes: 6:40 Arrae & site check w. L. 261.48 7.50 Carl overle with topo map. We betarwive use are much to high to be in required water to ble ours water is perches. We will repress 4" to 346 cms or un cuttings. 14:20 9" Down to 342 Crew Tries to Time Schramm on hade. I go so 90. Day		
your respection à change out 18 reapy to trip IN 17:10 60 pour bale All haups offs.	of von and 5' havener	

	······································	
Project Number/WBS: 744/39/20010	Date: 9/21/04	
SWMU: 58	Arrival Time: 6:50	
Team Leader: Jest Bigelow	Departure Time \Destination: 12:30	
Team Members: Matt luens	Weather: Overas (1300) Nowwo	
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Test Pit GPS CPT Other (specify)	Well Installation D-(7 Well Development Microwell Sampling Monitor Well Sampling Vertical Boring Angle Boring Hand Auger Surface Soil Sampling	
Protection Level: ND C DB DA	Layne (TK, NS, DK)	
Health and Safety Briefing: Time 7:38 People Present Klaufelver Hall luers		
Topics Discussed: Dort rush - be ellective anvellice 1		
Logbook Book # BOT 1503 M/C Parties Page # 27 Notified	☐ TEU Response ☐ Lockheed Monitoring ☐ Range Control/Security (460) ☐ Pillbox Support ☐ Meteorology	
Photos Camera # Roll #	Frame #	
IDW Drums: Purge / Rinse / Soil / Other #ES(s) Closed?: Y/N Current Location: Update DITF?: Y/N		
Notes: 6:50 Armine & sile 7:20 rig inspection 7:38 Hès factgare 8:00 lower 6" Downhole 8:25 Roos on bottom (345') 840 Bejon		
Drilling 4:10 Can't raise collings - book up aux compressor 10:05		
Hole unplagges. Drilling @ 356 11:15 Drilles to 370 bit hole is cause at 365. Could lock boildring, we take WL= 336.7		
12:00 Crow word leave for topay (Doctor) so we pull 6" up		
INSIDE & and lay to sound bottom but court get by bit		
will lower bit to bottom in morning. Source water soil and		
sup built well. 12:30 Offste		

Project Number/WBS: 744139 20010	Date: 9/22/04	
SWMU: 58	Arrival Time: 6:40	
Team Leader: Richard Junix	Departure Time \Destination: 16:15	
Team Members: Jell 13 , qelow, Matt ber		
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Gest Pit GPS CPT Other (specify)	Well Installation D-/Z Well Development Microwell Sampling Monitor Well Sampling Vertical Boring Angle Boring Hand Auger Surface Soil Sampling	
Protection Level: D D C DB DA	Layne (TK, NS, DK)	
Health and Safety Briefing: Time 1:25 People Present Klewleber (Ivers)		
Topics Discussed: Vehicle Mou	earcu	
Page # 29,30 Notified	☐ TEU Response ☐Lockheed Monitoring ☐ Range Control/Security (460) ☐ Pillbox Support ☐ Meteorology	
Photos Camera # Dog Hal (KA) Roll #	Frame #	
IDW Drums: Purge/Rinse/Soil/Other #ES(s) Closed?: Y/N Current Location: Update DITF?: Y/N Notes: 6:40 Armye & 619 405 avorve & D-12 7:25 creat armives 9:16 Lower 6" to 345' and take W. L. = 336.2' bg 8:30 Lower 6" to 365 where it is cared 9:00 6" tripper out Sound bottom & 364' bgs WL= 336.2' bgs 9:40 Dismaille Schramm quere off hole 10:30 Becker over hole 11:00 lower well power hole 11:45 Well son bottom - solift well 6" off: Screen 361.5 to 341.5 bgg. 13:35 Well Samper to 339' bgs. 14:10 Bertonte seel to 334 bgs. 15:20 Tom i I visil D-13 size 16:15 All hours offsile		

Project Number/WBS: 744/39 20010	Date: _ 9/23/04	
SWMU: 58	Arrival Time: 6:30	
Team Leader: Richard Tunk	Departure Time \Destination: 17:15	
Team Members: Jeff Byelow, Hoth luers	Weather: Clear (25-80°)	
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Test Pit GPS CPT Other (specify)	Well Installation D-17 Well Development Microwell Sampling Monitor Well Sampling Vertical Boring Angle Boring Hand Auger Surface Soil Sampling	
Protection Level: D D C DB DA	layue (Tik, N.S, R.S)	
Health and Safety Briefing: Time 7:40 Peo	ple Present KA (Ivers)	
Topics Discussed: Bendonde SI.	pping Hazaro	
Logbook Book # BOT 1503 M/C Parties Page # 31,32,33 Notified	☐ TEU Response ☐Lockheed Monitoring ☐ Range Control/Security (460) ☐Pillbox Support ☐ Meteorology	
Photos Camera # KA Digital Roll #	Frame #	
IDW Drums: Purge / Rinse / Soil / Other #ES(s) Closed?: Y/N Current Location: Update DITF?: Y/N		
Notes: 6:30 Arrive of site, clean orung, change locking bolts 7:00 Creat		
Coron Figo His forgate 9:00 & Drume to go Day yard PARSUZO426401 Horos FARSUZO426501 Haru 03 manufes P4007 load freket 516956 10:15 Bogin		
growting 11:40 De weekly Drum inspection 12:20 90 feet out of hole go to warm for water 13:25 200' out of hole 14:00 290' out of hole 16:50 Out of hole 96 bay of bentonde uses to get to		
20' bas. 1 calculates 60.5 to get to 10' bas so the hole is caused or very transmissive 17:15 affects		

Project Number/WBS: 744139/2040	Date: 9/24/04	
SWMU: 58	Arrival Time: 7:10	
Team Leader: Richard Junk	Departure Time \Destination:	
Team Members: Tell Bigelow, Mod luers	Weather: Clear (140-75°) NO WIND	
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Test Pit GPS CPT Other (specify)	Well Installation	
Protection Level: D D C DB DA Health and Safety Briefing: Time 9.40 Peop	Layre (TK, NS, RS)	
Topics Discussed: Beworke pour		
	a- respiratory hazars	
Logbook Book # <u>ROTISOS</u> M/C Parties Page # <u>34</u> Notified	☐ TEU Response ☐Lockheed Monitoring ☐ Range Control/Security (460) ☐Pillbox Support ☐ Meteorology	
Photos Camera # Roll #		
IDW Drums: Purge / Rinse / Soil / Other #ES	(6)	
Closed?: Y/N Current Location:	Undate DITE? V/N	
Notes: 7:15 avenue & D-12 8:10 (vew avenues and mixes 6 bag bestaville growt to top all well to surface 9:40 His Starfaste 10:00 Move to 90-Day yand to De-con pipe is fig generale 125 gellow 13:20 Head but to D-12 to mix cement growt for a footing for 10" steel surface casine 14:10 Growt from 8' to 2.5' bys 12 bags cement 14:45 Offsite.		

Project Number/WBS: 744/39/2000	Date: 10-4-04	
SWMU: Well D-12	Arrival Time: 07:00	
Team Leader: J. Bigelow	Departure Time \Destination: 18:00	
Team Members: J. Hann, M. Byer		
Purpose: (Attach all appropriate forms) Geophysical Survey Soil Gas Survey Hydropunch Gest Pit GPS CPT Other (specify)	 Well Installation Well Development	
Protection Level: D D C DB DA		
Health and Safety Briefing: Time 130 People Present See above		
Topics Discussed:pinch point	ls	
Logbook Book # TEAQ M/C Parties Page # 32-33 Notified	☐ TEU Response ☐Lockheed Monitoring ☐ Range Control/Security (460) ☐Pillbox Support ☐ Meteorology	
Photos Camera # Roll #	Frame #	
IDW Drums Purge Rinse / Soil / Other #ES(s) PARS N20427801 Closed? (Y) N Current Location: On-Site Update DITF?: Y (N)		
Notes: 07:00 Arried on site, veolia arrived, MParrived 08:00 Storked Surgingthanling, 4" banks getting stack, borroved 3" banks from Layre Christensen 10:30 Storker h. 1 211 h. 1		
13:33 Strka pumping 4:30 Backflushing 5x		
15-15 Buck Hushim SX		
Pumped 662 gallens, w.L. at 334.50 at end Locked up MP Inker for move to 90-day year tomorn		
Visited up 1917 Inker ter	15, 4:00-16:15	

Date: 9 / 2 / 04	Time: 8:30	
Site Health and Safety Officers(s)		
ATTENDEES	S SIGNATURE	
1. Thomas Kan	11.	
2. Abtha Solozar	12.	
3. Maria a Van	13.	
4. 2/2//	14.	
5. Ridford First	15.	
6. In Virth	16.	
7.	17.	
8.	18.	
9.	19.	
10.	20.	
ACI	ENDA	
_		
1. Grass Fires - Present and Known Danger 2. Cyclore Purch Point		
3. luhalation Hazards		
4. Proper application of PPE for this COC		
5.		
6.		
7.		
8.		
9.		

ate: 7 / 3 / 09	Time: <u>7:00</u>
te Health and Safety Officers(s)	
АТТ	ENDEES SIGNATURE
1. Wathland	11.
2. Phomor La	12.
3. Agthur Salagar	13.
4. Marina Dans	14.
5.	15.
6.	16.
7	17.
8.	<u>. 18.</u>
9.	19.
10.	20.
1. Roogers Road has	AGENDA Surprising amount of Traffic
2. Be very exert b	acking out of sile out roap
3.	
4. Most ording ing	vues occur to hause aux
	y aware when adding casing seet
6.	
7.	77
8.	·
9.	

Date: 9 15 104	Time: _8:1	5"
Site Health and Safety Officers(s)	, ·	WELLD
ATT	ENDEES SIGNATURE	WELL
1. Il Al Warfe	11.	
2. Ton Hall	12.	
3. N. M.	13.	
4. Dathat Salara	14.	
5.	15.	
6.	16.	
7.	17.	
8.	ŝ 18.	
9.	19.	
10.	20.	E. A. A.

AGENDA

1.	Because of the way the oischarge hose
2	is attached to the eyclone, cuttings
3.	exit at high speeds so alway wear
4.	safety glasses tight to face avours cyclone
5	and avoid potting hour or Discharge stream
<u>6.</u>	without gloves elso be cartious of classes
<u>7.</u>	of rock rickocheting out of wheel barrel
8	in random Directions
9.	

_	•
Date: 9 17 104	Time: 7:15
Site Health and Safety Officers(s)	
ATTENDE	ES SIGNATURE
1. Well har	11.
2.11/1/2	12.
3. Homer Ka	13.
4. Nathan Salagar	14.
5/AD Else	15.
6.	16.
7.	17.
	18.
9.	19.
	20.
	GENDA
1. We may encounter go	vear vitrile gloves and
2. saturates cuttings	wear vitrile gloves and
4. low level TCE	with contact one to potential
5.	
	42
7. Re candil shad Di	vehing hand when performing
8. this adjusty	and must be 40 part
O CONTROL OF THE CONT	

Date: 9 / 8 / 04	Time: 7:10
Site Health and Safety Officers(s)	
ATTENDE	ES SIGNATURE
1.1/4/	
1. Wall faces	11.
2. Hours Kee	12.
3. Nathan Salagar	13.
Affilm a Winne	14.
5. Chill Chomas	15.
6.	16.
7	17.
	18.
9.	19.
10.	20.
·	
AC	GENDA
1. Plugging and air builts	of in the cyclour can vesult
2. IN violent Discharges	. Be cautious when movine
3. cuttings or sampling a	Be cautious when moving
4.	
5	·
6.	
7.	
8.	
9.	

Date: 9 / 9 / 04	Time: 7:10
Site Health and Safety Officers(s)	•
ATTENDE	S SIGNATURE
1. May land	11.
3. THOMAS Ke	12.
4. phthe Salazar	14.
<u>5.</u> <u>6.</u>	15. 16.
7. 8. ż	17.
9.	19.
10.	20.
A	ENDA
	lowing concerns at yesterous
3. 1. No consumption o	I bop or Drink in the exclusion
5. 2. Handle cuttings =	Loon cyclone with vitral
7. 3. Appilional Delail	appen to my inspection

		•
Date: 9 / 10 / 04	_	Time: 7:15
Site Health and Safety Office	cers(s)	
	ATTENDEES	SIGNATURE
1. Wat las	wy	11.
2. Nathan Sa	lugar	12.
1/1/1/19	2	13.
4. Jely My	14	14.
5. Thomas Kr		15.
6		16.
		17.
8.	غ	18.
9.		19.
10.	1, 1	20.
	AGEI	NDA
1. We shoul	•	value the salvater
2. zone to	sacr Went D	wopen PPE (N.Y. Chi
3. eye suol	in Cooks	roper PPE (Nival Gloves a avoir hand to
4. moute	coulact	
5.		
6. Be carr	eral of Dis	de pointe aux
7. back (N)	iver where	houstime Drums
8.	7	1
9.		

Date: 9 / /3 / 04		Time: 7:40
Site Health and Safety Officers(s)	ë Ë	
A	ATTENDEES	SIGNATURE
1. Wat fun		11.
2. July Bush		12.

6.

8.

10,

ACENDA

14. 15.

16. 17.

18. 19.

20.

	AGENDA	
1. Polling	zeus is a good opertunity to mur oves to	ach
2. Use pro	er lother technique bevo at kores las	7
3. with 1	en listing technique, beno at knees, lift, point twist and lift, ask for help w	Lus
4. NEEDED		
5,		
6.		
7.		
8.		
9.		

Date: 9 / 14 / 04	Time: 4.40
Site Health and Safety Officers(s)	•
ATTENDEE	S SIGNATURE
1. That loves	11.
2. Marles a name	12.
3. THowarks	N13.
4. Dather Salegar	14.
5. Gill Thomas	15.
6.	16.
7.	17.
8.	18.
9.	20.19.
10.	20.
AG:	ENDA
1 ha had	ive Drill vice oner the
2. same hole to par	so there will be
3. much mayenest of	larco velvelos un the
4. Limber VISION, TRE	aware at all times
	lean of extra tools
6. and watch offer	4

Date: 9 1 15 104	Time: (0:50
Site Health and Safety Officers(s)	
ATTENDEE	S SIGNATURE
1. West land	11.
2. Honocha	12.
3. Michael Minni	13.
4.	14.
5.	15.
6.	16.
	17.
	18.
9.	19
10	20.
•	
	ENDA
1. We will be away Draw	s whit with Down
	the Dun clamp Keep
	ap before operation
	heach other when
5. operating this machine	j
6. UNDER a Suspenden D	why.
8.	
9.	

Layne Christensen Company Job Site Safety Date 9/2/04 Site: TEAD Phase II RFI @SWMU-58 (D-12) Client: USACE	
Rig/Crew: Tom Koro / Mike Winmill / Nate Salazar	
Observers: Matt Ivers / Carl Cole Kleinfelon / USACE	
	۷/A
	=
	Ξ
	<u></u>
	Ξ_
	<u> </u>
DOT physical card, CDL and logbooks present and up to date? D D Emergency numbers/HASP present and posted?	一,
Comments:	
Site Set-up and Safety	
Hole openings covered or tied off? ☐ ☐ ☐ ☐ Timbers and set-up jacks stable? ☐ ☐ ☐	
Anchor guy lines secure, evenly Mud or circulation pits barricaded tensioned and flagged? Mud or circulation pits barricaded or fenced?	
Excavation permit (CA) and shoring Traveling blocks, widow makers and elevators inspected?	<u></u>
Site clean and organized? Föoting?	/
Pipe blocked and sloped from work area?	
Overhead and underground lines identified? Chemicals stored away from fuel and protected?	<u> </u>
Material Safety Data Sheets present? 🖸 🛘 🗘 Warning signs/Exclusion zone posted?]
Comments:	
Rig Safety	
Kill switch operational?	 1
Vehicle pretrip inspection performed and documented? Seat beits available and used on all	
Fire extinguisher present and charged?	
Pages points cotor coded?	
Stide quarticities an electron start.	
Tentre and sectoring whater annual 22 CT	
Good housekeeping in vehicle cabs? □ □ □ Spill control materials present? © □ □ ©	

DAILY DRILL RIG INSPECTION CHECKLIST

D-12

Employee Name:	Matt Ivers /	Tous Kern	Date: 9/7/04	···· <u>·</u> -·
Type/Make/Mode Project Location:	el of Equipment: <u>AF</u> TEAD Phase TL 1	1000 Becken Hung	License Plate Number:	

CHECKESIE	Ness.	170	EN/ATE	1	
Are adequate and serviceable fire extinguishers provided?	V			-5-2	Ŀ
Is a first aid kit provided?	1	 	 	"	_
Are all wire rope cables in good condition?	1				
Are wire rope, sockets, splices, thimbles, and clips adequate and properly applied?	~				
Are hooks, safety nooks, shackles, rings, etc. in good condition?	V				
Are drums for load lines equipped with at least one positive holding device, applied directly to the motor shaft or some part of the train gear?	/				
Are operating levers equipped with latch or other devices to prevent accidental starting?	1				
Are belts, gears, shafts, electrical contacts, etc. adequately guarded?	1				
Are tires in good condition and properly inflated?					
Is acceptable spark arrestor installed and working?					
Are required pressure, temperature, and relief gauges and valves installed and operable?	1				
Are hydraulic jacks in good condition and operable?	1				
Is "kill" or "deadman" switch operational?	1				
Are adequate headlights, tail-lights, and turn signals provided and in proper operating condition?			/		
Are brakes in proper operating condition?	T			i i	
Do windshields have wipers in proper operating condition?	- 				
Are rear view mirrors provided?	1				
Are reverse signal alarms on equipment?					
Are all glasses in operator's compartment safety glasses and in good repair?	1				
Are seat belts provided?	 			ı	
Is recommended preventative maintenance being followed?	1				

ADDITIONAL REMARKS: Five extinguisher on truckness charging Employee Signature



Layne .C	hriste	nsen	Comp	any Job Site Safety		>-12	
Date 9/8/04 Site: TEAD	Phase	II	efI (6 SWMU 58 Client: USAC	E	7). 7)	
Rig/Crew: Tom Kenn, Nate Sa	lazan	, ol	ke a		· · · · · · · · · · · · · · · · · · ·		
Observers: Matt /vers (asl	Cole	J.	11 TI	homa s			
Crew Safety/PPE	YES	NO	N/A		YES	NO	N/A
Hard Hat	8	D	0 .	Safety Glasses	9/	====	
Lifting Belt	₽′	. 🛮	O.	Training Certificates		D D	Ę
Gloves	₽⁄	0		Hearing Protection	6 /		
Safety Shoes	2/		0	Proper Clothing		C	
Layne Safety Practice Manual			₽⁄	Dust masks/Level C respirators	0	<u> </u>	E/
DOT physical card, CDL and logbooks present and up to date?			N	Emergency numbers/HASP present and posted?			
				<u> </u>			
rive examquia	SUCA	on	rig	has been recharged	SINCE	0	
yesterday							
<u> </u>							
Site Set-up and Safety							
Hole openings covered or tied off?	0	а	<u>t</u>	Timbers and set-up jacks stable?	- <u>Q</u>		<u> </u>
Anchor guy lines secure, evenly tensioned and flagged?	D.		0	Mud or circulation pits barricaded or fenced?	a	0	رو
Excavation permit (CA) and shoring considerations?	D	0	13 /	Traveling blocks, widow makers and elevators inspected?	0	Ø	₽.
Site clean and organized? Footing?	<u> </u>	0		Bulk fuel stores lined and grounded?		0	9
Pipe blocked and sloped from work area?	2	<u> </u>	о·	Correct monitoring equipment present?	Ξ		<u> </u>
Overhead and underground lines identified?	<u> 5</u>			Chemicals stored away from fuel and protected	? 0		<u></u>
Material Safety Data Sheets present?	ŒY.	<u> </u>	O.	Warning signs/Exclusion zone posted?	5/	= -	<u> </u>
Comments: Rapiator fluis a Sheeting un	sp.11	e b	4 es	werray laubob on p	lastic	•	
Rig Safety							
Xill switch operational?	ē	0	0	All mast wiring in conduits?	₽.	C	₽
Vehicle pretrip inspection performed and documented?		0	₂ /	Seat belts available and used on all equipment?	0	0	2/
Fire extinguisher present and charged?	3	D		First aid/BBP kit present and stocked?	8	0	-
Danger points color coded?	G	<u></u>		Controls identified?	<u> </u>	□	G
Side guardrails on platform rigs?		0	9	Ropes and chains in good condition?	0/	0	<u> </u>
Betts and rotating shafts guarded?	10	0	<u> </u>	All hooks have safety latches?	2/	<u> </u>	Ç
Cables in good shape, clamps installed properly?	ß			Pressure hoses safety chained at connections?	سي	□	3
Good housekeeping in vehicle cabs?		₽	9	Spill control materials present?	ī	Ξ.	س <u>ت</u>

Layne C	Layne Christensen Company Job Site Safety						
Date 9/9/04 Site: TEAD	Phas	e II I	IFI (d	SWMU 58 Client: USACE		-12	 ,
Date 9/9/04 Site: TEAD Rig/Crew: Tom Kern, Nate Sa Observers: Mett lucys	laza	2, M	like	Winnell			
Observers: Matt loevs							
Crew Safety/PPE	YES	NO.	N/A		YES	NO	N/A
Hard Hat	⁄ي	0		Safety Glasses	- Z		
Lifting Belt	8		. 🗅	Training Certificates			<u>۔۔۔۔</u>
Gloves	₽⁄		0	Hearing Protection	₽′		=
Safety Shoes	0/	D	D	Proper Clothing	Q		0
Layne Safety Practice Manual	G		B /	Dust masks/Level C respirators	Ω	Ö	<u></u>
DOT physical card, CDL and logbooks present and up to date?	; 		~	Emergency numbers/HASP present and posted?	<u></u>	- - -	D.
Comments:	·-·-·	•			 -		-
							·
Site Set-up and Safety							
Hote openings covered or tied off?				Timbers and set-up jacks stable?	5 /		0
Anchor guy fines secure, evenly tensioned and flagged?			9	Mud or circulation pits barricaded or fenced?	0	0	<u> </u>
Excavation permit (CA) and shoring considerations?		0	9	Traveling blocks, widow makers and elevators inspected?	0		′~ت
Site clean and organized? Footing?	9	0		Bulk fuel stores lined and grounded?	0		_ _
Pipe blocked and sloped from work area?	u /	0	O	Correct monitoring equipment present?	<u> </u>	0	
Overhead and underground lines identified?	8/	0		Chemicals stored away from fuel and protected?	0	₽	
Material Safety Data Sheets present?	0			Warning signs/Exclusion zone posted?	•		
Comments: J. 11 Thomas appeo	the	s to (lowe	ug items yesterbay			
Comments: J.11 Thomas aboed	73.	etter	es 1	Fluiplevels &			
HOUNS V	B.	rake	s v	,			
Lights V	W	per	<u>د د</u>	<u> </u>			
Rig Safety	- :						
Kill switch operational?	B		Ο,	All mast wiring in conduits?	G.	φ.	□
Vehicla pretrip inspection performed and documented?			₽′	Seat belts available and used on all equipment?			<u></u>
Fire extinguisher present and charged?	Q /	0	o.	First aid/BBP kit present and stocked?	8	0	0
Danger points color coded?	a	0	© ∕:	Controls identified?	2	o o	0
Side guardrails on platform rigs?	∞ ∕	В		Ropes and chains in good condition?	<u>.</u>		C
Belts and rotating shafts guarded?	2/		0	All hooks have safety latches?	<u>.</u>	0	c
Cables in good shape, clamps installed properly?	a ⁄	0		Pressure hoses safety chained at connections?	2	0	<u> </u>
Good housekeeping in vehicle cabs?		0	2/	Spill control materials present?	9		Ξ

Layne	Christ	ensen	Com	pany Job Site Safety	<u>~</u>	-12	-
TEA	D Phi SWM	se I	[/2		<u>- r</u> 5	<u></u>	
Rig/Crew: Tourkers, Nate S	alaza	<u>, </u>	like	Www. (Allfield rehi)	
Observers: Matlluers, I	cff	Bu	se 100	<u></u>			
Crew Safety/PPE	YES	NO.	N/A		YES	NO	N/A
Hard Hat		. 0		Safety Glasses	Q.	-	0
Lifting Selt	ď			Training Certificates	89/	0	Ξ.
Gloves	<u>\$\cdot \cdot \cdo</u>	0		Hearing Protection	0/	<u></u>	=
Safety Shoes	W		O	Proper Clothing	5 ⁄	C	Ξ.
Layne Safety Practice Manual	-57			Dust masks/Level C respirators	<u> </u>		<u>.</u>
DOT physical card, CDL and logbooks present and up to date?	' _@	(С	Emergency numbers/HASP present and posted?			
Comments:							_==
•							
Site Set-up and Safety		j.					
Hole openings covered or tied off?	ď	٥		Timbers and set-up jacks stable?			
Another guy lines secure, evenly tensioned and flagged?	<u>o</u> ⁄			Mud or circulation pits barricaded or fenced?			
Excavation permit (CA) and shoring considerations?	<u>&</u>	0		Traveling blocks, widow makers and elevators inspected?	·		
Site clean and organized? Footing?	⊕ ∕	8	0	Bulk fuel stores lined and grounded?			
Pipe blocked and sloped from work area?	D2		Ö	Correct monitoring equipment present?	32/		
Overhead and underground lines identified?	<u> </u>			Chemicals stored away from fuel and protected?	<u></u>	<u> </u>	
Material Safety Data Sheets present?	3			Warning signs/Exclusion zone posted?	3/		
Tires, Homs, Lights, bo	attevi	es, k	orake	es, wipers, fluid herels i			
Rig Safety							
Kill switch operational?	œ́			All mast wiring in conduits?	Y .	0	
Vehicle pretrip inspection performed and documented?	a		0	Seat belts available and used on all equipment?	0	0	
Fire extinguisher present and charged?	GV	0		First aid/BBP kit present and stocked?	50/		_ _
Danger points color coded?	Ū∕_	0	0	Controls identified?	<u>-</u>	 	_ <u></u> _
Side guardrails on platform rigs?	58/			Ropes and chains in good condition?	02		_
Belts and rotating shafts guarded?	O/	0	0	All hooks have safety latches?	<u>v</u>		₽
Cables in good shape, clamps installed properly?	œ	ū	0	Pressure hoses safety chained at connections?	₹		
Good housekeeping in vehicle cabs?	3		0	Spill control materials present?	<u> </u>		

Layne	Christ	enser	ı Com	pany Job Site Safety	<u> </u>	12	
))				TESUMU 58 Client: USACE		1-12	·———
RigiCrew: Took Keru, Nate Sc	Star,	Miles	· Wi	a vecl	. .	~	
Observers: Matt luess, Jeff	Bigeloa	ر					
Crew Safety/PPE	YES	NO	N/A		YES	NO	N/A
Hard Hat	8	D		Safety Glasses	e/	/*	
Lifting Belt	©		Ω.	Training Certificates	<u> </u>		 -
Gloves	₽/		. 0	Hearing Protection	-		<u>_</u> _
Safety Shoes	1	_ ·o	0	Proper Clothing	<u> </u>		
Layne Safety Practice Manual	0	٥	2	Oust masks/Level C respirators		 _	
DOT physical card, CDL and logbooks present and up to date?	, –	0	© /	Emergency numbers/HASP present and posted?	<u> </u>		
Comments:		•••	2				
				and the second of the second o			
2							
Site Set-up and Safety	<u> </u>						
Hale openings covered or tied off?		Ö	8	Timbers and set-up jacks stable?	192		
Anchor guy lines secure, evenly tensioned and flagged?	О	0	9	Mud or circulation pits barricaded or fenced?	<u>.</u> .		
Excavation permit (CA) and shoring considerations?		0	<u> </u>	Traveling blocks, widow makers and elevators inspected?	_ _		
Site clean and organized? Footing?	2/	a	0	Bulk fuel stores lined and grounded?		<u>_</u>	
Pipe blocked and stoped from work area?	9	۵		Correct monitoring equipment present?	<u> </u>	_ _	<u>=</u>
Overhead and underground lines identified?	8	<u> </u>		Chemicals stored away from fuel and protected?	<u>~</u>	 	
Material Safety Data Sheets present?	9			Warning signs/Exclusion zone posted?	~/ ~/		
Tires, Horns, Lights, b	oatteri	es, k	orako	es vipes, fluid texts		<u></u>	
Rig Safety	: . ز	41 W. 1					
Kill switch operational?	e)	О	۵	All mast wiring in conduits?	<u>.</u>		0
Vehicle pretrip inspection performed and documented?		0	2	Seat belts available and used on all equipment?			سع
fire extinguisher present and charged?	52		0	First aid/BBP kit present and stocked?		<u> </u>	
Danger points color doded?	0	D	0	Controls identified?			<u> </u>
Side guardrails on platform rigs?	5	0	0	Ropes and chains in good condition?	<u>-</u>	 	
Belts and rotating shafts guarded?	اً ا	D		All hooks have safety latches?	<u>-</u>		_ _
Cables in good shape, clamps installed properly?	· G/	0		Pressure hoses safety chained at connections?	<u>.</u>	<u> </u>	
Good housekeeping in vehicle cabs?	Д	<u> </u>	9/	Spill control materials present?	<u> </u>		_

Christ) Doc-		none lab Chi Ci i			
Christi	ensen	Com	pany Job Site Safety	<u> </u>	-12	
D Pho	se.	II k	PFI@SWWU-58 Client: USAC	<u> </u>		
Sala	2001	, M	ike Wiwoull			
···					-	
YES	NO.	N/A		YES	NO	N/A
⊌′	0	0	Safety Glasses	52/		
<u> </u>		0	Training Certificates	52 ∕		 5
<u> </u>	0		Hearing Protection	G/		 -
₹	<u> </u>		Proper Clothing	E.	C	
	<u> </u>	<u>ec</u>	Dust masks/Level C respirators			
1 			Emergency numbers/HASP present and posted?	70/		
					<u>.</u>	
	:	·				
	a	5	Timbers and set-up jacks stable?			
	0	19	Mud or circulation pits barricaded or fenced?			_ <u></u>
0	0	Q /	Traveling blocks, widow makers and elevators inspected?			<u></u>
<u>8</u>	0		Bulk fuel stores lined and grounded?			
<u>a/</u>	0		Correct monitoring equipment present?	<u>-</u>		<u></u>
<u> </u>	D	a	Chemicals stored away from fuel and protected?	9/		
0/		0	Warning signs/Exclusion zone posted?	0	<u></u>	
alterio	25, k	vake	es, viepen, Philos tevels.			
rà e	0	0	All mast wiring in conduits?	Œ.	0	C
	0	9	Seat belts available and used on all equipment?	П		
<u> </u>		0	First aid/BBP kit present and stocked?	<u> </u>		_
	0	9	Controls identified?	<u>-</u>		=======================================
D/		0	Ropes and chains in good condition?			_
<u>8</u>	0		All hooks have safety latches?	%	Э	9
<u>e/</u>	0		All hooks have safety latches? Pressure hoses safety chained at connections?	5 ∕	<u>o</u>	9
	YES Sola	YES NO YES NO O O O O O O O O O O O O	Phase II R Salazan, M YES NO N/A O O O O O O O O O O O O O O	YES NO. N/A YES N	Phase II RFIC SUNU-58 Client: USACE Sclazor, M. Ke Wevacell YES NO. N/A YES G	PROBLET RETESCIONU-58 Client: USACE Sclazar, Mike Williamses G G G Safety Glasses G G G Training Certificates G G G D Safety Glasses G G G D Training Certificates G G G D Safety Glasses G G G D Training Certificates G G G D Dust masks/Level C respirators G G D Dust masks/Level C respirators G G D Safety Glasses G G G G D Safety Glasses G G G G G G G G G G G G G G G G G G G

							
Layne C	hriste	nsen	Comp	pany Job Site Safety	D-	12	
Date 9 15 04 Site:	Phas	e II j	LFI (2 SWMW 578 Client: USAC	ϵ		
Rig/Crew: Tom Kern, Mik	e h	liw u	ull			-	
Observers: Hatt lueng							
Crew Safety/PPE	YES	NO.	N/A		YES	NO	N/A
Hard Hat	<u>6</u> /		0	Safety Glasses	سج		_ <u>'''^</u>
Lifting Belt	של	0	0	Training Certificates			— <u>=</u>
Gloves	a /	О	Ω.	Hearing Protection	9/	C	= =
Safety Shoes	D/		۵	Proper Clothing	12	С	=======================================
Layne Safety Practice Manual	. O		8	Oust masks/Level C respirators	0	Ω	_ <u>:</u> _
DOT physical card, CDL and logbooks gresent and up to date?	1 D			Emergency numbers/HASP present		-	
Comments:		0		and posted?	<u></u>		_==
				,			
Site Set-up and Safety		<u></u>		<u> </u>			
Hole openings covered or tied off?	D	a	_8_	Timbers and set-up jacks stable?	<u> </u>		G
Anchor guy lines secure, evenly tensioned and flagged?		a	G/	Mud or circulation pits barricaded or fenced?	<u> </u>		
Excavation permit (CA) and shoring considerations?	0		<u> </u>	Traveling blocks, widow makers and elevators inspected?			
Site clean and organized? Footing?	<u> </u>	Q.	O.	Bulk fuel stores lined and grounded?	 	. <u> </u>	_
Pipe blocked and stoped from work area?	D /		0	Correct manitoring equipment present?	2/		Ξ
Overhead and underground lines identified?	8	0	0	Chemicals stored away from fuel and protected?			
Material Safety Data Sheets present?	<u> </u>	D	0	Warning signs/Exclusion zone posted?	T.		□
Tires, Homs, Lights; bo	itteria	25, K	vake	es, wiper, fluid herels			
Rig Safety							
Kill switch operational?	è	0		All mast wiring in conduits?	S.	9	C
Vehicle pretrip inspection performed and documented?		0	19	Seat belts available and used on all equipment?		0	
Fire extinguisher present and charged?	52	C	0	First aid/BBP kit present and stocked?	0/		C
Danger points color coded?	0			Controls identified?	,o/	۵	2
Side guardrails on platform rigs?	9 /		G.	Ropes and chains in good condition?	(C)	ā	5
Belts and rotating shafts guarded?	0	0	0	All hooks have safety latches?	s/	J	
Cables in good shape, clamps installed properly?			0	Pressure hoses safety chained at connections?	2	<u> </u>	=
Good housekeeping in vehicle cabs?	0	0		Spill control materials present?	3/	9	<u> </u>

				pany Job Site Safety	D-	12	
Date 9/16/04 Site: TEA	D Ph	ase I	I R	F1 @SWMU58 Client: USAC	E		
Rig/Crew: Tom Kerv, Node	Salaza	21, E	30b H	ypelman			
Observers: Matt lvers							
Crew Safety/PPE	YES	NO.	N/A		YES	. NO	N/A
Hard Hat	G/	0		Safety Glasses		7 -=	<u> </u>
Lifting Belt (Hunness)	g/		ū	Training Certificates			
Gloves	⊚⁄	0	0	Hearing Protection			 _
Safety Shoes	g/	0	Ö	Proper Clothing	0	- -	
Layne Safety Practice Manual	D	ū	<u> </u>	Dust masks/Level C respirators			
DOT physical card, CDL and logbooks present and up to date?		0	8/	Emergency numbers/HASP present and posted?			
Comments: Crew has how	vela	l as	uew	is rig and its support	111	700	<u></u>
Site Set-up and Safety		υς 		s rig and its support a	ekic	les 	
Hole openings covered or tied off?	<u> </u>			Timbers and set-up jacks stable?			
Anchor guy lines secure, evenly tensioned and flagged?			_ <u>_</u>	Mud or girculation pits barricaded or fenced?			<u>0</u>
Excavation permit (CA) and shoring considerations?	,	0	<u>.</u>	Traveling blocks, widow makers and elevators inspected?	<u> </u>		
Site clean and organized? Footing?	₽∕	Ö	D	Bulk fuel stores lined and grounded?	0		
Pipe blocked and stoped from work area?	53 /	0	Ο.	Correct monitoring equipment present?	2		
Overnead and underground lines identified?	<u> </u>	Ò	a	Chemicals stored away from fuel and protected?	52/		
Material Safety Data Sheets present?	<u> </u>			Warning signs/Exclusion zone posted?	<u></u>	3	<u> </u>
Tires, Homs, Lights; bo	itterie	es, k	orake	es, wipers, Philod hevels v	, ·		
Rig Safety							
Kill switch operational?	œ	0	a	All mast wiring in conduits?	₽.	9	
Vehicle pretrip inspection performed and documented?	0		g	Seat belts available and used on all equipment?	0	0	
Fire extinguisher present and charged?				First aid/BBP kit present and stocked?		<u> </u>	
Danger points color coded?	0	0	D	Controls identified?			
Side guardrails on platform rigs?	ឱ		9	Ropes and chains in good condition?	© /		<u>~</u>
Belts and rotating shafts guarded?		Ü	0	All hooks have safety latches?	9 /	<u> </u>	
Cables in good shape, clamps installed properly?	9/	0	0	Pressure hoses safety chained at connections?		0	Ξ ;
Good housekeeping in vehicle cabs?	ū			Spill control materials present?	2		

										
Layne Christensen Company Job Site Safety D-12										
Date 9/17/04 Site: 7840	Phas	e II	2Fl	@ SWMU 58 Client: USACE	<u>, </u>					
Rig/Crew: Tom Kern, Wax.	<u> </u>	laz	er, T	Padrick Mc Gannon						
Observers: Matt (vers, Carl	Col	e								
Crew Safety/PPE	YES	NO.	N/A		YES	NO.	N/A			
Hard Hat	مستق		D	Safety Glasses	<u> </u>		<u></u>			
Litting-Belt Hanses	₽^		ם	Training Certificates						
Gloves -	⁄ ي			Hearing Protection			_ _			
Safety Shoes	<u>G</u>	0	٥	Proper Clothing	9	<u></u>	<u>=</u>			
Layne Safety Practice Manual		O	<u> </u>	Dust masks/Level C respirators	C					
DOT physical card, CDL and togbooks present and up to date?	~/									
Comments: VS /		1D:	M	and availlary						
						,				
compressor	2010	ac v	70	O K H						
		_								
Site Set-up and Safety										
Hale openings covered or tied off?	0	<u>ū</u>		Timbers and set-up jacks stable?		<u> </u>				
Anchor guy lines secure, evenly tensioned and flagged?			9	Mud or circulation pits barricaded or fenced?	<u> </u>	_ _ _				
Excavation permit (CA) and shoring considerations?	0	0	<u> </u>	Traveling blocks, widow makers and elevators inspected?			<u></u>			
Site clean and organized? Footing?	2			Bulk fuel stores lined and grounded?						
Pipe blocked and sloped from work area?	8		0	Correct monitoring equipment present?	<u> </u>	, 				
Overhead and underground lines identified?	9	0	0	Chemicals stored away from fuel and protected?		 _	_ _			
Material Safety Data Sheets present?	<u> </u>			Warning signs/Exclusion zone posted?		_ <u>_</u> _	<u></u> _			
Comments: Tires, Horns, Lights, bo	tterie	25, k	vak	es, wipers, fluid herels						
Rig Safety		an Viet								
Kill switch operational?	è			All most wiring in conduits?		<u> </u>				
Vehicle pretrip inspection performed and documented?		Ö	D	Seat belts available and used on all equipment?		<u> </u>				
Fire extinguisher present and charged?	B		0	First aid/BBP kit present and stocked?	<u> </u>	<u>.</u>	_ _			
Danger points color coded?	0	0		Controls identified?	سم	<u></u>				
Side guardraits on platform rigs?	0	Q	9	Ropes and chains in good condition?			_ _			
Belts and rotating shafts guarded?	<u>u</u>	Ö	0	All hooks have safety latches?	<u>-</u>		_ 			
Cables in good shape, clamps installed properly?	a /	0	0	Pressure hoses safety chained at connections?			_ 			
Good housekeeping in vehicle cabs?										

-

B							
				pany Job Site Safety	D-	12	
Date 9/20/04 Site:	> Phas	e #	FF]	Client: USACE		<u> </u>	
Aig/Crew: Tom Kere, Nate	! 5a	laza	21, A	Have Kyle			
Observers: Matthus							
Crew Safety/PPE	YES	NO.	- N/A		YES.	NO.	 N/A
Hard Hat	8			Safety Glasses		7 -	
histing Beh Howess	@/		Q	Training Certificates			
Gloves	8	0	ū	Hearing Protection			— <u> </u>
Safety Shoes	D/	۵		Proper Clothing	<u> </u>		— <u>-</u> E
Layne Safety Practice Manual		0	<u> </u>	Dust masks/Level C respirators			
DOT physical card, CDL and logbooks present and up to date?	1		0	Emergency numbers/HASP present and posted?			
Comments: Becker Hamme	en A	P100	3O			<u>—</u> _	
Sulair 900 Kl Drum Truck	K /	Δ11. N					
Drum Truck	ה בני לוגע	out p	E	Š			
	ren		000	,	-11	 .	
Site Set-up and Safety	<u> </u>	• .	· 	a			
Hole openings covered or tied off?	<u> </u>	O	9	Timbers and set-up jacks stable?	5/		<u> </u>
Anchor guy lines secure, evenly tensioned and flagged?		0	10/	Mud or circulation pits barricaded or fenced?	9	0	
Excavation permit (CA) and shoring considerations?		O	ره_	Traveling blocks, widow makers and elevators inspected?	0		
Site clean and organized? Footing?	0	Ė	0	Bulk fuel stores lined and grounded?			
Pipe blocked and sloped from work area?	0/			Correct monitoring equipment present?	<u> </u>		_ _ _
Overhead and underground lines identified?	<u>~</u>	О		Chemicals stored away from fuel and protected?	-C		
Material Salety Data Sheets present?	0			Warning signs/Exclusion zone posted?	_و_	/	
Tires, Horns, Lights, bo	ittevi	es, k	orako	es, wipers, fluid herels	/		
Rig Safety		- 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	urine Design				-
Kill switch operational?	È			All mast wiring in conduits?	₽.	9	0
Vehicle pretrip inspection performed and documented?	W.	0	2	Seat belts available and used on all equipment?			
ire extinguisher present and charged?	2	0		First aid/BBP kit present and stocked?	0	_ 	
Danger points color coded?			6	Controls identified?	9	D D	9
Side guardrails on platform rigs?	0			Ropes and chains in good condition?	E /	a	
Belts and rotating shafts guarded?	2	0		All hooks have safety latches?	<u>_</u>	 	
Cables in good shape, clamps installed properly?	©/	0	0	Pressure hoses safety chained at connections?		<u> </u>	
Good housekeeping in vehicle cabs?	×			Spill control materials present?			<u> </u>
							

	<u> </u>								
· [pany Job Site Safety		12	<u></u> _		
Date 9/21/04 Site: @	SWI	hage uv	II 76 58	Client: USA	<u>(E</u>				
Rig/Crew: Tom Kern, Nos	le 5	la:	عمب	Dave Kyle					
1	المين	<u>(o</u>	(e						
Crew Safety/PPE	YES	NO.	N/A	· ·	YES	NO	N/A		
Hard Hat	_ 0	<u> </u>		Safety Glasses		=======================================			
thing Bell harvess	Training Certificates			<u></u> _					
Gloves		/ 0		Hearing Protection			_ _		
Safety Shoes	<u>Q</u>	′ 0		Proper Clothing	<u> </u>	 	<u>-</u>		
Layne Safety Practice Manual									
DOT physical card, CDL and logbooks present and up to date?	1 0	0		Emergency numbers/HASP present and posted?					
Comments: Schoaum - C	DEX	Y -1	· · ·	Prom truc	k V				
Solar 900x	(4(cow	Dues:	sov					
ODEX you to	ر بر اے ہے۔	< 1/							
Site Set-up and Safety	······································				-				
Hale openings covered or tied off?		0	B /-	Timbers and set-up jacks stable?					
Anchor guy lines secure, evenly tensioned and flagged?			<u>.</u>	Mud or circulation pits barricaded or fenced?					
Excavation permit (CA) and shoring considerations?	<u> </u>		<u>-</u>	Traveling blocks, widow makers and elevators inspected?		0			
Site clean and organized? Footing?	<u> </u>			Bulk fuel stores lined and grounded?	<u></u>				
Pipe blocked and stoped from work area?	9/			Correct monitoring equipment present?	<u></u>	 			
Overhead and underground lines identified?				Chemicals stored away from fuel and protected			=		
Material Safety Data Sheets present?	5			Warning signs/Exclusion zone posted?		_ 	_ 		
Comments: Tires, Horns, Lights, bo	riter	es, l	brake	es vipes, Philod bevels.			<u>-</u>		
Rig Safety							 .'		
Kill switch operational?	Ġ	0		All mast wiring in conduits?	<u>o</u> .				
Vehicle pretrip inspection performed and documented?	<u>a</u>		<u>o/</u>	Seat belts available and used on all equipment	<u> </u>	a	1		
Fire extinguisher present and charged?	œ/	0	0	First aid/88P kit present and stocked?		<u>.</u>	<u></u>		
Danger points color coded?	0	Ö	CS/	Controls identified?	<u>e</u>	<u>.</u>	<u>.</u>		
Side guardrails on platform rigs?		Ö	0	Ropes and chains in good condition?	<u>~</u>				
Belts and rotating shafts guarded?	12/	D D	0	All hooks have safety latches?		3	<u>=</u> =		
Cables in good shape, clamps installed properly?	B			Pressure hoses safety chained at connections?	5	<u></u>	<u> </u>		
Sood housekeeping in vehicle cabs?	131/	0		Spill control materials present?	<u></u>	<u> </u>			

	78.00						<u></u> _
				pany Job Site Safety	D	-12	
1 0/ /	0 Phas 5W8	-		Client: USACE			
•			<u> </u>				
Rig/Crew: Tow Kern Note	e Sal	aza	1, C	Pave Kyle			_ <u>_</u>
Observers: Mext luess, Ca	<u>n(C</u>	ole					
Crew Safety/PPE	YES	NO-	N/A		YES	NO	N/A
Hard Hat			D	Safety Glasses	2		_ <u></u>
Litting Belt horvess	<u> 9</u> /	_ []	0	Training Certificates			
Gloves			D	Hearing Protection	10/		
Safety Shoes	TC/		0	Proper Clothing	- P		
Layne Safety Practice Manual	Ð		<u> </u>	Dust masks/Level C respirators		— 	
DOT physical card, CDL and logbooks present and up to date?) 	0	©	Emergency numbers/HASP present and posted?			
Becker Haumer Shraum Rob Touch Drow Truck							
Site Set-up and Safety		j -	4.				
Hole openings covered or tied off?	D.	0	11 /	Timbers and set-up jacks stable?	ارج		
Anchor guy lines secure, evenly tensioned and flagged?		<u></u>	P	Mud or circulation pits barricaded or fenced?	_ 		
Excavation permit (CA) and shoring considerations?	<u> </u>	5		Traveling blocks, widow makers and elevators inspected?	<u> </u>	_ 	<u> </u>
Site clean and organized? Footing?	□ 2	0	0	Bulk fuel stores lined and grounded?	_ 		— } _
Pipe blocked and sloped from work area?	<u> •</u>	0		Correct monitoring equipment present?			<u></u>
Overhead and underground lines identified?	2/			Chemicals stored away from fuel and protected?		- 	
Material Safety Data Sheets present?	<u>rg</u>	0	ם	Warning signs/Exclusion zone posted?	<u> </u>	_ _	_
Tires, Horns, Lights, bo		s, k	orake	is, wiper, fluid texts /			
Rig Safety							
Cill switch operational?	<u> </u>	<u> </u>	0	All mast wiring in conduits?		<u> </u>	
/ehicle pretrip inspection performed and locumented?			8	Seat beits available and used on all equipment?	0	<u> </u>	
ire extinguisher present and charged?	D /	0	D	First aid/BBP kit present and stocked?	<u>-</u>	<u>-</u>	<u>-</u>
Danger points color coded?	0	0	02/	Controls identified?		<u>.</u>	<u>.</u>
iide guardrails on platform rigs?		0	<u>G</u>	Ropes and chains in good condition?		<u></u>	
elts and rotating snafts guarded?	12/	Ω	1	All hooks have safety latches?	<u>-</u>	<u></u>	
ables in good shape, clamps installed property?	Z	٥		Pressure hoses safety chained at connections?		<u></u>	
ood housekeeping in vehicle cabs?	0		/1	Spill control materials present?	5/	<u></u> -	

Layne Christensen Company Job Site Safety D-12											
					ν	12	 -				
Date 9/23/04 Site: Teat	> Phase	12 1	VFI &	SWMV 58 Client: DSAC	5						
RigiCrew: Tom Kern, Nate So	loza	2 F	icki	Smith							
Observers: Matt lvers Carl	(61	e_				· ·					
Crew Safety/PPE	YES	NO.	N/A		YES.	NO	N/A				
Hard Hat	2	_ O	Q	Safety Glasses	<u>۔</u>	 _	_ 				
titting Belt harvess	ing Bell Larness U [] Training Certificates										
Glaves -		۵		Hearing Protection	<u> </u>		_ <u>=</u> _				
Safety Shoes		<i>'</i>	۵	Proper Clothing			 				
Layne Safety Practice Manual	0			Oust masks/Level C respirators	 	<u></u> _					
DOT physical card, CDL and logbooks present and up to date?				Emergency numbers/HASP present and posted?	~ ~~ ~~						
Comments: Growt Plant Draw Truck Braker Hammer						•					
Site Set-up and Safety							 -				
Hote openings covered or tied off?			<u>P</u>	Timbers and set-up jacks stable?	<u></u>	<u> </u>	— <u>—</u>				
Anchor guy lines secure, evenly tensioned and flagged?				Mud or circulation pits barricaded or fenced?	<u> </u>		 ~!				
Excavation permit (CA) and shoring considerations?	0			Traveling blocks, widow makers and elevators inspected?	D	<u>_</u> _					
Site clean and organized? Footing?	₽/	0	Ð	Bulk fuel stores lined and grounded?	- <u>-</u>		_ <u></u>				
Pipe blocked and stoped from work area?	52			Correct monitoring equipment present?	- <u>-</u>	<u></u>	_ 				
Overhead and underground lines identified?	5 /	<u> </u>	0	Chemicals stored away from fuel and protected?	<u> </u>	. <u>-</u>	- 				
Material Safety Data Sheets present?	~	0	Ð	Warning signs/Exclusion zone posted?	- - -		_ 				
Tires, Horns, Lights, bo	ilterie	es, k	orake	es, wiper, fluid bevelow	/						
Rig Safety											
Kill switch operational?	<u> </u>	8		All mast wiring in conduits?	ġ.						
Vehicle pretrip inspection performed and documented?	0		B	Seat belts available and used on all equipment?							
Fire extinguisher present and charged?	2	0	0	First aid/BBP kit present and stocked?		.I .e					
Danger points color coded?	0_	0	87	Controls identified?		<u></u>	<u> </u>				
Side guardrails on platform rigs?	B _	0	0	Ropes and chains in good condition?							
Belts and rotating shafts guarded?	0	0	0_	All hooks have safety latches?	2/	<u> </u>					
Cables in good shape, clamps installed properly?	Ģ	0		Pressure hoses safety chained at connections?	<u> </u>	_					
Good housekeeping in vehicle cabs?			50/	Spill control materials present?	¥	<u> </u>	<u></u>				


Layne Christensen Company Job Site Safety 2-12												
						12						
Date 9/24/04 Site: 7can	1 wase	y rr	و رسم ر-	SWMU 58 Client: USACB			<u>-</u> _					
Rig/Crew: Tom Kern												
Observers: Math livers		. <u>.</u>			<u>-</u>	<u></u>						
Crew Safety/PPE	YES	NO.	N/A		YES.	NO	N/A					
Hard Hat	ر و	\□	0	Safety Glasses	0	7 =						
Lifting Belt	0		8	Training Certificates		٥						
Gloves	8	0		Hearing Protection	- 0							
Safety Shoes	0			Proper Clothing	Q-	_ c						
Layns Safety Practice Manual	D		0	Dust masks/Level C respirators	0		<u> </u>					
DOT physical card, CDL and togbooks present and up to date?	1	0		Emergency numbers/HASP present and posted?								
Comments: Pipe Time	\mathcal{R}_{α}		11		1							
IIID GO D	الكفك	Ker.	Manu	mer being De-Conner 2	0							
or to pay	Jamo	سسا										
·												
Site Set-up and Safety	<u>. </u>	:	S				·					
Hole openings covered or tied off?			-	Timbers and set-up jacks stable?	<u>.</u>	.□						
Anchor guy lines secure, evenly tensioned and flagged?	Ö	0	9	Mud or circulation pits barricaded or fenced?								
Excavation permit (CA) and shoring considerations?		٥	۔	Traveling blocks, widow makers and elevators inspected?			<u> </u>					
Site clean and organized? Footing?	0	0		Bulk fuel stores lined and grounded?			<u> </u>					
Pipe blocked and sloped from work area?	8	0		Correct monitoring equipment present?								
Overnead and underground lines identified?	0	0	0	Chemicals stored away from fuel and protected?	<u> </u>	- <u>-</u>						
Material Safety Data Sheets present?	0/	Q	Ð	Warning signs/Exclusion zone posted?	Ω							
Comments: Tires, Horns, Lights, bo	ulterio	es, I	oraki	es, vipes, fluid bevel -	/							
Rig Safety	<u> </u>											
Kill switch operational?	ď	0	ET .	All mast wiring in conduits?								
Vehicle pretrip inspection performed and documented?		0	e	Seat belts available and used on all equipment?	5		<u> </u>					
Fire extinguisher present and charged?	D/	G	۵	First aid/88P kit present and stocked?	5	<u> </u>						
Danger points color coded?	0	0	<u>.</u>	Controls identified?		<u></u>	_ <u></u> _					
Side guardrails on platform rigs?	0	а	0/	Ropes and chains in good condition?	2	<u> </u>	_ _					
Betts and rotating shafts guarded?		Ó	0	All hooks have safety latches?	5	<u> </u>	_ _					
Cables in good shape, clamps installed properly?	O/	0		Pressure hoses safety chained at connections?	ī	0						
Good housekeeping in vehicle cabs?	0/		0	Spill control materials present?	3/							

Lavas	Chris		. C.				
Layrie	Christ	tense	n Com	pany Job Site Safety		·	
Date 10-4-04 Site: 1	Ylun	ler	ry le	11 D-12 Client: 45AC1	<u> </u>		
Rig/Crew: Veo/io /	Jeff	Hann	nint	11 P-12 Client: 45/4C/			
Observers: JCH B146		·					
Crew Safety/PPE	YES	NO	N/A		YES	NO	 N/A
Hard Hat	ď		0	Safety Glasses			<u>```</u>
Lifting Belt	<u> </u>			Training Certificates	<u> </u>	<u>_</u> _	
Gloves	Ŀ		D.	Hearing Protection			<u>-</u> _
Safety Shoes	_O	0		Proper Clothing	02		
Layne Safety Practice Manual	0/	٥		Oust masks/Level C respirators	_ <u>-</u>	<u>_</u>	
DOT physical card, CDL and logbooks present and up to date?	1			Emergency numbers/HASP present and posted?	ئ		
Comments:	<u>-</u>						<u>=</u> .
•							
Site Set-up and Safety	<u> </u>	+ 1					 -
Hole openings covered or tied off?	0√	0		Fimbers and set-up jacks stable?			
Anchor guy lines secure, evenly tensioned and flagged?	₩	- 0	0	Mud or circulation pits barricaded or fenced?	*		_ _
Excavation permit (CA) and shoring considerations?	4 /	Д		Traveling blocks, widow makers and elevators inspected?			
Site clean and organized? Footing?	ď			Bulk fuel stores lined and grounded?			
Pipe blocked and sloped from work area?	4 /			Correct monitoring equipment present?	<u> </u>		<u></u>
Overhead and underground lines identified?	· V	Ü	σ.	Chemicals stored away from fuel and protected?			<u> </u>
Material Safety Data Sheets present?	ď⁄	0	0	Warning signs/Exclusion zone posted?	V V		
Comments: Tires, Horns, Lights, b	atteri	es, k	orake	es, wiper, fluid herels	<u>+</u>	_	<u> </u>
Rig Safety	1 2 2 1 1 2 1 1 1						· -
Kilf switch operational?	Q'	D	0	All mast wiring in conduits?	0	9	
Vehicle pretrip inspection performed and documented?		0		Seat beits available and used on all equipment?	D/	_ _	
ire extinguisher present and charged?	Ð	0	0	First aid/B8P kit present and stocked?			
Danger points color coded?	Q/			Controls identified?		<u> </u>	<u> </u>
Side guardrails on platform rigs?	₽⁄			Ropes and chains in good condition?		<u> </u>	<u> </u>
Belts and rotating shafts guarded?	□ □	0	0	All hooks have safety latches?	<u>~</u>		<u> </u>
ables in good shape, clamps installed properly?	4	<u> </u>	0	Pressure hoses safety chained at connections?	<u>V</u>	0	
lood housekeeping in vehicle cabs?	₹		0	Spill control materials present?	<u>D</u>	0	
				, modern;	.		□ .

EQUIPMENT CALIBRATION LOG Tooele Army Depot

Eqpt. Type	Serial No.	Date	Calibration Time	Calibration Gas	Calibration Gas Lot No.	Calibrated By:	Comr	nents
Environmental Instruments	580 U-60884	9/15/04	10:00	OO ISOBUTELENE 90		Matt Ivers	101.6 ppm	D-12
Photo	(9/16/04	9:45	(1	1	102.2	11
Detector 580 B		10/7/04	11:50				99.2	D-13
		11	13:40				.97.8	11
		10/11/04	8:00				97.6	-11
		10/19/04	12:05				103.4	D-16
		10/20/04	8:35				101.2	(1
		11/1/04	8:05				96.7	C-41
		11/2/04	12:55				97.6	u
		11/11/04	7:45				103.4	C-42
		11/19/04	9.25			1	(04.3	C-44
		11/22/04	9:10				104.8	11
		12/7/04	12:45				101.2	C-43
		12/30/04	7:55				103.4	D-14
		1/4/05	8:50				104.2	1(
/			9:35				102.6	N
Ψ	<i>✓</i>	1605	11:25	4	1	1	103.4	u

Attachment 7-1



				//			Hole No.	D-12	
DRII	LING L	~~ !	DIVISION	1/	LATION			SHEET /	7
1. PROJECT			Sacramento	100	2000	1 - my	Depot	OF (O SHEET	S
		Plan	eII RFI. SUMU 58	10. SIZ	E AND TYP	E OF BIT	10 " OPEN 1	Face	
2. LOCATIO	W (C	1 Mass	STI KLTI JOHO 28	11. DAT			N SHOWN (TBM or MSL)	
73677	17.94	maiee or s ? ← ∧ }	1410018,176 E		MS				
3. DRILLING	GAGENC	Y	, , , , , , , , , , , , , , , , , , , ,	1° 72	P-100	ER'S DES	cker Hawn		
	LAY			13 707	AL NO. OF	- 0V50	DISTURBED	UNDISTURBED	
4. HOLE NO). (As sho umber)	wn on draw	wing title D-12	BUF	POEN SAMP	LES TAK		NA	
S. NAME OF			V-12	14 TOT	'AI NUMBE	PCOPE	BOXES NA		\dashv
			ate Salazar, Hike Wwrull	<u></u>				<u> </u>	\dashv
6. DIRECTIO			ere seeman, the works			10010 #	ATER 339.61 (TOC		_
			D DEG. FROM VERT.	16. DAT	E HOLE			9/28/04	
Ç <u>2</u>			DEG. FROM VER!		VATION T				\dashv
7. THICKNE	SS OF OV	ERBURD	EN 346 S+				CASING 4803.	····	
8. DEPTH D	RILLED I	INTO ROC	x 24 f+		AL CORE		Y FOR BORING A	<u> </u>	-
9. TOTAL D	EPTH OF	HOLE	370 ft	13. 310	1/2/5	////	G50	949	İ
		1	CI ASSIEICATION OF MATERIA		% CORE	BOX OR	REMAR		ㅓ
TIME	DEPTH	LEGEN	(Description)	L.5	RECOV-	SAMPLE NO.	(Drilling time, wate	er loss, depth of	
	Ь.	С.	dd_		•	.,,	weathering, etc.,	ii eigniiicanu	_
9:30	-		Silty Sand (SM) 5-10%	5114			The Becken H	wanner	F
<u> </u>	_	⊒. Կ1	Med sand, Non plastic		X	1	Method allow		E
l	2		brown-bank brown 7.54R	4/2			maximum cl		-
}	` =		Moist				of 6" to be de	4	
{	_		1			ĺ	the surface t		
	4	0		ı			guantities of		-
	7 -	: ; .o.;	Rody Graveo Sano W/grav	el	}		boulders abou	رو 6 ^{اا}	
	=];;;;;;	(SW)~ 20% Gravel \$7.51				count be s	eterniaco	
	6 -	P.0%	to Subscine and to the	عد °		ર	· - •		\vdash
			to subround gravel to 4'cl	u/^	1				
	=	7.0"	MOIST, Gravels are prese	Ku suu	4				
,	8 -	100	Hand tau quarterte and gre grey investore, with trace	y to par	l4				
	=	10:0	grey (mestone, with trace sandstone) thyolite unless	s ot other as	אם ואיםור	arco			F
9:39						~			
	10-	0,00	poorly grapes gravel who so	Li			1.1 f+/min		
9:47		1000	309. fine samp s. ANG to 5	רואם דו	\times	3			F
	_	A.6.	gravel to 4 cm, DARK Brown						
,	12-	000	7.5 YR 3/2, moist, All cla	14		Ì			
		OF 81	and fines efforress s	rough		1			-
		1. 1.01	IN HCI except fresh fa	دود ۱					F
	14	0 101:	of tan quartzite.			ĺ			上
1	' _	10.4 F	(5)						-
{		120	Silty Gravel WISOUD (GM)			4			F
j	16	9 6 5	60 % Growel 25% Silt 15%				•		
]	=	0	Samp, S.A to S.R claste to		ļ				上
1		10	Pale brown 10YR 6/3, mo	ist					\vdash
	18-	1010	•		1				F-
	-	00							
9:59	\exists		1/00	, [1.3 ft/mw		
10:06	20	1:1:1	Silty Sano wigravel (SM	'		}-	11-11-11-11-11-11-11-11-11-11-11-11-11-		<u> </u>
70:02		10.11	60 % saup, 20 % gravel, 2009.	\$1 l+ [5			
	7		Growelto 6 cm, fine to men	>		ŀ			E
[,	22	;: QI.	Saud, S. A to SR. gravel, F			İ			<u></u>
		清洁清	brown 10 YR 6/3, mois		1	1			F
	, □		·	1		1			
	24	1:1:1							<u> </u>
	\exists	0	1	Ļ					F
	, ∃:	1.1.12	-as above		><	6			
:	26-			ř					
	3 J:								<u> </u>
	<u>, </u>	1.6							F
1	38 —	016						İ	_
	□	100				1		ļ	
10:20	<u>, </u>	1	And the C			[-	0.7 ft/nin		<u> </u>
10:27	30 <u> </u>	4.V.	poorly Gradeo Gravel with	$\tilde{}$		y -		ŀ	
-	7	V. Q	silt and Sand (GW-GM					Ì	
e.	2	200	55% granel, 35% samo, 10		1				_
	32	040	clasts to x cm, pale S.A	+د ا					_
<u>}</u> }	그	1	s.k., pare promu, 10 4.8	6/3		1		ŀ	_
1	34 📑	1018	moist			1		ŀ	
10:34	`' <u></u>	10314						F	
11:02	一,;	036	Silty Gravel wisaum (Gr			8		t	
··· · · · · · · · · · · · · · · · · ·	36 —	9 10	5590 gravel, 3090 silt, 1	5%		D		ŀ	
	ぱ	I OF	Sand. Gravel to 7 cm, Se					F	
	→	610et	five, SA to SR clasts. Gr	دبر -				ļ	_
	38	N.C.	light grey 10 YR 6/1, Dry	1		ļ	•	Ŀ	
	二	3011	•					F	
11:10 4	10 I	16121		1.		ر ا	.7 ft/mo	F	-
	0.2.1				ROJECT			Tuoi = ::	-
NG FORM T	ბ ქ 6 г	PREVIOUS	EDITIONS ARE OBSOLETE.		TEAR D	الآمرين	RFI ESWAU	HOLE NO.	
		•			I CHD I	442C T	こう してら	D-12	

		1 6	DIVISION	Timesai	ATION		Hole No.			
DRIL	LING L	.OG	Sacto	INSTAL	_			SHEET 2		
1. PROJECT	 		······································	TEAD OF LO SHEETS 10. SIZE AND TYPE OF BIT 18 11 OD OPEN FACE						
!	Phas	· II A	2F1 @ SWHU 58	11. DATUM FOR ELEVATION SHOWN (TBM or MSL)						
2. LOCATIO	N (Coord	and the second		MSL , `						
3. DRILLING	Applic			12. MANUFACTURER'S DESIGNATION OF DRILL						
Lay,		•	nstruction		N Sys-			e Hanner		
4. HOLE NO.	(As sho		ring title	13. TOT	AL NO. OF DEN SAMP	OVER- LES TAKI	EN 11	UNDISTURBED		
and file nu	emb ex)		D-12		44 1111100		<u> </u>	. 8		
5. NAME OF	_ *	R			AL NUMBE			S		
TOM &	Cern			15. ELE	VATION G		ATER 339.61 (TO			
				16. DAT	E HOLE		1/2/04 9	128/04		
(25) VERTI	CAL L	JINCLINE	DEG. FROM VERT.	17 51 5	VATION TO					
7. THICKNES	SS OF OV	/ERBURDE	EN 3461	17. ELEVATION TOP OF MORE CASING 4803.053 FT						
8. DEPTH DE	RILLED	INTO ROC	к 24'		AL CORE		Y FOR BORING -			
9. TOTAL DE	EPTH OF	HOLE	3 5 0 t	24		us	(650949))		
			CLASSIFICATION OF MATERIA	15	% CORE	BOX OR	REMAR	KS		
ELEVATION	DEPTH	LEGEN	(Description)		RECOV- ERY	SAMPLE NO.	(Drilling time, wate weathering, etc.,	r loss, depth of if significant)		
a	Ь	C C	<u> </u>			1	9			
11:13	-	4.0	Proply Graped Graye	.1	$>\!\!<$	9				
	-	11.20	Poorly Graveo Grave Wisith and savo (GF	2-GM)		Ţ				
	42-	00	10-459	<i>y</i>			İ			
	" =	JO: 14	60-65% Grave 1,20-25%	Samp						
	-	16707	10-15% Silt, SAto S.R.	clasts to	Bem	1	†			
	44_	0.0	I soup is very fine grav	Neo		1				
į	_	100:10	Sour is very five grave grave greyish brown 104R	5/2			}			
	-	THE BEAT	i allalifi irrare+	./		10				
	46 —	1.01	The second secon	aboue-		ļ . Ŭ				
		1		١. ـ ٧			1			
	-		I solty Clay (CL), Mell pla	sticity.		1				
	18-	 	Solly Clay (CL), med pla No Doladeway Med Dry Motteled yellowich brow.	strewall	1	}				
İ	_	 	Motteles yellowich brow.	0 104R	5/4					
11:18	-	 	and palebrown 104R e	5/5		ļ	2.0 ft/nw			
11:20	50	-	Moist	7;						
11.20	-		as a	bove -		11				
	-] -' -	-7				,			
	52	 		,						
	_] 								
		 	1							
	<i>54 —</i>	 	1							
	_		Poorly Grasses Saus (SP)	Fine						
ļ	_		- to men quain, pale brown 10	YR 6/3	N.	12				
	<i>56</i> —	1000	Morst	3		,,				
	-									
		1000								
	58 <u>—</u>	TOP IN								
	_	190.98					_			
11:27		1750					1.4 ft/min			
/1:29	60	1000	Poorly Grapes Gravel with	١, ١		12	-			
11.61	_	10,00	Silt and Sand (GP-GM)	10 %		13				
		INO C	Grave 1, 40% samp, 10% si	14						
}.	62 <u>—</u>	1000						}		
	_	1210g	Gravel S.A to SR to 7 cm							
		16.50	five to mes sans, Brown	16 x K 3/3						
	64	10	Moist				,			
		1				ا ا	· .			
	<i>"</i> =			١,,	><	14				
	16		- silty Clay (CL) as sample	1)		'		}		
		10	above but with trace f	140				ļ		
11:34	,	1-1	gravel			ĺ				
11:35	18 —									
	_	1					۸۱ .			
11:37	y a -	17.16	- Silly Some wigravel (SM	5 1			1.4 ft/min			
11:40	#0 - <u> </u>		~20% gravel, S. Ato SR, So	ا مسد		سد و	,			
	_	ام ازارا	is 20% self with slight			15				
l.	1. =	11, 12 11	plasticity, pale brown 104	D XIT						
	72 —	01.10	. <u> </u>	1 610		.,				
	<u>, </u>	1-19 1-11	Moist]			ļ		
],	10	1.101]					
1	7 7	6.10		Į	. 1	1				
	_	K); 66		ļ		,				
].	,, <u> </u>	1:10:1:			><	16				
[3	7 <i>/</i> —	1:1:1		†		}				
		1-10:15		1	i					
].	7¢ -	1. 7.27]		į		 				
1	78	では	Ellica In Icm	ŀ	İ	•	EL/			
			5, thy Grave w/ saus (GM) 7090 gravel, 2000 saus, 2000	sitte		Į.	1.4 ft/min			
11:47	SU =	170%	Grave SA to SR to 16 cm, Samo	Gar	Greato lib	lut Greu !	104R6/1, Dry			
	1021				PROJECT			HOLE NO.		
NG FORM	1836	PREVIOU	IS EDITIONS ARE OBSOLETE.			Phase	II RFI	ł		
			COOD ASSOC STORESTING		, (ñ	D-12		

DRI	LLD	IG L	og	DIVISION Sact				LLATION TEAD				SHEET 3			
1. PROJEC	T T		- L		"		10. SI	TEAD ZE AND TY				OF (SHE	ETS		
LOCAT					SWMU	58	11. 07	11. DATUM FOR ELEVATION SHOWN (TBM or MSL)							
	·				·····		12. MA	12. MANUFACTURER'S DESIGNATION OF DRILL							
. DRILLI	NG AC	ENCY	•				10. 70								
HOLE N	numb	a ahov	m on dra	wing title	D	17	13. TOTAL NO. OF OVER- DISTURBED UNDISTURBED BURDEN SAMPLES TAKEN								
S. NAME C	F DR	ILLER				1	ļ	14. TOTAL NUMBER CORE BOXES							
. DIRECT	ION C	E HO	F			···	15. EL	EVATION							
				ED	DE	EG. FROM VER	16. DA	TE HOLE	31	9/2/04	(9/28/04			
, THICKN	ESS C	FOVE	ERBURO	EN			17. EL	EVATION 1	TOP OF H	OLE					
. DEPTH					· · · · · · · · · · · · · · · · · · ·		<u> </u>	TAL CORE		RY FOR BORIN	G		•		
, TOTAL	DEPT	н оғ	HOLE					n/H	/au	650	949)				
ELEVATIO	ם אפ	EPTH	LEGEN	о с	LASSIFICAT	ION OF MATE	RIALS	% CORE	SAMPLE		REMAR	KS loss, depth o			
a		Ь	С	_		d		ERY •	NO.	weatherir	ve, etc., i	t eigniticent)	•		
11:52			0.110					$\geq \leq$	17						
	8	, –	015	-											
			0:0	Poor	ly Gras	es Grave	el w/son	Δ.	1						
			6 C)	(GP)	Cobbles -	es 60000 to 2000	(samo			- Priles 1	votes	boulous			
	84	' —	80	fine	to men	~ (~ 2090) ~ observ	41			1 6012121	ć >				
				, Calu	de ski	n observi	es on								
	86		000	i langt	y lunest	fore class	15, 3A	\geq	. 18						
	100	`	0.	; to si	2, Greyia	, a Isvour	10 48 8/2								
			3												
	&&			- Lear	· Cla. (-1) hink	ola elitatu	1							
		\exists		100 T	وراما حدكم	L) high high 10 YIZ 6/	streasth	.							
2:05	90			Pale	- promy	10 412 61	3, mo (5)			0.8 ft/	HIN				
2:35	/		0 (V		er Sand			19		-				
		\exists	ري (<i>د</i>)	(50)	407. G	rowel to	wgrouel		T						
	92	\dashv	1. 511	6090	Web.	Saus, go	ALL CHA		}						
		=======================================				medare									
	94		80	1 80a	skstr	light yellow									
	77	=======================================	0) 00 x	12 6/4, W	locst		L							
								\supset	20						
	96	===	O -	•	,							•			
		4		Claye	y 5, 14 (~	IL), mes pl	acticity,								
	98	—	74 H.	light	yellow bu	وهاس 10 YR	6/9								
		\exists	一儿							,					
1:43	100	7	(a.Q.	Poorly	ı Grapet	o gravel w	uth			1.3 ft/	u i as				
13/04	100		000	SAND ((GP) Trace	e cobble,	2 0%	>	21						
8:15	[\exists	000	Soure.	80% grave	e(to 5 cm	•		,						
	102		200.	bre	y is h bro	WW 10 YR	6/2								
	ŀ	\exists	7.00.												
	104														
	707	_6	3000												
		□ [\$	0.0	·as uf	ove			$\overline{}$	22						
	106.								~~						
	108-		0.0.					}							
	,-,	⊐ં&	0.00												
: 25		II.	à.0							1.0 ft	~ 1A2				
35	110	- ⊣ģ	20.0	-as ab	ove				23						
ĺ		∄	000						~3						
İ	112-	Д. С	100].	-Bouloer at	114				
36	, -	73	ونب								•		ļ		
22	1/4-	7	X				ļ			- bloddind					
	117-	4			_	/ . · >	,	-							
.02		7	بحر.			(CC) 30%			24	Sustane E	العوا	N 5 - NEED			
145	116 -					ranel to 5			¬'	appitions	بر کار	APVESSOF	ļ		
		=	, O.			souro, s.a plastic c						1 .	ļ		
j	118-	- 5		Mat	LIX (60%	a), right re	opish						ļ		
	r (U =		$\frac{\mathcal{S}}{\mathcal{S}}$	brow	on SYR	6/3, mois	'			<u>.</u>			ļ		
		\pm	<u></u>]			0.7 ft/	min				
150	20												1		

							Hole	No. U-12	
DRIL	LING L		Sacto	INSTAL	EAD			SHEET 4	
1. PROJECT					AND TYP	E OF BIT		OF (SHEET	긤
2 1 00 1 7 10	Lare	II P	F1 @ SWMU 58				N SHOWN (TBM or	MSL)	7
2. LOCATIO	N (Coordin	nates or St.	ation)	12 MAN	HEACTHE	EB'S DESI	GNATION OF DR		_
3. DRILLING	AGENCY	···		12	OFACION	ER 3 DESI	GRATION OF DR	166	
4. HOLE NO.	. (As shou	m on draw	ing title	13. TOT	AL NO. OF	OVER-	DISTURBED	UNDISTURBED	
and file m	umb et)		D-12	ļ			<u>.</u>		
5. NAME OF	DRILLER	!				ROUND WA		· · · · · · · · · · · · · · · · · · ·	\dashv
6. DIRECTIO	N OF HO	LE		 		! ST A	RTED	COMPLETED	\dashv
VERT	ICAL _	INCLINED	DEG. FROM VERT.	16. DAT	E HOLE	9	12/04	928/04	_
7. THICKNE	SS OF OVE	ERBURDE	N	17. ELE	VATION T	OP OF HO	LE		
8. DEPTH DI	RILLED II	NTO ROCK	ξ ,		·	RECOVER	Y FOR BORING	· · · · · · · · · · · · · · · · · · ·	*
9. TOTAL D	EPTH OF	HOLE		U	Z	Jus		50949)	
ELEVATION	DEPTH	LEGEND	CLASSIFICATION OF MATERIA	LS	% CORE RECOV-	BOX OR	(Dalling time	EMARKS water lose, depth of	
	Ь	c	(Description)		ERY	SAMPLE NO.	weathering,	etc., if significant)	
13:20	120 _	. 0	- as above Clayey Gra	1 el(GC)		25	You prol	ling with	\top
İ	=	D		,		~	auxillary	compressor	F
	122-	0					(Sular	Compressor 900 KH)	F
		7 000							F
	124	900							F
		0000							F
		0.00	Poorly Graped gravel W/sau			26			F
ļ	126		(GP) 60% gravel, 40% san			75			<u> </u>
}		9200	gravel fine to 7 cm, sours.						E
	128	9,000	to men, sa. to s.R. gravel	۱					E
:			light yellow brown, 104 Slightly usosil	R 614		f f			E
13:28	=	9,9	sugar of acord				1.3 ft/m	·) (.	E
13:34	130					27	7.3 .32		
	=	000	-as above but gravel Size increases	ł		~7			
	/3z —	50.83	, and the second second						
		0.00							E
	,,, =	00.0							
	134	30			;				
	=	20 O	- as above but						
	136	00:0	20% sand, light brown 7	YR 614		28			上
		000	20 10 11	I					=
	139	0.00							F
ľ	' '' =	0:00	W de						F
13:42	_ =	0.80					1.3 ft/m	Δ,	E
13:42	140-	0.00	-as sample 26	†	$\overline{}$	29			E
}	コ	00.0	,	ŀ					E
	142 -	2 0 c		ł		j			L
		0,00				1			E
		1.0.8							
	144	000		1,		ł			
	7	1,8,1	as above but	1		70			
/	46	201)	30% cobble to 14 cm	-		30			
]	[jøjøj]	4090 gravel, 3090 sant						F
	148	0,0	• • • • • • • • • • • • • • • • • • • •						F
ľ	'° →	() S		İ			•		F
14:01	_ ;	200					0.9 64/	เมื	E
14:05	150	O.O.	- as above	٣		31		•••	
	= 1₁	700		 			l'.		E
,	52	0,0	•			İ	!		L
[*	~ =;	0.00		ł		}	•		F
] ,	(100)		ļ					E
'	154	600							=
	7	认从	as above	*		32			F
/	56-	30,00	, 			34			上
1	$\exists :$	Qoa					•		F
	58-3	SO.			Ì				
		0.0					· ~ Et/		F
14:15	160	Y.C.				-	1,0 P/M	ľικ	E
	1001	PEVIOUS	EDITIONS ARE OBSOLETE.	F	ROJECT		77 5	HOLE NO.	
MAR 71			TRANSILUCENT)	ı	TEAD	Phas Cuimu	e II rei	D-12	

· · · · · · · · · · · · · · · · · · ·	DIVISION	lines of	1 4 2 1 2		Hole N	40. D-12
DRILLING LOG	Sasto		EAD			SHEET 5
Phase II RF	I @ SWMU 58	10. SIZ	E AND TYP	2E OF BIT		
LOCATION (Coordinates	or Station)	11. DAT	TUM FOR E	LEVATION	N SHOWN (TBM or)	WSL)
DRILLING AGENCY		12. MAN	JUFACTUR	ER'S DESI	GNATION OF DRIL	
		13 703	TAL NO. OF	- OV==	DISTURBED	! , , , , , , , ,
HOLE NO. (As shown on d and file number)	trawing title	BUF	RDEN SAMP	LES TAKE		UNDISTURB
NAME OF DRILLER		***************************************	AL NUMBE			
DIRECTION OF HOLE		15. ELE	VATION GI			
VERTICAL MINCLI	NED DEG. FROM VEI	16. DAT	E HOLE	,	2/04	9/28/04
THICKNESS OF OVERBUR	DEN	17. ELE	VATION TO			11.0101
DEPTH DRILLED INTO RO	ЭСК				Y FOR BORING	
TOTAL DEPTH OF HOLE		19. SIGN	ATURE OF	USPECT	OR .	
EVATION DEPTH LEGE	ND CLASSIFICATION OF MATE (Description)	RIALS	% CORE	BOX OR SAMPLE	REN	MARKS
a b c	d		RECOV- ERY	NO.	(Drilling time, w weathering, et	rater loss, depth o
4:20 160 -098	Poorly Graded Gravel	w/sand		33		9
	(GP) 1090 cobble to			,,,,,		
162 -000	50,90 gravel, 4090 sa					
	gravel five to coarse	, saus				
164 - 0.00	five to oneo, SA to SE		, 1	1		
	of light yellow brown 10			ļ		
166 - 000	-as above		$\rightarrow \subset$	34		
		ľ				
70:04		1		•		
168		1		-		
	d					
26 170 - 000	- as above	-		7-	1,7 ft/win	
	,	-		35		
172 - (30)	,].				
7,0,0						
	Poorly Grapeo Gravel as	s above	-	}		
174 - 10, 5, 5	I but with clauserosa	10(GP)				
0:0:	Soup, five to coarse que	1 days [34		
176	five to coarse soup, SA	405R		5-		
	Piokish Grey 54R	7/4				
افاراه - ۱۶۶			-			
8 180 700	Bank Guaran annial.	u.			1.1 A/min	
180 - O.I.D.	Poorly Graders gravel (S. 14 AND Sand (GP)	GMD F		3 7	——————————————————————————————————————	
11.0.6	(1040 S. H, 2090 Samb)					
152 - 0100	. ,			<i>Y</i>		
7000						
184						
انت قد	- as sample 33			1		
186 -0000			<u>><</u> ?	38		
1,00%						
700.00			. .			
188 3000						
0 300					. 3 ft/min	
6 190 - 0.0.0	-as above				, U 47/4/1N	
			\leq 3	39		
0 192 - 0			ļ.		sown to tight	en bolte on
				h	neap + fuel li	No
194-00						
80.0	ee e L		40	0		
196 - 0:0:0:	as above		~ "	-		
Trai						
198 - 0:2:0						
3000					7 ft/niv	
200 - 8:152			1	10.	H TT/MIN	

		Τ	DIVISION	1			Hole No.	
	LLING	LOG	Sacto		EAD			SHEET C
PROJEC		DET	@ SWHU 58	10. SIZ	E AND TYP			
		inates or		11. DA	TUM FOR E	LEVAT	TON SHOWN (TBM or MSL)	
DRULIA	G ACEN			12. MAI	NUFACTUR	ER'S D	ESIGNATION OF DRILL	
	IG AGEN				FA: 110 -	F A	Pressure = =	
HOLE N	O. (As shoumber)	own on dra		13. TOT	TAL NO. OI	PLES TA	AKEN DISTURBED	UNDISTURBED
NAME O	F DRILLE	R	D-12	14. TOT	TAL NUMBI	ER COR	E BOXES	
Diesa	ON OF H	01 5		15. ELE	VATION G			
			ED DEG. FROM VER	16. DAT	TE HOLE			MPLETED / 28/04
				·	VATION T			72.109
 		INTO ROC					ERY FOR BORING	*
TOTAL				19, SIGN	ATURE OF	· /	12021	46
LEVATIO			CLASSIFICATION OF MATER	IALS	% CORE		R REMAR	
a a	b b	H LEGEN	(Description)	25	% CORE RECOV- ERY	NO.	E (Drilling time, water	loss, depth of
5: 33	<u> </u>	1000	3. D / C C /	(65)		///	g	
		146	Poorly Grapes Gravel			41		
	202 -		0 70% cobbles 20%					
			1090 saud, cobble to	Sour				
5:40	204	1000	Men to course, SA +	-, sums				
:57	-		Clasts, light yellow				- Down-fuel lin above farrel-	e gracted
	-		10 YR 6/4		\supset	42	above farrel-	crew repairing
	206 -		A .			1	,	
	=		-cemented matrix	1				
	208-		- CEMENTED MATTIX					
	=	٥١٥	•					ļ
1:12							0.45 H/MW	
17/04	210	02	-as above (sample 41)		$\overline{}$	43		
7:45			Saus increases to					
•	212 -	000	yellow brown 10YR	5/4			- Slowert Pen	v-ostarts
	_	الماقيل المالية					to rate	
	214							
	217	000		ĺ				
			- as sample 41		$\overline{}$	44		!
	2i6 —	900		ľ		` '		
		0.000		1				
	บ <i>ย</i> —	Onese		ľ				[
	-	2007						<u> </u>
30	220-	SO SO	- cobble becreases to	ے ا			0.22 H/min.	
33	-	0:00	20% Gravel 70% sa	up 10%	>	45	0.22 TYMIN.	ļ.
		Ragi		ľ				ļ
ļ	222-	100						ļ
	=	30.00						F
	724-			-				
	=							E
	26	10:01	- sand increases to		><	46		E
Ī	~~ =	2011	30% Graved 50% Cobble	e 207c		•		-
		0000	•		-			<u> </u>
	D8	20:00						<u> </u>
, .	4	けば						F
13	30	201	Silty Grand (CM)	_			ft/mil	-
15		0.0	Silty Gravel (GM)		><	4#	HI	-
_	<u> </u>		~30% cobble to 20 cm					, ,
51	32	اجراف	30% course gravel	İ			@8:51 8219 Da	was told
0	\exists		20% silt		1		live break	<u> </u>
_	34-	100	Gravel S.A +o S.R qua	tzile			9:50 Repair	Complete E
	$\exists :$	101	and limeston (hair)					E
5	36 — P	100	clasts to 12 cm. Pal		\sim	48		<u></u>
	三	76.9	brown OKR 6/3 mo					
	<u>, </u>		Limestone and times	, l.				E
198	38 —	2 0	efforcess strongly. a	ب المعالمة				_
4	1/	ו ייניה כ	weakly					F
	72	8 01	1	4 1975	S ., 1	1	0 20 111	
	40	الْحَادِ الْحَادِ الْحَادِ الْحَادِ الْحَادِ الْحَادِ الْحَادِ الْحَادِ الْحَادِ الْحَادِ الْحَادِ الْحَادِ ال	(0.28 ft/min	E

		Nation .				Hole No.	D-12
DRILLING L	og °	Sacto		EAD			SHEET 7
Phose II RE	•	SWMU 58	10. SIZ	E AND TYP		N SHOWN (TBM or MSL.	
2. LOCATION (Coordin	ates or St			IUM FOR E	LEVATIO	N SHOWN (TBM of MSL)	5
3. DRILLING AGENCY	,		12. MAI	NUFACTUR	ER'S DESI	GNATION OF DRILL	
4. HOLE NO. (As show	m on draw	ing title	13. TO	TAL NO. OF	OVER-	DISTURBED	UNDISTURBI
and (ile number) 5. NAME OF DRILLER		D-17		DEN SAMP			
		· · · · · · · · · · · · · · · · · · ·		VATION G			······
6. DIRECTION OF HOL			16. DAT	E HOLE	1	<i>7 1</i>	MPLETED
		DEG. FROM		VATION TO	1 9		128/04
7. THICKNESS OF OVE 8. DEPTH DRILLED IN				····		Y FOR BORING	· · · · · · · · · · · · · · · · · · ·
9. TOTAL DEPTH OF I		4	19, SIGN	ATURE OF	INSPECT	2	
ELEVATION DEPTH	LEGEND	CLASSIFICATION OF M. (Description)	ATERIALS	% CORE	BOX OR	REMAR	KS
аЬ	6 6 1	d		ERY	NO.	(Drilling time, water weathering, etc., ;	r loss, depth of It significant)
10:26			(1. A)		49		······································
292	000	Silty Gravel WIS	and (CM)				
	0.000	~ 20% cobble t	0 15cm				
244	1.00	50% graves 20% s, 1+					
247 =].	00	10% + five san	. D				
	1(())	Gravel S, A to			50		
246—	(O,0)	to locu. Pale	Brown				
	30.18	104R 6/3; ma	ist			A	
248	1:0	,			-	0.5 ft/min Ria Down - 0	
	5 00					Pie Down - 0	staf robs
10:45	7000				E	also rapid	on chacke
9/8/04 70	000		-		51	- repairs com	
252	000					▼	1
- -	000						
254	400						
	000	Poorly Grapes 6	Secure			***	
256	500	(GP) 10% cobble	+015cm +	\leq	52		
	50%	80% five to	coanse	.]		*	
258	(50,0) (60,0)	gravel 10% met Sand. Gravel S.A	grain				
		Quartzide and Limi				_	
260	554	Dank yellow Brow	10184/4 -			0.5 ft/min	
:54 3	र्ट्ड	Moist	-	$\geq \leq$	53	Crew replace	
262		Growelly Clay (CL)	~ 109n			over haune	· Dischange
	0	five gravel aus	some				,
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	-0-	continue classis is	0,00				
264	8	Stiff, Dank repo brown 2.54R	ish				
2/	05	Moist to Very ordin	ct. percher		54		
266	000	_	_				
		Silty Gravel, &GA					
268	000	20% cobble to 15	cay				
	00	60% gravel' 15% silt 5% sa	us		_	4 ft/min	
22 270 -00		Cobble & Gravel SA	to SR		75	i i i i / Pecco	
	21.9	tale Brown 104R6	13, Dry				
272	100	cueasur sans					
	Sig						
274		ilty clay (c1), st	00				
	<u> </u>	with "1090 aimile	or F		ا رسا		
276 0		with 1000 gravel cobble, men elast	ادرتكم إ	\leq	56		
)2	X	Park reposed by	ww		_ 6	skutrown - hea	m tan 1f
88 278	0 1		chap 1120				
00	C C	emented Gravel	hand		ı	shud poww-pish hose breaks	an heap
7-9	18.75		1			027 ft/min	
280			ĺ	ļ		ロスキーグ	

			\(\C\C\C\C\C\C\C\C\C\C\C\C\C\C\C\C\C\C\								No.		2
- 4.44.4	LLING LO	G DI	vision Sac	to		INSTALL TEX			77			SHEET	•
PROJEC	•	. 6				10. SIZE AND TYPE OF BIT							
LOCATIO	I RFI ON (Coordina		11. DATUM FOR ELEVATION SHOWN (TBM & MSL)										
. DRILLIN	G AGENCY					12. MANUFACTURER'S DESIGNATION OF DRILL							
		******				13. TOTA	- AU.	OF OVE	D 100	TURBED		1151515	
i. HOLE NO and file r	O. (As shown number)	on drawir	ng title	D-12		BURD	EN SAN	MPLES T	AKEN	- OKBED		UNDISTU	RBED
. NAME OF	DRILLER		<u>Ĺ</u>	<u> </u>	-				RE BOXES				
. DIRECTI	ON OF HOLI	E	····			15. ELEV	ATION						
VERT	ICAL TI	CLINED		DEG. F	ROM VERT.	16. DATE	HOLE		9/02/0	34		/28/0	
. THICKNE	SS OF OVER	RBURDEN			[17. ELEV	ATION					7-070	<i></i>
DEPTH D	RILLED INT	O ROCK							ERY FOR	BORING			*
. TOTAL D	EPTH OF H	OLE				19. SIGNA	THE O	of INSP	ECTOR				
ELEVATION	DEPTH	-EGEND	CLA	SSIFICATION C	F MATERIAL	.s	% CORI	E BOX		R	EMARI	<s< td=""><td></td></s<>	
a	ь	c		d d			ERY	NO f		eathering,	etc., i	loss, depi eignifica	nt)
1/9/04			- cener 40 %	uted Grave cement, 1	ichtoreu 10	40-010 YR 7/1	><	59			4		
11:35 12:10	202			IT Setting					ער דין	والبهج ص ^ا ج ال	* p~	eaks a	*
12:35	282-		less 4		= +=++,/ 🐷)	'			1 ~ 00	~ s ·			
12:44		20%	ENDO	f ceneu	283.7	'							
	284 - 0	8O.			-								İ
).F) 65 -	- Poorle	Grabes	Graves 11	A (9.							
	286	0.01	COPP	les to 12 o coarses twe sou	cm (30°	25 /	\simeq	58					
		0%	Fine +	o coanse	zravel (60	25							
		1.000	3. Thy	y we som	D (1096)	,							
İ		190	راه چې	s are lar	elu Siehon	neimail							
3:20		800	DADM	N 10 YR	5/3, Moi	s+			0.09	ft/mi	یں		Ì
3:44	29.0	-01 -	- Gran	elly Clay (1(1) 220	9.		5.9	- hes	us hot			ļ
			C00P)	e à gravé	1 to 9 cm			3.7					ŀ
	292-7	10	ک د ریمرا	Lau, wi	eb elacti.	, N/a							
	$\exists \exists$	=0=	14500	12 KOLOM.	0 2.54R	5/4							
ļ	294-	101	Mois	1									þ
	""	010	5, {4.	Gravel (G	M INSM								þ
	<u> </u>		Calli	- 20	1. 2			6					F
ŀ	²⁹⁶ ∃5	00:	30%	sill light	grey 10 YR	7/2 K		+ .					F
	∂E	000											E
ä	48 - O	10V:1-	above	Grapes G.	58 L. 4		-			4			þ
	J'o		30% 5	and 40% 5	vave 3020	obble			0.47	ft/mw)		F
	00 - 3	00:		U		K		ļ	- Creu	s chee	k ha	es auc	> E
:23	32):					<	61		5 0 N			E
,	02-30	0.0				1		``,					
5	~ = 13%	01											F
	コマ <u>デ</u>	7											-
3	04 - 6	0.0											E
		7: - a	is abo	00°									E
3	× - 10	0.0						62					E
		71											F
30	07	Ø.											F
		(2)							0 41-	- 111			E
20	<u>ر _ع</u> ک	10	• u 4.	. 1	, / >				J . 7 ?	5 C4/m	ω		E
31		ord-F	4 alan	l with grav	nel (CH)		\supset	63					E
			215 70	coarre g e (ullem)	ravel to	ار ا		ړ به					
31	12		2. 5 V)	2 5/4 Mais	Much Dlack-	ا ۱۸۰۸			į				F
	-		nity cla	ey (CL) no stic PINK	grave ((a) d							F
31	4	→ c.	emente	io clay as a	2 12 014, A	m, 2,	}	· .					F
	0,1			FAST .		a							E
١,,	<u>, ∃∞</u>			lylichau (coonse qu				64					E
31	حوات "	7 ~	ugu lan	to subve	vubeo,								E
	195	-C4 Re	epish k	mottel	mith pin	te		1					E
31	8 0 5	te	parit -	bossible	- Fault			į					上
	700	14 g	ومرو	où turbi 1 Deposit, E	outy me			j	0.24	11			F
76	, 		الأفكرة	1.00001		- 1	1		U. ~~~~	1 1/447	A.Z		.

Hole No. D-12 INSTALLATION DRILLING LOG TE40 1. PROJECT 10. SIZE AND TYPE OF BIT 9" OF OPEN F.
11. DATUM FOR ELEVATION SHOWN (TBM or MSL) Open Face Phase II RFI & SWMU 58 12. MANUFACTURER'S DESIGNATION OF DRILL 3. DRILLING AGENCY Becker Hammer AP100C 4. HOLE NO. (As shown on drawing title D. 17 TOTAL NO. OF OVER-BURDEN SAMPLES TAKEN 14. TOTAL NUMBER CORE BOXES 🗝 S. NAME OF DRILLER 15. ELEVATION GROUND WATER 337.11 bas an 10/4/04 Tow Kern 6. DIRECTION OF HOLE STARTED 16. DATE HOLE 9/2/04 *94€*04 VERTICAL | INCLINED 17. ELEVATION TOP OF HOLE 344.346 feet . THICKNESS OF OVERBURDEN 18. TOTAL CORE RECOVERY FOR BORING . DEPTH DRILLED INTO ROCK 10-221 feet 9. TOTAL DEPTH OF HOLE % CORE BOX OR SAMPLE CLASSIFICATION OF MATERIALS (Description) REMARKS ELEVATION DEPTH LEGEND (Drilling time, water loss, depth of weathering, etc., if significant) 15:43 65 Fat - head is shooting flowe 16:01 46:21 as above Gravelly Clay (G) from fivel Aujectar - short 16:30 but gravel waveasing to 9/10/04 50% Clasts up to 15em 69:00 Clay is very high ory Strength No Diletery, and High tough was and plasticity 66 Dank Reopish Brown 2.5 YR 3/4 moist @ 388 lifting cuttings Begin Containing Cutting on 9113109 puring resulty 10:17 0,088 HIN PID 20.0 - as a bove 10:30 67 11.4 min/1+ Befor Pulling 3421 332 Groundwater in Isolated bedrock @ 336, 2 bas au 9/17/04 Cementer Gravel (GP) 12:10 68 60% cobble & gravel, mostly subvouvoer agth hard Break-coolhead :0.0 12:43 eat lunch matrix cement, appears impermeable, coment W. L= 337. () 338 00 10/4/04 is lightgrey 54R 7/1 13:04 0.080 Huin 69 13:15 14:15 392 14230 .cool hears - Quartzite builders or weathered berrock 15:10 9/13/04 70 23 mules Switch to ODEX 9:10/14:50 Sampstone berock 12:40/15:10 (SS), augular clasts to 3 cm, new soft, weathered 9/16/04 @10:25 348 faces with iron oxide and manquese on Sorfaces occusionally, 4(light yellow brown 104R6/4 -0.0 -a somo zone observen at 352' moist to wet from 346-349, Day to 356 72 10,50 9/21/04 10:05 FORM 1836 PROJECT TEAD Phase II RF1 PREVIOUS EDITIONS ARE OBSOLETE.

D-12

@ SWMU ZZ

(TRANSLUCENT)

DELLING LOG DIVIDION THE PARTY TO SUMMULTS LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL OF SIGNAL LOCATION CENTRAL DEPTH LOCATION OF HOLE LOCATION OF HOLE LOCATION CENTRAL OF SIGNAL LOCATION			<u></u>					Hole N	
L DOCKTOR CONSERVATOR STATEMENT AND AND AND AND AND AND AND AND AND AND	DRIL	LING L	OG C	_ 1	INSTAL		AD		
DOLLING AGENCY 1. MANUFACTUREN'S DESIGNATION OF DRILL 1. MANUFACTUREN'S DESIGNATION	DI		TT 10	_:		AND TYP	E OF BIT	EUOWN /Thr	
S. DRILLIAN AZERVY THE THE CALL AND THE PROBLEM STATES THE THE CALL AND THE PROBLEM STATES S. AME OF GRALLER S. AME OF GRALLER S. AME OF GRALLER S. AME OF GRALLER S. DRIEFTON OF MOLE THE CALL MUSER CORE BOOKES THE CAL			nates or Si	lation)	-[UM FOR E	LEVATION	SHOWN (1DM OF M	ist)
A SOLE BY CARREST SAMPLE STARCE WAS ARROWN AND THE STARCE SAMPLE STARCE WAS ARROWN AND THE STARCE SAMPLE STARCE WAS ARROWN AND THE SAMPLE STARCE SAMPLE STARCE SAMPLE STARCE SAMPLE STARCE SAMPLE SAMP	3. DRILLING	AGENCY	7		12. MAN	UFACTUR	ER'S DESI	GNATION OF DRIL	L
R. HAME OF GRILLER B. DIRECTION OF DOLE B. DIRECTION OF DOLE B. DIRECTION OF DOLE B. DIRECTION OF DOLE B. DIRECTION OF DOLE B. DIRECTION OF DOLE B. DIRECTION OF DOLE B. DIRECTION OF HOLE T. THICKNESS OF OVERBURDER B. DESTA DOLLED INTO ROCK B. DIRECTION OF HOLE B. DOTAL DEFTIN DECEMB CLASSIFICATION OF NATERIALS B. DESTA DOLLED INTO ROCK B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS B. DIRECTION OF HOLE CLASSIFICATION OF NATERIALS CLASSIFICATION OF HOLE CLASSIFICATION OF HOLE B. DIRECTION OF HOLE CLASSIFICATION OF HOLE B. DIRECTION OF HOLE CLASSIFICATION OF HOLE B. DIRECTION OF HOLE CLASSIFICATION OF HOLE B. DIRECTION OF HOLE CLASSIFICATION OF HOLE B. DIRECTION OF HOLE CLASSIFICATION OF HOLE B. DIRECTION OF HOLE CLASSIFICATION OF HOLE B. DIRECTION OF HOLE CLASSIFICATION OF HOLE B. DIRECTION OF HOLE CLASSIFICATION OF HOLE B. DIRECTION OF HOLE CLASSIFICATION OF HOLE B. DIRECTION OF HOLE CLASSIFICATION OF HOLE CLASSIFICATION OF HOLE CLASSIFICATION OF HOLE CLASSIFI	4. HOLE NO	. (As show	m on draw	ring title	13. TOT	AL NO. OF DEN SAMP	OVER-	DISTURBED	UNDISTURBED
EDIRECTION OF MOLE VERTICAL MICHIEVE OBS. PRODUCTS 1. HOLD VERTICAL MICHIEVE OF MICHIEVE OBS. PRODUCTS 1. THICKNESS OF VERBURGET 1. THICKNESS OF VERBURGE			₹	D-12	14. TOT	AL NUMBE	R CORE	OXES	
DESTRUMENTS OF PROPERTY OF STATE OF STA	6 DIRECTIO	N OF HO	1 F		15. ELE	VATION GI			COMPLETED
DEPTH DILLEGEND CLASSIFICATION OF MATERIALS SELEVATION DEPTH LEGEND CLASSIFICATION OF MATERIALS SAME STONE DESCRIPTION OF MATERIALS SAME STONE DESCRIPTION OF MATERIALS SAME STONE DESCRIPTION OF MATERIALS SAME STONE DESCRIPTION OF MATERIALS SAME STONE DESCRIPTION OF MATERIALS SAME STONE DESCRIPTION OF MATERIALS AUGUST STONE CALLS STONE OF MATERIALS AUGUST STONE CALLS STONE OF MATERIALS MATERIAL	1			DEG. FROM VERT.	16. DAT	E HOLE			
NO FORM 1836 A REMOVE SINDON ARE DATE OF THE PROJECT HOLE NO.	7. THICKNE	SS OF OV	ERBURDE	:N					
ELEVATION DEPTH LEGEND CLASSIFICATION OF MATERIALS SALESTON OPENTALS SALESTON OF THE CONTROL OF MATERIALS SALESTON OF THE CONTROL OF MATERIALS SALESTON OF THE CONTROL OF MATERIALS SALESTON OF THE CONTROL OF MATERIALS SALESTON OF THE CONTROL OF MATERIALS SALESTON OF THE CONTROL OF MATERIALS SALESTON OF THE CONTROL OF MATERIALS SALESTON OF THE CONTROL OF MATERIALS SALESTON OF THE CONTROL OF MATERIALS SALESTON OF THE CONTROL OF MATERIALS SALESTON OF THE CONTROL OF THE CONT		 		K			INSPECT	OR	~
Semportance betweek (SS) 302 Semportance betweek (SS) Clasts to 4 can, new softty Soft, many weatheress 344 355 366 Soft words considered to the soft of the semportance of the		T	T	CLASSIFICATION OF MATERIA	ALS	% CORE	BOX OR	REN	MARKS
angular to subangular Clasts to tam, new soft to Soft, many wethers to faces, iron orite author Mangular to subangular Southers, lightly yellow brown 1048 /4 pro a highly treatured Tope of 364-367 FORM 1334 Decides and the subscription of	1		j	(Description)		ERY	NO.	weathering, et	
Clasts to 4 cm, new soft to 30 c		_ =	1	Sansatone bedrock	(55)	\times	73		· · · · · · · · · · · · · · · · · · ·
Soft, wenty weethers Socs, Ivon oxide audion Manganeze co many Sorties, lightly predict brown IVR 44 pre a highly fractives Toke of 364-367. 1115 11		362];'•'	1, 3,	· O .				= 0.2
Taces, wow oxide ambler Thousances, held yellow brown 10/8 /4 pre a highly fractioned Tope 21 364-367 Tope 21 364-367 To the precediment of		=	`. `	1 4		1			=
MG FORM 18 36 ADVANCE AND SEE PROJECT PROJECT INCLE NO.		2/4-		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	-				
NO FORM 18 36 A DEPURE AND SEE PROJECT INCLE NO.		20 7 =	3 6 5 5	1			,		
Brown 10 VR 44 and a highly fractured to a highly fractured to a highly fractured to a highly fractured to a second and a second and a second and a second and a seco		3/6-	5.5 6	1 ()	1		74		0.0
TODE EN 18 36 ADDRESS ENVIRON DE CONTROL TE PROJECT PROJECT NOCE DO 18 18 36 ADDRESS ENVIRON DE CONTROL DE CON		=	55.5	110000					
TO FORM 18 36 A PROJECT PROJEC		268		a highly fracture	o`				E
Hole Discoviniues Due to Fractured Trock at 364-367 canny above bit in the Unicasety hole		=		Tone 2 364-367			g		
Hole proceditioned Due to fractive Droce and set set set set set set set set set set	11:15	724				$\geq \leq$	75		
To fractive rock to a 364-367 caring above by in the two cases hole	•	=	EOH					Hole Disco.	utiques Due
NG FORM 18 36 DEPUTE TO PROJECT HOLE NO.								to fractu	red rock [
NG FORM 18 36 DEPUTE TO PROJECT HOLE NO.		_						at 364-3	67 caving
NG FORM 18.36 DESCRIPTE PROJECT HOLE NO.		_	1					above D	1.10
NG FORM 18 36. PREMIONE EDITIONS ARE ORGALETE. PROJECT HOLE NO.		_						UN CASED	No TE
NG FORM 18 36. PREMIONE EDITIONS ARE ORGALETE. PROJECT HOLE NO.									F
NG FORM 18 36. PREMIONE EDITIONS ARE ORGALETE. PROJECT HOLE NO.		_							E
NG FORM 18 36. PREMIONE EDITIONS ARE ORGALETE. PROJECT HOLE NO.									F
NG FORM 18 36. PREMIONE EDITIONS ARE ORGALETE. PROJECT HOLE NO.									E
NG FORM 18 36. PREMIONE EDITIONS ARE ORGALETE. PROJECT HOLE NO.									
NG FORM 18 36. PREMIONE EDITIONS ARE ORGALETE. PROJECT HOLE NO.	ļ	_							E
NG FORM 18 36 PREVIOUS SPECIFICANES ARE ORSOLETE. PROJECT HOLE NO.									F
NG FORM 18 36 PREVIOUS SPECIFICANES ARE ORSOLETE. PROJECT HOLE NO.		=							
NG FORM 18 36 PREVIOUS FOLTIONS ARE OBSOLETE. PROJECT HOLE NO.									F
NG FORM 18 36 PREVIOUS FOLTIONS ARE OBSOLETE. PROJECT HOLE NO.									
NG FORM 1836 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT TEAD Plan TO PET TO D 1/7									F
NG FORM 18 36 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT THAT PL TO THE NO. TO THE NO. TO THE NO. TO THE NO. TO THE NO. TO THE TO THE NO. TO THE NO. TO THE NO. TO THE NO. TO THE NO. TO THE NO. TO THE NO. TO THE NO. TO THE NO. TO THE NO. TO THE NO. TO THE THE THE NO. TO THE NO.									E
NG FORM 18 36 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT THAD PLANT TRET HOLE NO. THAD PLANT TRET TO DE 1/7		_=							F
NG FORM 18 36 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT TFAD Pl. TRET HOLE NO. TFAD Pl. TRET D-177									E
NG FORM 18 36 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT TEAD PLANT RET D-17									F
NG FORM 18 36 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT TPAD Plan TI PET D-17									E
NG FORM 18 36 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT THAD Plant TI RET TO TO 17		_=							上
NG FORM 18 36 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT TEAD Place TO PET D-17		目							E
NG FORM 18 36 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT TFAD Place TI PFT D-17									F
NG FORM 18 36 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT TEAD Plant TI RET D-17									E
NG FORM 18 36 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT TEAD Plant TI RET D-17		_ =							F
NG FORM 18 36 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT TEAD Plant TI RET D-17		\exists			1				E
NG FORM 1836 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT TFAD Plan TT RET D-17		_=					ļ		E
NG FORM 1836 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT TFAD Plan TT PFT D-17		日							E
MG FORM 1836 PREVIOUS EDITIONS ARE OBSOLETE. PROJECT TEAD Place TT RET D-17		=							
(TRANSLUCENT) (LAF (daself F12)	NG FORM	1836	PREVIOU				Plan	TI RET	HOLE NO. D-/Z

(TRANSLIICENT)



Integrated Subsurface Evaluation

311 Rock Avenue • Golden, CO 80401 PH 303.526.4432 • FAX 303.526.4426 email: PedlerRAS@aol.com • www.rasinc.org

D-12

OTHER SERVICES.

COMPANY

US AEC

WELL

: D-12

LOCATION/FIELD TEAD

COUNTY

: TOOELE

STATE

: UTAH

SECTION

TOWNSHIP

RANGE :

DATE

12/07/04

DEPTH DRILLER

PERMANENT DATUM : TOSC

= NA

LOG BOTTOM LOG TOP

361.20 3.10

LOG MEASURED FROM: TOSC DRL MEASURED FROM: NA

DF

KB

CASING DIAMETER: 0

CASING THICKNESS: D

CASING TYPE : PVC

LOGGING UNIT FIELD OFFICE

202

RECORDED BY

BOREHOLE FLUID

MATRIX DELTA T

: who

FILE : PROCESSED

BIT SIZE MAGNETIC DECL : 0

1.6

. 0 : 0

140

MATRIX DENSITY | 2.71

NEUTRON MATRIX : Dolomite

RM TEMPERATURE

1.0

TYPE : 9512A

THRESH: 4000

ALL SERVICES PROVIDED SUBJECT TO STANDARD TERMS AND CONDITIONS


KLEINFELDER ARSONS

Date:09/23/2005 Project Number 48743.1B TEAD Phase II RFI

WELL D-12 **NATURAL GAMMA AND** INDUCTION ELECTRICAL LOGS SLC5Q232.ppt

PI ATF

C-2a






TEAD Phase II RFI

WELL D-12
NATURAL GAMMA AND INDUCTION LOGS

SLC5Q034.ppt PLATE

C-2b



- Phase I RFI Well
- △ Phase I RFI Well Abandoned
- △ Phase II RFI Installed Fall-Winter 2004
- △ Phase III RFI Installed Summer 2005
- △ Proposed Phase II RFI Well
- TEAD/UID Groundwater Monitoring Wells
- Existing Well
- Phase II RFI Well Installed Fall-Winter 2004
- Phase II RFI Well Installed Summer-Fall 2005
- Proposed Phase II RFI Well

* Survey Benchmark

Approximate Phase II RFI Well Access Route

-- Cross Section Line

Former Landfill

Parcel Boundaries / Owners

SWMU 58 PHASE II RFI TOOELE ARMY DEPOT TOOELE, UTAH




PLATE C-3

GROUNDWATER
MONITORING WELL
LOCATION MAP



tegrated Subsurface Evaluation

311 Rock Avenue • Golden, CO 80401 PH 303.526.4432 • FAX 303.526.4426

email: PedlerRAS@aol.com • www.rasinc.org


D-12


MPANY	: US AEC		OTHER SERVICES		
FLL	D-12				
CATION/FIELD	TEAD				
YTNUC	: TOOELE				
ATE	: UTAH				
:CTION	•	TOWNSHIP	:	RANGE	:
ΛE	12/07/04	PERMANENT DATUM	: TOSC		
PIH DRILLER					: NA
G BOTTOM	361.20	LOG MEASURED FROM	: TOSC	OF	:
G TOP	3.10	DRL MEASURED FROM	: NA	GL	; na
SING DIAMETER	: 0	LOGGING MIST	: 202		
SING TYPE	: PVC	FIELD OFFICE			
SING THICKNESS	3: 0	RECORDED BY	: whp		
r size	∹ 6	BOREHOLE FLUID	: 0	FILE	: PROCESSED
AGNETIC DECL.	. 0	RM	: 0	TYPE	: 9512A
ATRIX DENSITY	: 2.71	RM TEMPERATURE	: 0		
EUTRON MATRIX	: Dolomite	MATRIX DELTA T	: 140		
				THRESH	H: 4000
		^			A


ADDITION OF BOREHOLE GEOLOGY (FROM GEOLOGIC BOREHOLE 166 BY MATTIVERS)


AND GEOPHYSIENL LOG INTERPRETATION BY R. JIRIK

	ALL SERVIC	ES PROVIDE	ED SUBJECT TO STAN	NDARD TERMS AND CO	ONDITIONS	
		FEET		AP-C	OND	
			60	MMH	IO/M	Ů.
GAM(NAT)				RE	S	
API-GR	100		Ū	ОН	Л- M	250
TEMP				co	ND	
DEG F	60	-		MMH	O/M	0
		Ī				










TOOL CALIBRATION D-12 12/07/04 13:50 TOOL 9512A

SERIAL NUMBER 993
DATE TIME

Jul16,04

TIME 01:01:14 SENSOR GAM(NAT) STANDARD
Default [API-GR]


RESPONSE
Default [CPS]







SLC5Q044.ppt




CONTRACTOR WELL NUMBER PLATE

Kleinfelder/Parsons D - 12 D-1

TEAD Phase II RFI - SWMU 58

MONITORING WELL INSTALLATION DATA RECORD

PROJECT: Phase II RFI - SWMU 58 LOCATION: Tooele County, Utah DRILLING SUBCONTRACTOR: Layne Geoconstruction DRILLER: Tom Kearn DRILLING METHOD AND EQUIPMENT: Becker Hammer-Drill Systems AP1000 HELPERS: Nate Salazar, Mike Winmill WATER LEVEL: 339.61ft (TOC) on 10/4/04 START: 9/2/04 GEOLOGIST: Matt Ivers, Kleinfelder END: 9/28/04



Legal Description - Monitor Well No. D-12


A fifty foot diameter well easement for the purpose of accessing monitor well No. D-12, the center point of which is described as follows:

Commencing at the West Quarter corner of Section 20, Township 3 South, Range 4 West, Salt Lake Base and Meridian; and running thence North 00°05'27" West along the west line of the Northwest Quarter of said Section 20, a distance of 12.32 feet; thence North 89°54'33" East, a distance of 627.80 feet to the center point of a PVC pipe marking Monitor Well No. D-12, and point of terminus.

Well No. D-12 - Access Easement Legal Description

A twelve (12) foot wide access easement for the purpose of accessing Monitor Well No. D-12 from a public highway, the centerline of which is described as follows:

Beginning at a point which lies South 00°00'42" East along the east line of Section 19, Township 3 South, Range 4 West, Salt Lake Base and Meridian, a distance of 1,332.55 feet, and South 89°54'33" West, a distance of 2,346.78 feet from a witness corner to the Northeast corner of said Section 19, said point being on the easterly right-of-way line of State Route 112; and running thence over and across a prescriptive right-of-way for Roger's Road the following three (3) courses: South 89°11'52" East, a distance of 1,865.02 feet; thence South 89°49'44" East, a distance of 766.25 feet; thence South 89°13'27" East, a distance of 371.00 feet to a point on a dirt road within the 100' wide right-of-way of the Western Pacific Railroad-Grantsville Tooele Branch, on file with the Tooele County Recorder's Office, dated May, 1917; thence South 00°41'04" West along said dirt road, a distance of 727.17 feet to a point on the perimeter of the fifty foot Monitor Well easement and point of terminus.



SUMMARY OF WELL SURVEY DATA TEAD Phase II RFI Groundwater Monitoring Wells

-----Elevations (ft above MSL)-----

				Top of	Bottom of		
Well No.	Measuring Point	Brass Cap	Bround Surfac	Well Screen	Well Screen	Measur	ing Point
			•			Northing	Easting
C-41	4804.70	4802.32	4801.67	4445.68	4425.68	7364933.324	1406930.413
C-42F	4785.09	4785.52	4785.27	4445.27	4425.27	7365504.752	1406335.618
C-43F	4754.87	4755.23	4755.21	4436.21	4416.21	7366968.52	1406061.58
C-44	4722.81	4720.44	4719.82	4439.82	4419.82	7367591.88	1404021.61
C-45							
D-12	4803.05	4800.56	4800.25	4455.25	4435.25	7367777.995	1410018.176
D-13	4720.05	4717.40	4720.47	4358.47	4338.47	7371760.079	1410629.706
D-14	4592.80	4590.93	4590.39	4335.39	4315.39	7374264.49	1403669.88
D-16	4580.11	4577.75	4577.20	4346.20	4326.20	7377300.289	1409139.940
D-17							
D-18							
D-19							


MSL: mean sea level

F for selected well identifiers designates flush-mount surface completion.

Coordinates for measuring point are US State plane 1983, Utah Central 4302, NAD 1983 (CONUS), GEO1D96 (continental US)

All survey data generated by Ward Engineering of Salt Lake City, Utah

C-45, D-17, D-18, and D-19 have not been surveyed as of 7/21/05.





TOOELE ARMY DEPOT MONITORING WELL SAMPLING DATA

Well II	Well ID: 0-12						Initial Depth to Water: 339,61						
Sample	ID:				· -	Total Depti		365.			<u></u>		
Duplies	te ID:				···	Well Diam							
Sample	Depth:					(a) 1 Casin	g Volume:						
Date:	10/4	104				(b) 1 Filter	Pack Water Vol	ume:			<u> </u>		
Sample		 ,				(a) + (b) x 3	Minimum Volu	ime to Purge			 _		
Method	of Sampl	lopmen t ling:	<u>B9</u>	ler	·	Method of		<u> </u>		<u> </u>		 _	
Time	Intake depth	Rate (gpm)	Cum. vol. (gal)	Temp (°F)	pH (units)	Conductiv (µS/cm)		TDS (g/L)	DO (mg/L)	ORP (mv)	Salinity (ppt)	Color & Sedimer	
1030	*15+	Bailer	_3	57,3	7.53	870	71000	,	<u> </u>		 	1019790	
1101	10th	Bailer	30	57.0	7.56	779	71000			 	 	Fine	
1140	aoth	Bailer	60	58.5	7.54		>1000			1	<u> </u>	Cloudy	
, ,	Surg;		well	انيا	Surge	Bloci						noné	
		Bailer	75	60.3	, ~		71000	,				Cloudy	
	Sura		Well	w	Surge							none	
; I	\ \frac{1}{2}	Bailer		61.4	7.56		,					Cloudy	
1:23							7,000					pone	
						1		1		<u> </u>		 	
												 	
					·	 						 	
										 		 	
	p	H Calibrati	on (select two)				vity Meter		Turbi	dimeter Ca	alibration	<u> </u>	
Buffe solutio		pH 4.0	pH 7.0		10.0	Solution	991	Standaro	- T				
Instrum			7.0	1	.0	Instrument		Instrume	nt	î, 39 î,39			
readin			L 0741		46	reading	0745	reading		743			
Notes:	*B9	iler '	holds	3 0	18		•						



TOOELE ARMY DEPOT MONITORING WELL SAMPLING DATA

Well II	<u>): [)</u>	-12		<u></u>		Initial Depth to Water: 339,61								
Sample	ID:					Total Depth		65.50						
Duplier	ne ID:	·				Well Diame	Well Diameter: 4"							
Sample	Depth:	 				(a) 1 Casing	Volume:	7001						
Date:	101	4/04				T	Pack Water Volum							
Sample	d By: ()					(a)+(b)x3=	Minimum Volum		: 519	29]				
Method of Sampling: 4" Submersible						Method of P	Development Aureine:		iubme	(sible				
Time	Intake depth	Rate (gpm)	Cum. vol. (gal)	Temp (°F)	pH (units)	Conductivit (µS/cm)	ty Turbidity (NTUs)	TDS (g/L)	DO (mg/L)	ORP (mv)	Salinity (ppt)	Color & Sediment		
1335		4.09	0					1				- Common		
1348	364	4.21	52	G5.2	7.49	840	182	1		ļ		Cloudy		
1401	364	4.21	104	G3.3	7.45	829	56.8	1-1		 		Cloudy		
1414	364	4.09	156	G3.5			29.3	1-1			 	Cloudy none		
1427	364	4.21	208	62.5	7.46		19.5					Clean		
	Pump	i I	1 4	ushed	well	57		1				none		
	. , ,		ter Backf	US 63.1	7.48	837	15	1		\vdash		Cloudy		
1459		4.21	960	6368		810	11.3	1			<u> </u>	none		
1512	364	4.09	312	62.7	7,45	825	6.98	1				C/eac		
1514	Pump	off	Backflus		well	5+		1		_ 		none		
1528	Palampi		1	G1.3	7.48	811	45.2	1-1				Clear		
1541	364	4,47		60.0	7.47	795	7,13	 				Clear		
	pH Calibration (select two)						vity Meter		Turbic	dimeter Ca	alibration	lnone		
Buffer solution		pH 4.0	pH 7.0	pН	10.0	Solution		Standard			Польцон			
lnstrume reading						Instrument reading		Instrument reading	ı					

Notes:

Pg 1 of 2



TOOELE ARMY DEPOT MONITORING WELL SAMPLING DATA

Well II	<u>):</u>	D-12				Initial Depi	h to Water:		•			·		
Sample	iD:					Total Depti	a of Weil:			<u> </u>				
Duplie:	ne ID:					Well Diameter:								
Sample	Depth:	 .				(a) 1 Casing	(a) 1 Casing Volume:							
Date:				<u> </u>		(b) 1 Filter	Pack Water Vol	ume:				- <u>-</u>		
Sumple	d By:					(a) + (b)x 3=	Minimum Volu	ime to Purg	e:			<u> </u>		
Method	of Samp	ling:				Method of	Purging:							
Time	Intake depth	Rate (gpm)	Cum. vol. (gal)	Temp (°F)	pH (units)	Conductive (µS/cm)	ity Turbidity (NTUs)	TDS (g/L)	DO (mg/L)	ORP (mv)	Salinity (pp!)	Color & Sediment		
1554	364	4,47	416	59.3	7.50	790	6.90	,		 	 	Clear		
1607	364	4.47	468	59.5	7.45		6.37				 	Clesin		
1620	364	4,21	520	58.8	7,44	789	3.79		<u> </u>	 	 	Clear		
1633	364	4.21	572	58.5	7.47	785	3,83			1		Clear		
Z:52											 	none		
								1		 				
	.,											 		
										 				
					_							 		
						·								
	P	H Calibratio	on (select two)			Conducti Calib	vity Meter ration		Turb	idimeter Ca	ilibration	<u> </u>		
Buffer solutio		pH 4.0	pH 7.0	pH	10.0	Solution		Standar		-				
Instrum readin						Instrument reading		Instrume reading				,		

Notes:

pg 2 of 2


41
Monday October 4, 2004
Weather Clear, Cool - 60°
Wind Breeze From South
0704 Acrive at 0-12 and Start Setup
Jeff WP915005 on-site
SWL 339.61 TO 365.56'
0737 Calibiate equipment
0827. A Hempted to bail well, Bailer is getting
hung up at ~ 335 ft Altached Surge block
and was able to reach bottom
1004 Pump and piping installed to the bottom
with no problems. Removed pump and piping
with no problems, hemoved pump and piping and will bail and surge when 3" bailer arrives
1030 1st Bailer removed Parameters Taken
1101 st 10th Bailer removed parameters Taken
1148 20th Bailer removed, Parameters Taken
1146 Surging well W/ Surge Block
1221 25 KBailer remared, Parameters Taken
1225 Sura na well w/ Surae block
1253 30th Bailer removed, Parameters Taken
only a minor amount of sand detected, Bailing
and Surging Complete
1306 Lowering our 0 900 0,000
1306 Lowering pump and piping 1332 Pump on establishing Flow
1335 Flow established at 4 apm, Intake 364'
1428 Pump OFF, BackFlushed well 5x
1514 Pump OFF, BackFlushed well 5+
1633 parameters stable and Furdity Turbidity below
5 NTUS, 572 sal pumped
1634 Pump off, Removing pump and piping
1717 Decon Equipment
1751 Leguing 0-12 + 6WTP

Date

JECT Continued From Page _ 30 1:180 17:32 Balk 1465 Cok arrived abula Stor /al 16:00 14 44 157:15 15:30 unplela sile 18:00 Locker Continued on Page Read and Understood By Jeff Bigelow-Purson 10-4-04 Signed Date Date

10-5-04 34
PROJECT TEAD Phu& IT Development D-12 Continued From Page THE DEVOLOPMENT on-site 90-day PARS N7042780 08/30 21,000 - gallas truck into 69:00 PARSW20426801 PARSIVZ0427801 09:20 Continued on Page Read and Understood By

Jeff Baelow-Purcose 10-5-09
Signed Date Signed Date



PDB MONITORING WELL SAMPLE LOG

(If multiple PDB samplers are deployed in a single well, use one sample log for EACH sampler)

PDB DEPLOYMENT

Project No.:		Well LOCID:	0-12				
Installation: TOOELE ARMY	/ DEPOT	Log Book No.	Log Book No. Pages: 45				
Contractor: Veolia W	ater	Sampler(s):					
PDB Deployment Date: /L	1/04; Time: 1215	Weather: Wind D	oir: , at ~n	nph; Air Temp: °F			
Well Labeled: Y/N [y] Wel	l Secure: Y/N[y]	Comments:					
PID SN:		Well Headspace (PID mu)	Odor			
Water Level Instrument: Sol	inst	Serial No.: n	ode1 101				
SWL (ft BTOC): 339,60	Measured Well Deptl	h (ft BTOC):	r	Depth (ft BTOC):			
Sediment Thickness (ft):	Number of PDB Sam	plers deployed in	Tether Line Mat	erial:			
	well:		Teston coat	ed S.S.			
Type of Tether Weight: 5.5	ò.	Total Weight used					
PDB bag length (inches): 16	PDB bag volume (ml		Protective Mesh	used: Y/N [y]			
Source of Deionized Water use	ed in Bag: Moon	+ Olympus					
	·	7 1					

PDB RETRIEVAL AND SAMPLE

Well LOCID: 0-12		PDB Retrie	eval Date: 11 33/04	Retrieval Time	e: 1143
Was ALL Deployed Eq	uipment Retrieved (Line,	Bags, Weights):	Y/N [y] if NO,	, Explain:	
Comments on Well and P	DB Tether Assembly Condi	tion:			_
Weather: Wind Dir:		Precipitation:	Air	Temperature:	°F
Sample No. (FIELDSAM)	PID): 0-126W001	Sample	Date:// /23/04	Sample Time:	1145
Sampler (s):	Sample Beg. Depth (ft bg	s):	Sample Ending De	epth (ft bgs):	
Sample Collection Method	i: Discharge Tube (Other (explain):			
Approximate Volume of F	Excess Sample Water After	Sampling (ml):	<u> </u>		
Excess Sample Water Place	ced in Drum: Y/N []	Drum Nun	iber:		
SWL Following Sampling	(ft BTOC):	Sample Eq	uipment Decon: Da	te: by:	
Decon Water Placed in Dr	um: Y/N []	Drum Num	iber:		
Prepared by:	Date: / /	Reviewed by:		Date: /	/

diversity and	45
	Tuesday November 2, 2004
	Weginer Clear, Cool 230°
27112	Wind: Breeze From South
0770	Arrive at 0-16 and start Setup
0/30	Calibrated Equipment
0816	Pump on establishing flow
0852	Flow established at 9 gpm, Intake 252
0000	Palameters stable Turbidity less than 5 NTV:
0853	Pump off
0900	Remarks Name and a second
0942	Removing pump and piping Decon Equipment
1042	Leaving 0-16 > Tanker
1103	Arrive at Tanker and offloading
	~350 gal of Purge water
	November
	Wovember 17 2004
	Weather : clear, warm 2500
	Wind None
1a15	Arrive at 0-12 and installing 1 sampler
	SWL 334.60) 9+ 351.5
	Arrive at D-13 and installing a samplers
1	9+317, SWL 357
1305	Arrive at 0-16 and Installing I sampler
	7 + 240, SWL 214.00
	<u> </u>

1 H

	55
	Tuesday November 23 2004
	Tuesday November 23, 2004 Weather: Clear, Mild 240°
	Wind. None
1130	Arrive at 0-12 and preparing to sample
11113	2 ON STATE
	Removing Di POB Sampler
	Sampled PDB sampler, 40 mc w/MCL 3 vons
	<u>U-136W001</u>
1157_	Leaving 0-12 -> 0-13
1205	Arrive at 0-13 and preparing to Sample
	Removing POB sampler
	Sampled PDB sampler, 40ML WIHCL
^	(3) UOAS Taken P-136WOOL
	(3) von's Tyken 0-13 FD001
	Leaving 0-13 7 0-16
1300	Allive at 0-16 and preparing to Sample
<u> 1306</u>	5 vons laken hemoving PDB Sampler
	5 VOB'S Taken from POB Sample T 40ML W/HCL
<u> 131 </u>	(3) D-166WOOL
<u> 1311</u>	(1) D-16 M5001
	(1) 0-1650001
<u> 13a1</u>	Leaving 0-16 7 Palsons Field office
· -	
-——	
<u></u>	
	· · · · · · · · · · · · · · · · · · ·
<u></u>	
<u></u>	
~ ·	
~	
·	
~	
	

ANALYTICAL QUALITY CONTROL SUMMARY

Samples were collected in accordance with the analytical and quality control specifications of the Final Phase II RCRA Facility Investigation SWMU-58 Work Plan (Parsons, 2003). Passive diffusion bag samplers were deployed in wells D-12, D-13, and D-16 on the same day. Samples (including field quality control samples) were collected on the 23rd of November 2004 and submitted to Ecology and Environment Analytical Service Center, a Utah and USACE-certified analytical laboratory.

Results were received and submitted to third party data review by Synectics. Data review included checks of the following data quality elements: Holding times, continuing calibration verification, method blanks, field blanks, laboratory control sample recovery, matrix spike and matrix spike duplicate recovery and precision, surrogate recovery, and field duplicate precision. No out of control events warranting qualification of the data were observed. Analytical and data validation reports are attached.



analytical services center

International Specialists in Environmental Analysis



4493 Walden Avenue, Lancaster, New York 14086 Tel: 716/685-8080, 800/327-6534 • Fax: 716/685-0852 • Email: asc@ene.com

December 13, 2004

Jan Barbas
Parsons Engineering Science, Inc.
406 W. South Jordan Pkwy.
Suite 300
South Jordan, Utah 840953944

RE: Tooele RCRA Phase II Work Order No.: 0411354

Dear Jan Barbas,

Analytical Services Center received 5 samples on Monday, November 29, 2004 for the analyses presented in the following report.

The ASC certifies that the test results in this report meet all requirements of NELAC for which it holds certification except as noted in this narrative and/or as flagged in the report.

The ASC is accredited in the Fields of Testing Potable water (SDWA), Solid and Chemical Materials (Solid Hazardous Wastes, RCRA), Water (CWA and other non-potable water) and Air and Emissions. Its primary accrediting authorities are New York State Department of Health and Florida Department of Health. The particular analytes/methods certified may be ascertained by requesting the laboratory's current certificates from your laboratory Project Manager.

You will receive an invoice under separate cover.

E & E will retain the samples addressed in this report for 30 days, unless otherwise instructed by the client. If additional storage is requested, the storage fee is \$1.00 per sample container per month, to accrue until the client authorizes sample destruction.

This report is not to be reproduced, except in full, without the written approval of the laboratory.

Sincerely,

Project Manager

CC:

Enclosures as noted

Analytical Services Center

International Specialists in Environmental Analysis Lancaster, New York 14086-

ecology and envisorment, inc. Phone: (716) 685-8080

Fax: (716) 685-0852

Laboratory Results

NYS ELAP ID#:

10486

CLIENT:

Parsons Engineering Science, Inc.

Project:

Tooele RCRA Phase II

Lab Order:

0411354

Date Received: 11/29/2004

Work Order Sample Summary

Lab Sample ID 0411354-01A 0411354-02A 0411354-03A	Client Sample ID D-12GW001 D-13GW001 D-13FD001	Alt. Client id	Collection Date 11/23/2004 11:47:00 AM 11/23/2004 12:18:00 PM
0411354-04A 0411354-05A	D-16GW001 TRIP BLANK		11/23/2004 12:30:00 PM 11/23/2004 1:11:00 PM 11/23/2004 7:00:00 AM



Laboratory Results

NYS ELAP ID#: 10486 Phone: (716) 685-8080

Client:

PARSONS ENGINEERING SCIENCE, INC.

Project:

Tooele RCRA Phase II

Lab Order:

0411354

CASE NARRATIVE

Samples were received at a cooler temperature of >15 C. They were shipped on 11/23/04 and received at the E&E corporate office on 11/26/04. The samples were then delivered to the Analytical Services Center on 11/29/04. A trip blank was received but was not listed on a chain-of-custody form. Jan Barbas was notified on November 29, 2004 and instructed the laboratory to attempt to analyze all samples including the trip blank within half the hold time (7 days). All samples were analyzed on the seventh day of the hold time.

GCMS VOLATILES

A DB 624 column and a trap packed with OV-1, Tenax, silica gel and activated charcoal was used for the volatile analysis.

Sample Analysis

All aqueous volatile samples were determined to be at a pH of 1.

All samples were analyzed within hold time.

Calibration and Tunes

All initial and continuing calibrations were acceptable.

There were no manual integrations required.

QC

All surrogate recoveries were within acceptable limits.

All blank analyses were acceptable.

All matrix spike/spike duplicate (MS/MSD) recoveries and RPD values were acceptable.

All laboratory control sample(LCS) recoveries were acceptable.

All internal standard area responses were acceptable.

Tony Bogolin

December 13, 2004

Project Manager

SAMPLE RECEIPT RECORDS

	CHAIN OF CUSTODY	Project Name:	Tocele Industrial Area	Contractor:	Parsons - SLC	Parsons Point of Contact: Jan Barbas 406 W. South Jordan Parkway
	PARSONS	Project Manager:	Ed Staes	Installation:	TEAD	Suite 300 South Jordan, Utah 84095
ĺ	COC ID: 821	Sample Coordinator:	Jeff Bigelow	Sample Program:	Shallow Soil Sampling	(801) 572-5999 FAX (801) 572-9069

Site ID	Location ID	Sample ID	Matrix	Method	Туре	Sample No.	Log Date	Log Time	Logged By	Beg. Depth	End, Depth	Total Conts.
D-12	D-12	D-12GW001	WG	DF	N	1	11/83/04	1147	スピ			3
	Analysis	Lab	Cooler	No. Conts	AB Lot	EB Lot	TB Lot	Remarks:	· ·		·	
voc		ECEN					23 110401]				

Relinquished by (Signature)	Date/Time	Received by (Signature)	Date/fime
May Farman	11/23/04 14/0		0171 PO WH ES
TOEWNEX	11/23/04 1600	tree	11/24/24 120
			170-40
•	:		,

·

40-44-6-4

CHAIN OF CUSTODY	Project Name:	Tocele Industrial Area	Contractor:	Parsons - SLC	Parsons Point of Contact: Jan Barbas 406 W. South Jordan Parkway
PARSONS	Project Manager:	Ed Staes	Installation;	TEAD	Suite 300 South Jordan, Utah 84095
COC ID: 822	Sample Coordinator:	Jeff Bigelow	Sample Program:	Shallow Soil Sampling	(801) 572-5999 FAX (801) 572-9069

Site ID	Location ID	Sample ID	Matrix	Method	Туре	Sample No.	Log Date	Log Time	Logged By	Beg. Depth	End. Depth	Total Conts.
D-13	D-13	D-13GW001	WG	DF	N	<u> </u>		1218				
······································	Analysis	Lab		No. Conts	AB Lot	EB Lot		Remarks:				L
VOC		ECEN		! 			2340401]				

Relinquished by (Signature)	Date/Time	Received by (Signature)	Date/Time
Alley Harmon	11/×23/04 1410	The state of the s	23 MOV 04
70 F30 EV	1/2×04 1600	Till	11/29/21 1820
		2	1
	:		F"

.

CHAIN	OF CUSTODY	Project N	ame:	Tooele in	dustrial Area	e Contr	actor:	Parsons - SLC		rsons Point of Cor 6 W. South Jordan		ıs
İ	PARSONS	Project M	anager:	Ed Staes		Instal	lation:	TEAD	Su	ite 300 uth Jordan, Utah 8		
COCIE	o: 823	Sample C	oordinator:	Jeff Bigel	ow	Samp	le Program:	Shallow Soil Sa)1) 572-5999 FAX		
Site ID	Location ID	Sample ID	Matrix	Method	Туре	Sample No.	Log Date	Log Time	Logged By	Beg. Depth	End. Depth	Total Conts.
D-13	D-13	D-13FD001	WG	DF	FD	1	11/83/04	1230	エコ			3
	Analysis	Lab	Cooler	No. Conts	AB Lot	EB Lot	TB Lot	Remarks:				
VOC	Ĺ	ECEN					2340401					

Received by (Signature)

Pate/Time

Received by (Signature)

Date/Time

Received by (Signature)

Date/Time

Pate/Time

Pate/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

voc

ECEN

CHAII	OF CUSTODY	Project N	ame:	Topele In	dustrial Area	a Contra	actor:	Parsons - SLC		sons Point of Con W. South Jordan		es
•	PARSONS	Project M	anager:	Ed Staes		Install	ation:	TEAD		te 300 ith Jordan Utah 8	4095	
- COC 1	D: 827	Sample C	oordinator:	Jeff Bige	low	Samp	le Program:	Shallow Soil S		1) 572-5999 FAX		
Site ID	Location ID	Sample ID	Matrix	Method	Type	Sample No.	Log Date	Log Time	Logged By	Beg. Depth	End. Depth	Total Conts.
D-16	D-16	D-16GW001	WG	DF	N	1	11/23/04	1311	スロ		!] 3
	Analysis	Lab	Cooler	No. Conts	AB Lot	EB Lot	TB Lot	Remarks:				

Relinquished by (Signature)	Date/Time	Received by (Signature)	Date/Time
Jeffen Otam	11/23/04 1410	XEM	23Nav04 1410
YEDI STO PEN EX	11/23/04 1600 K	Men	11/09/04 120
			<u> </u>
		0	:

CHAIN OF CUSTODY	Project Name:	Tooele Industrial Area	Contractor:	Parsons - SLC	Parsons Point of Contact: Jan Barbas 406 W. South Jordan Parkway
PARSONS	Project Manager:	Ed Staes	Installation:	TEAD	Suite 300 South Jordan, Utah 84095
COC ID: 828	Sample Coordinator:	Jeff Bigelow	Sample Program:	Shallow Soil Sampling	(801) 572-5999 FAX (801) 572-9069

Site ID	Location ID	Sample ID	Matrix	Method	Type	Sample No.	Log Date	Log Time	Logged By	Beg. Depth	End. Depth Total Conts.
D-16	D-16	D-16MS001	WG	DF	MS	1	11/83/04	1311	511		i /
	Analysis	Lab	Cooler	No. Conts	AB Lot	E8 Lot	TB Lot	Remarks:	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	
voc		ECEN					23110401				

Received by (Signature)

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

Date/Time

CHAI	N OF CUSTODY	Project N	ame:	Tocele In	idustrial Area	Contr	actor:	Parsons - SLC	-	arsons Point of Cor 06 W. South Jordan		S
PARSONS		Project Manager: Ed Staes			Installation:		TEAD		Suite 300 South Jordan, Utah 84095			
coc	COC ID: 829 Sample Coordinator: Jeff Bigelow		Samp	Sample Program: Shallow Soil Sampling			(801) 572-5999 FAX (801) 572-9069					
Site ID	Location ID	Sample ID	Matrix	Method	Туре	Sample No.	Log Date	Log Time	Logged By	Beg. Depth	End. Depth	Total Conts.
D-16	D-16	D-16SD001	WG	DF	\$D	1	11/33/04	1311	311			
	Analysis	Lab	Cooler	No. Conts	AB Lot	EB Lot	TB Lot	Remarks:				
voc		ECEN					23110401]				

•

Relinquished by (Signature)	Date/Time	Received by (Signature)	Date/Time
Slax Otamin	11/23/04 1410	(III)	23Nox-04 1410
AS LED EX	d) for 204 1600		(1/24/01 1300
		•	

to the control of the control of the control of the control of the control of the control of the control of the

11811	Coo	ler Receipt Form	
No. of Packages:		Date Received:	- Ilmby
Package Receipt No.:	1506	Project or Site Name:	11/09/07
Client	15016		
	100,001,5		
1. Did coolers come with	mination and Receipt Pha a airbill or packing slip? e and print airbill number below: Fi		Yes No NA
Shipped as high	hazard or dangerous goods?	<u> </u>	Yes No NA
2. Did cooler(s) have cus			· (res) No NA
	ibroken and intact on receipt?		TES NO NA
4. Were custody seals da	_		Mes No NA
5. How was package sec	ured? II Not secured II Fi	iberglass Tape il TAPE	
			- Particular recording agreem
B. Unpacking Phas	se		
6 Data englanda)	is both con	ier(s) opened by:	Oh.
Date cooler(s) opened Was a terminature by:	ank vial included inside cooler(s)?	(Squature)	
		Coolog Triber	Yes No NA
	ase record reinperature vial of	Cooler Temperature for Each Cooler, Ra	
9457 2745 Z	MI >5.0	Military and the Children of the State of State	HAURO CONTRACTOR CONTR
012 2707 7	70,5		
Thermometer No.:	(3) Correction Factor:	*If temperature is outside of Notification form indicating	acceptable range, prepare a PM
8. Were the C-O-C forms	received?		Yes No NA
C-O-C forms numbers			
	naterial used in cooler(s)?/		Yes No NA
Type of material:	☐ Vermiculite X Bubble W		
	l, what was the means (type ice) of	cooling used: Devet Dry Distue (Other NA
· · · · ·	aled in separate plastic bags?		Fes No NA
	e unbroken and in good condition?		Yes No NA
13. Interim storage area if	not logged:		
In: Date	Time	Signature	
Out: Date	Time	Signature	
C. Login Phase			
Samples Logged in By Signa	. (//////	Date:	Ulzalin
	ls complete (e.g. date, time preserv		/ Yes No NA
	lled out properly in black ink and sig	gried?	Yes) No NA
	ee with containers received?		7965) NO NA
	iners used for the tests requested?		YES) NO NA
	rvatives listed on the sample labels?	·	Mes No NA
·	volume sent for the tests requester	d?	No NA
20. Were all volatile sample	s received without headspace?		(Yes) No Na

PROJECT MANA	GER NOTIFI	CATION
Originator: KONKI	Date:	11/29/24
ASC Project Manager: Tom Boyle	Client:	
Job Nos.:		
Sample Nos.:	· <u></u> :	
Nature of Concern:		
□ Samples warm @ <u>>15.0 °</u> c		
List Containers:		
		· ·
Containers broken. List:		
Discrepancy between sample containers and COC form		
Incorrect or insufficient preservation		
Headspace in volatile vials (waters samples only)		
Lost shipment:		
Other (e.g., leaking container, unreadable label, COC form):		
Further Description:		
	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	-
PROJECT MANAGER FOLLOW-UP		, ,
Notified Client: Jen Barlow	·	on 11 29 04 (Date)
Notification attempted:		(,
Means:		on(Date)
Notification unnecessary Notify Samole Management		
1 Notify Sample Management Action: Sa attached email		
asservey oman		
Project Manager Signature Dat	Meday	·
Project Manager Signature Dat	e	

Bogolin, Tony

From:

Barbas, Jan [Jan.Barbas@parsons.com]

Sent:

Monday, November 29, 2004 5:00 PM

To:

Bogolin, Tony

Cc:

Torgensen, John

Subject: RE: Tooele sample receipt 112904

Hi,

Please analyze the trip blank.

The EDD does go to Synectics.

Jan

From: Bogolin, Tony [mailto:ABogolin@ene.com] Sent: Monday, November 29, 2004 2:43 PM

To: Barbas, Jan Cc: Torgensen, John

Subject: RE: Tooele sample receipt 112904

Here is the sample receipt information. We received a trip blank that was not listed on the COC forms. We logged it in for analysis. Let me know if you do not want it analyzed.

Does the EDD for these samples go to Synectics?

Tony

From: Barbas, Jan [mailto:Jan.Barbas@parsons.com]

Sent: Monday, November 29, 2004 2:37 PM

To: Bogolin, Tony

Cc: Torgensen, John; Wehrmann, Pamela A SPK Subject: RE: Tooele sample receipt 112904

Go ahead and log them in. If you can run them tommorrow I think that would work since I miscounted the hold time. We have until tommorow. If not lets plan on running them anyway. I'll let the client know and get their input.

Jan

From: Bogolin, Tony [mailto:ABogolin@ene.com]
Sent: Monday, November 29, 2004 12:16 PM

To: Barbas, Jan

Cc: Torgensen, John; Wehrmann, Pamela A SPK Subject: RE: Tooele sample receipt 112904

No. The instrument is fully loaded for today so the quickest would be some time tomorrow evening if we could get another instrument up for low-level water VOCs.

From: Barbas, Jan [mailto:Jan.Barbas@parsons.com]

Sent: Monday, November 29, 2004 1:45 PM

To: Bogolin, Tony

Cc: Torgensen, John; Wehrmann, Pamela A SPK Subject: RE: Tooele sample receipt 112904

Hi Tony,

Thanks for the heads-up. We thought they'd be in last Wednesday. The rule on warm samples is that if they are analyzed within 1/2 hold time they are ok. These were sampled Tuesday. That would mean they have to be analyzed by mid-night today. Can you do that?

Jan

From: Bogolin, Tony [mailto:ABogolin@ene.com] Sent: Monday, November 29, 2004 11:30 AM

To: Barbas, Jan Cc: Torgensen, John

Subject: Tooele sample receipt 112904

Jan:

We received these samples today. They were shipped by FedEx on 11/23 and marked for overnight delivery. Why they did not show until today I don't know. Of course they were warm >15 C. Should we cancel the analysis as they are VOC samples? Let me know.

Tony

<<tooelecoc.pdf>>

MISC RECORDS



Analytical Services Center

International Specialists in Environmental Analysis

Lancaster, New York 14086-

Phone: (716) 685-8080

Fax: (716) 685-9852

Laboratory Results

NYS ELAP ID#:

10486

Phone:

(716) 685-8080

Order:

0411354

nt:

Parsons Engineering Science, Inc.

ject:

Tooele RCRA Phase II

DATES SUMMARY REPORT

	· · · · · · · · · · · · · · · · · · ·		•
3) Sample ID (CLIENT)	Matrix Test Name	Collection Date Received Date HT (Days) / HT Expire Analyzed* - Analysis/BatchID	Type DF #Analytes F
354-01A D-12GW001	Water Low Level VOCs by Method 8260B	11/23/2004 11:47:00 AM 11/29/2004 12:00:00 PM 14:C 12/7/2004 11:47:00 AM 11/30/2004 4:18:00 PM 1072898	SAMP 1 21 [
3) Sample ID (CLIENT)	Matrix Test Name	Collection Date Received Date HT (Days) / HT Expire Analyzed* - Analysis/BatchID	Type DF #Analytes F
354-09A D-13FD001	Water Low Level VOCs by Method 8260B	11/23/2004 12:30:00 PM 11/29/2004 12:00:00 PM 14:C 12/7/2004 12:30:00 PM 11/30/2004 5:21:00 PM 1072900	SAMP 1 21 [
B) Sample ID (CLEENT)	Matrix Test Name	Collection Date Received Date HT (Days) / HT Expire Analyzed* - Analysis/BatchID	Type DF #Analytes F
854-02A D-13GW001	Water Low Level VOCs by Method 8260B	11/23/2004 12:18:00 PM 11/29/2004 12:00:00 PM 14:C 12/7/2004 12:18:00 PM 11/30/2004 4:49:00 PM 1072899	SAMP 1 21 [
B) Sample ID (CLIENT)	Matrix Test Name	Collection Date Received Date HT (Days) / HT Expire Analyzed* - Analysis/BatchID	Type DF #Analytes Fl
954-04A D-16GW001	Water Low Level VOCs by Method 8280B	11/23/2004 1:11:00 PM 11/29/2004 12:00:00 PM 14:C 12/7/2004 1:11:00 PM 11/30/2004 5:52:00 PM 1072901	SAMP 1 21 [
3) Sample ID (CLIENT)	Matrix Test Name	Collection Date Received Date HT (Days) / HT Expire Analyzed* - Analysis/BatchID	Type DF #Analytes Fi
354-05A TRIP BLANK	Water Low Level VOCs by Method 82608	11/29/2004 7:00:00 AM 11/29/2004 12:00:00 PM 14:C 12/7/2004 7:00:00 AM 11/30/2004 3:46:00 PM 1072897	SAMP 1 21 [

rom: C-Collection / R- Receipt(VTSR) / P-Prep / T-TCLP Prep

salyzed" reflects the analysis date and time or injection time for analytical tests. For preparation tests "Analyzed" reflects the start of the preparation except when "AFCEE criteria used"; flag indicates date time of completion of the preparation.

ICLP/SPLP Extractions and subsequent preparation tests..."Analyzed" reflects the date of TCLP/SPLP Extraction/preparation. For Re-extracted (RE) samples: Preparation tests completed dates reflects extraction from the original sample leacheate unless an "RE" Sample exists for the extraction (tumble) test.



Analytical Services Center

International Specialists in Environmental Analysis Lancaster, New York 14086-

Fax: (716) 685-0852

Laboratory Results

NYS ELAP ID#:

Client:

Parsons Engineering Science, Inc.

Project:

Tooele RCRA Phase II

Work Order:

0411354

Method References

GCMS Volatiles

Parsons, Tooele - VOCs, Low Level by GCMS Method

Test Methods for Evaluating Solid Waste: Physical/Chemical Methods. 3rd ed. 1986. Volumes. I A, 1B, 1C & Volume 2. (Includes all Updates). U.S. Environmental Protection Agency, Office of Solid Waste and Emergency Response.

RESULTS SUMMARY



i Analytical Services Center

International Specialists in Environmental Analysis

4493 Walden Avenue

ecology and environment, inc. Lancaster, New York 14086

Laboratory Kesuits

NYS ELAP ID#: 10486

Phone:

(716) 685-8080

Client:

Parsons Engineering Science, Inc.

Lab Order: 0411354

Project: Tooele RCRA Phase II Client Sample ID: D-12GW001

Alt. Client ID:

Method: SW8260B

Collection Date: 11/23/2004 11:47:00 A % Moist:

Lab ID: 0411354-01A

Sample Type: SAMP

Matrix: Water

Test Code: C_8260B_5030B_LL_W_018

.OW LEVEL	VOCS BY	METHOD	8260B
-----------	----------------	--------	-------

OW LEVEL VOCS BY METHOD 8260B				M	ethod: S	W8260B F	Prep Method: SW5	030B_LL
nalyte .	Result	Q	RL	Units	DF	Date Analyzed	Run Batch ID	Analyst
1.1-Trichlorgethane	ND		1.00	uali	1	11/7/7/2004 A:49:00 DM	DEDDA 0411301	0147

Analyte .	Result Q	RL	Units	DF	Date Analyzed	Run Batch ID	Analyst
1,1,1-Trichloroethane	ND	1.00	μg/L	1	11/30/2004 4:18:00 PM	PERRY_041130A	RMJ
1,1,2-Trichlorgethane	ND	1.00	μg/L	,	***************************************	LC05(1_041330N	HMD
1,1-Dichloroethane	ND	1.00	μg/L	,			
1,1-Dichloroethene	ND	1.00	μg/L	1	•		
1,2-Dichloroethane	ND	1.00	μg/L	1			
1,2-Dichtoropropane	ND	1.00	µg/L	1			
Benzene	ND	1.00	μg/L	1			
Carbon tetrachloride	NO	1.00	μg/L	1			
Chloroethane	ND	1.00	μg/L	1			•
Chloroform	ND	1.00	μg/L	1			
cis-1,2-Dichloroethene	ND	1.60	μg/L	1			
Ethylbenzene	ND	1.00	μg/L	1		•	
m,p-Xylene	ND .	1.00	μg/L	1			
Methylene chloride	ND	2.00	μg/L	1			
Naphthalene	ND	1.00	μg/L	1			
o-Xylene	ND	1.90	μg/L	1			
Tetrachloroethene	ND	1.00	μg/L	1			
Toluene	ND	1.00	μg/L	1	·		
trans-1,2-Dichloroethene	ND	1.00	μg/L	1			
Frichtoroethene	ND	1.00	μg/L	1			
Vinyl chloride	ND	1.00	μg/L	1			
Surr:1,2-Dichloroethane-d4	110	70 - 130	%REC	1	11/30/2004 4:18:00 PM P	ERRY_041130A	RMJ
Surr:4-Bromofluorobenzene	108	70 - 130	%REC	1		-	
Sun:Toluene-d8	112	70 - 130	%REC	1			

Deficitions:

NP - Petroleum Pattern is not present

B - Analyte found in Method blank

DNI - Did not Ignite

J - Estimated value NC - Not Calculated

P - Post Spike Recovery outside limits

D - Diluted due to maxtrix or extended target compounds

E - Result above questitation limit (high standard or ICP linear range).

M - Maurix Spike Recovery ourside limits

ND - Not Detected at the Reporting Limit

R - RPD omside recovery Emits

^{* -} Recovery outside QC Errits

DF - Dilution Factor

H - Value Exceeds Maximum Contaminant Level

N - Single Column Analysis



LAnaiyucai betvices Center

International Specialists in Environmental Analysis

Sample Type: SAMP

ecology and environment, inc. Lancaster, New York 14086

Laboratory Results

NYS ELAP ID#: 10486

Phone:

(716) 685-8080

Client:

Parsons Engineering Science, Inc.

Client Sample ID: D-13GW001

Alt. Client ID:

Project:

Lab Order: 0411354

Tooele RCRA Phase II

Collection Date: 11/23/2004 12:18:00 P % Moist:

Lab ID: 0411354-02A

Matrix: Water

Test Code: C_8260B_5030B_LL_W_018

LOW LEVEL VOCS BY METHOD 8260B

Method: SW8260B

Prep Method: SW5030B_LL

Analyte	Result	Q	RL_	Units	DF	Date Analyzed	Run Batch ID	Analyst
1,1,1-Trichloroethane	ND		1.00	μg/L.	1	11/30/2004 4:49:00 PM	PERRY_G41130A	RMJ
1,1,2-Trichloroethane	ND		1.00	μg/L	1			
1,1-Dichtoroethane	NO		1.00	μg/L	. 1			
1,1-Dichloroethene	ND		1.00	μg/L	1			
1,2-Dichtoroethane	ИD		1.00	μg/L	1			
1,2-Dichtoropropane	ND		1.00	μg/L	1			
Benzene	ND		1.00	μg/L	1			
Carbon tetrachloride	CM		1.00	μg/L	1	•		
Chloroethane	ND		1.00	μg/L	1			
Chloroform	0.193	J	1.00	μg/L	. 1			
cis-1,2-Dichlorcethene	ND		1.00	μg/L	1			
Ethylbenzene	NØ		1.00	μg/L	1			
m,p-Xytene	ND		1.00	μg/L	1			
Methylene chloride	NĐ		2.00	μg/L	1			
Naphthalene	NO		1.00	μg/L	1			
o-Xylene	NO		1.00	μg/L	1			
Fetrachloroethene	ND		1.00	μg/L.	1			
Toluene	NO		1.00	μg/L	1			
Irans-1,2-Dichloroethene	ND		1.00	μg/L	1	-		
Trichloroethene	ND		1.00	μg/L	1			
Vinyl chloride	ND		1.00	μg/L	1			
Surr:1,2-Dichloroethane-d4	108		70 - 130	%REC	1	11/30/2004 4:49:00 PM P	ERRY_041130A	RMJ
Sun:4-Bromottuorobenzene	107		70 - 130	%REC	1			
Surr:Toluene-d8	113		70 - 130	%REC	1			

Definitions:

^{7 -} Recovery outside QC limits

DF - Dikution Factor

H - Value Exceeds Maximum Comaminant Level

N - Single Column Analysis

NP - Petroleum Pettern is not present

B - Analyte found in Method blank

DNI - Did not Ignite

^{3 -} Estimated value

NC - Not Calculated

P - Post Spike Recovery outside limits

D - Diluted due to maxtrix or extended target compounds

E - Result above quantitation limit (righ standard or ICP inear range).

M - Matrix Spile Recovery outside limits

ND - Not Detected at the Reporting Limit

R - RPD outside recovery limits



Alialytical octatics cetter

International Specialists in Environmental Analysis

4493 Walden Avenue

ecology and environment, soc. Lancaster, New York 14086

Laboratory Results

NYS ELAP ID#: 10486

Phone: (716) 685-8080

Client:

Project:

Parsons Engineering Science, Inc.

Lab Order: 0411354

Tooele RCRA Phase II

Client Sample ID: D-13FD001

Alt. Client ID:

Collection Date: 11/23/2004 12:30:00 P % Moist:

Lab ID: 0411354-03A

Sample Type: SAMP

Matrix: Water

Test Code: C_8260B_5030B_LL_W_018

AWLEVEL	HOOD BY METHOD	
LUWLEVEL	VOCS BY METHOD	8260R

LOW LEVEL VOCS BY METHOR	D 8260B		***	ſV	lethod:	SW8260B	Prep Method: SW	5030B_LL
Analyte	Result	Q	RL	Units	DF	Date Analyzed	Run Batch ID	Analyst
1,1,1-Trichtoroethane	ND		1.00	μg/L		11/30/2004 5:21:00 PM	PERRY_04113QA	RMJ
1,1,2-Trichtoroethane	ND		1.00	μg/L		· · · [11112
1,1-Dichloroethane	ND.		1.00	μg/L		· 		
1,1-Dichloroethene	ND		1.00	μg/L				
1,2-Dichloroethane	ND		1.00	μg/L		- 		
1,2-Dichloropropane	ND		1.00	μg/L				
Benzen e	ND		1.00	μg/L				
Carbon tetrachloride	ND		1.00	μg/L		1		
Chloroethane	ND		1.00	μg/L	,			
Chloroform	0.195	3	1.00	μg/L,	1	· [
cis-1,2-Dichloroethene	ΝĐ		1.00	μg/L		•		
Sthylbenzene	ND		1.00	μg/L		1	•	
n,p-Xylene .	ND		1.00	μg/L	•	· 		
Methylene chloride	ND		2.00	μg/L	1			
Vaphthalene	ND		1.00	µg/L	1			
o-Xylene	ND		1.00	μg/L	•			
Tetrachioroethene	ОN		1.00	μg/L	1			
Tatuene	ND		1.00	μg/L	1	· [
rans-1,2-Dichloroethene	ND		1.00	µg/L	1	· 	•	
Frichloroethene	ND		1.00	μg/L	1			
Vinyl chloride	ND		1.00	μg/L	1			
Surr:1,2-Dichloroethane-d4	109		70 - 130	%REC	_	11/30/2004 5:21:00 PM	PERRY 041130A	
Sum4-Bromofluorobenzene	107		70 - 130	%REC				1 11140
SumToluene-d8	113		70 - 130	%REC	•	· }		

Definitions:

[.] Recovery ourside QC limits

DF - Dilution Factor

H - Value Exceeds Maximum Contactions Level

N - Single Column Analysis

NP - Petroleum Pattern is not present

B - Analyte found in Method blank

DNI - Did not Ignite

I - Estimated volue

NC - Not Calculated

P - Post Spike Recovery outside limits

D - Diluted due to maximix or extended target correpounds

E - Result above quantitation limit (high standard or ICP irrear range).

M - Matrix Spike Recovery outside limits

ND - Not Detected at the Reporting Limit

R - RPD outside recovery timits



Analytical Del vices Center

International Specialists in Environmental Analysis

4493 Walden Avenue

ecology and environment, inc. Lancaster, New York 14086

Laboratory Results

NYS ELAP ID#:

10486

Phone: (716) 685-8080

Client:

Parsons Engineering Science, Inc.

Lab Order: 0411354

Project:

Tooele RCRA Phase II

Client Sample ID: D-16GW001

Alt. Client ID:

Collection Date: 11/23/2004 1:11:00 P

Lab ID: 0411354-04A

Sample Type: SAMP

Matrix: Water

Test Code: C_82608_5030B_LL_W_018

ı	OW L	EVE	VOCS	BY ME1	HODE	2608

LA	40	L	_	4	

Method: SW8260B

Prep Method: SW50308 LL

Analyte	Result Q	RL	Units	DF	Date Analyzed	Run Batch ID	Analyst
1,1,1-Trichloroethane	ND	1.00	µg/L	1	11/30/2004 5:52:00 PM	PERRY_041130A	FIMU
1,1,2-Trichloroethane	ND	1.00	μg/L	1		· =	1 11453
1,1-Dichtoroethane	ND	1.00	µg/L	1			
1,1-Dichloreethene	ND	1.00	μg/L	1			
1,2-Dichloroethane	ND	1.00	μg/L	1			
1,2-Dichloropropane	ND	1.00	μg/L	1			
Benzene	ND	1.00	μg/L	1			
Carbon tetrachloride	ND	1.00	μg/L,	1			
Chloroethane	ND	1.00	μg/L	1			
Chlaroform	, ND	1.00	μg/L	1			
cis-1,2-Dichloroethene	МĐ	1.00	μg/L	1			
Ethylbenzene	ND	1.00	μg/L	1			
n,p-Xylene	ND	1.00	μg/L	1			
Methylene chloride	ND	2.00	μg/L	1			
Vaphthalene	ND	1.00	μg/L	1			•
-Xylene	ND	1.00	μg/L	1			
Tetrachlorcethene	ND	1.00	μg/L				
oluene	ND	1.00	μg/L	1			
rans-1,2-Dichloroethene	ND	1.00	μg/L				
richloroethene	ND	1.00	μg/L	1			
Vinyl chloride	ND	1.00	μg/L	1			
Surr.1,2-Dichloroethane-d4	109	70 - 130	%REC	1	11/30/2004 5:52:00 PM PE	ERRY 041130A	- RMJ
Surc4-Bromofluorobenzene	108	70 - 130	%REC	1		5 *** 150/4	าเพม
Surr:Toluene-d8	112	70 - 130	%REC	1			

Definitions:

NP - Petroleum Pattern is not present

^{• -} Recovery outside QC limits

DF - Dilution Factor

H - Value Exceeds Maximum Contaminant Level

N - Single Column Analysis

B - Analyte found in Method blank

DNI - Did not Ignite

I - Estimated value

NC - Not Calculated P - Post Spike Recovery outside limits

D - Diluted due to maxtrix or extended target compounds

E - Result above quantitation limit (high standard or ICP linear range).

M - Matrix Spike Recovery outside finits

ND - Not Detected at the Reporting Limit

R - RPO outside recovery Emits



Allarytical octypes Center

International Specialists in Environmental Analysis

4493 Walden Avenue

and environment, inc. Lancaster, New York 14086

Laboratory Resums

NYS ELAP ID#:

10486

Phone: (716) 685-8080

Client:

Parsons Engineering Science, Inc.

Client Sample ID: TRIP BLANK

Lab Order: 0411354

Project:

Tooele RCRA Phase II

Alt. Client ID:

Collection Date: 11/23/2004 7:00:00 A % Moist:

Lab ID: 0411354-05A

Sample Type: SAMP

Matrix: Water

Test Code: C_8260B_5030B_LL_W_018

LOW LEVEL VOCS BY METHOD 8260B

Method: SW8260B

Prep Method: SW50308 11

Analyte	Result	Q	RL	Units	DF	Date Analyzed	Run Batch ID	Analyst
1,1,1-Trichloroethane	ND		1.00	μg/L	1	11/30/2004 3:46:00 PM	PERRY_041130A	RMJ
1,1,2-Trichloroethane	ND		1.00	μg/L	1			1 1.140
1,1-Dichloroethane	ND		1.00	μg/L	1			
1,1-Dichtoroethene	ND		1.00	μg/L	1			
1,2-Dichloroethane	ND		1.00	μg/L	1			
1,2-Dichloropropane	NO		1.00	µg/L	1			
Benzene	ND		1.00	μg/L	1			
Carbon tetrachloride	ND		1.00	μg/L	1			
Chloroethane	ND		1.00	μg/L	1			
Chlereform	'ND		1.00	µg/L	1 1			
cis-1,2-Dichloroethene	ND		1.00	μg/L	1			
Ethylbenzene	ND		1.00	μg/L	1			
m,p-Xylene	ND		1.00	μg/L	1			
Methylene chloride	0.207	J	2.00	μg/L	i			
Naphthalene	ND		1.00	μg/L	1			
o-Xylene	ND		1.00	μg/L	1			
Tetrachloroethene	ND		1.90	μg/L	1			
Foluene	0.262	J	1.00	μg/L	1	•		
rans-1,2-Dichloroethene	ND		1.00	μg/L	1			
Frichloroethene	ND		1.00	μg/L	1			
/inyl chloride	ND		1.00	μg/L	1			
Surc1,2-Dichloroethane-d4	115		70 - 130	%REC	1	11/30/2004 3:46:00 PM PE	ERRY 041130A	RMJ
Surr:4-Bromofluorobenzene	108		70 - 130	%REC	1			run,
SumToluana-d8	110		70 - 130	%REC	1			

Definitions:

^{• -} Recovery outside QC limits

DF - Dilution Factor

H - Value Exceeds Maximum Contaminant Level

N - Single Column Analysis

NP - Petroleum Pattern is not present

B - Analyte found in Method blank

DNI - Did not Ignite

J - Estimated value

NC - Not Calculeted P - Post Spike Recovery outside limits

 $[\]boldsymbol{\Theta} \cdot \boldsymbol{\mathsf{District}}$ due to maximix or extended target compounds

^{6 -} Result above quantitation limit (high stendard or ICP linear range).

M - Matrix Spike Recovery outside firms

ND - Not Detected at the Reporting Limit

R - RPD outside recovery limits

AUTOMATED DATA REVIEW SUMMARY

Facility:

SWMU 58

Event:

2004 10 SWMU 58 Vertical Profile Borings

Contract:

9T9H213C

Sample Delivery Group:

0411354

Field Contractor:

Parsons Engineering Science, Salt Lake City

Laboratory Contractor:

Ecology and Environment, Inc., Lancaster, NY

Data Review Contractor:

Synectics, Sacramento, CA

Guidance Document:

Final Phase II RCRA Facility Investigation SWMU-58 Workplan,

December 2003

Analytical Method

Normal Samples

Field QC Samples

SW8260B

3

2

This report assesses the analytical data quality associated with the analyses listed on the preceding cover page. This assessment has been made through a combination of automated data review (ADR) and supplemental manual review, the details of which are described below. The approach taken in the review of this data set is consistent with the requirements contained in Final Phase II RCRA Facility Investigation SWMU-58 Workplan, December 2003 to the extent possible. Where definitive guidance is not provided, data has been evaluated in a conservative manner using professional judgment. In cases where two qualifiers are listed as an action, such as "J/UJ", the first qualifier applies to positive results, and the second to non-detect results.

Samples were collected by Parsons Engineering Science, Salt Lake City; analyses were performed by Ecology and Environment, Inc., Lancaster, NY and were reported under sample delivery group (SDG) 0411354. Results have been evaluated electronically using electronic data deliverables (EDDs) provided by the laboratory. The laboratory data summary forms (hard copy) have been reviewed during this effort and compared to the automated review output. Findings based on the automated data submission and manual data verification processes are detailed in the ADR narrative. The following quality control elements were evaluated during this review effort:

Technical Holding Times
Continuing Calibration Verification
Method Blank Contamination
Field Blank Contamination
Blank Spike Accuracy
Blank Spike Precision
Matrix Spike Accuracy
Matrix Spike Precision
Surrogate Recovery
Laboratory Duplicate Precision
Field Duplicate Precision

A minimum of ten percent of sample and QC results were manually evaluated for compliance with project specific requirements and consistency with hard copy results. The following reports were generated during the evaluation of this data set and are presented as attachments to this report as applicable.

Data Submission Warnings – Warnings encountered during the data submission process are evaluated and their affect on data quality is discussed in the narrative.

Batch – The analytical batch report is reviewed for completeness and compliance with project specific requirements. Incomplete or non-compliant run sequences are identified and their impact on data quality are discussed in the narrative.

QC Outlier – Results exceeding the evaluation criteria are reviewed for compliance with project requirements and a minimum of ten percent of the non-compliant QC values reported electronically are verified for consistency with hard-copy values.

Qualified Results – Qualified results are evaluated for compliance with project requirements and ten percent of qualified results are verified for consistency with the QC Outlier Report.

Field Duplicate – Field duplicate comparison results are evaluated for compliance with project requirements and ten percent of values reported are verified for consistency with the hard-copy data.

Rejected Results – All rejected results are evaluated for compliance with project requirements. The reason for rejection of the data is verified against hard copy data.

Analytical deficiencies, project non-compliance issues and inconsistencies with hard copy results observed during ADR evaluation process and their impact on data quality are summarized in the ADR narrative.

ISSS-539-01 2/3

Released by		 , <u>, , , , , , , , , , , , , , , , , , </u>

Reason and Comment Codes

<u>Code</u>	<u>Definition</u>
C1	Diluted Out
C2	Flag Parent Only
C2S	Flag Parent (Soil); Batch (Water)
C3	No Action
C4	No QC Outliers
C5	One or both values <5x RL
C6	Recalculated Value
C7	Material Blanks
C8	Spike Insignificant
C9	No Flags; set to ND by method/cal. blank

Definition

Reasons

<u>Code</u>

	<u>e ommen</u>
Α	Serial dilution
В	Calibration Blank - Negative
	Negative Blank
B1	Blank
B2	Calibration Blank
С	Continuing Calibration Verification
	Continuing Calibration Verification RRF
D	BS RPD
	Field Duplicate RPD
D1	Lab Replicate RPD
D2	MS RPD
E	Exceeds LinearCalibration Range
F	Hydrocarbon pattern does not match standard
G	Initial Calibration RRF
	Initial Calibration RSD
Н	Test Hold Time
	Prep Hold Time
1	Internal standard
K1	Equip Blank
K2	Field Blank
K3	Trip Blank
L	LCS Recovery
M	MS Recovery
N	Blank - No Action
0	Interference check sample
P	Column RPD
Q	Material Blank
S .	Surrogate
T	Receipt Temperature
TI	Tentatively Identified Compound
TR	Trace Level Detect
W	Column breakdown (pesticides)
X	Raised reporting limit
Υ	Analyte not confirmed on second column

ADR CASE NARRATIVE

Laboratory ID: 0411354

Prior to loading and processing data, modifications to the project setup may be requested by the laboratory and/or contractor, and approved by the client. These modifications allow the loading of data that was not in complete agreement with the project guidance document; in some cases, variances to the project document may be in process, in others, the changes are required to accept data that had not been generated in compliance with the project guidance document. All project setup modifications are listed below:

There were no project setup modifications associated with this sample delivery group.

Chemistry Data Quality

It was found that all field sample reporting limits (RL) reported by the lab did not meet the project specified RLs required in the project setup.

Data Verification

The data verification process includes a manual review of information on the chains of custody and laboratory case narratives, a check of all rejected results and a minimum of 10 percent of sample and QC results for consistency with hard copy reports, and a cursory review of all reports generated during the automated review process. The following comments are associated with the verification process:

There were no data verification findings associated with this sample delivery group that require discussion beyond that summarized in the attached reports.

All of the reports utilized during the data verification process are provided as attachments to this report.

Batch Report

Facility:

SWMU 58

Lab:

ECEN

Filename:

0411354

Status:

Certified - 12/16/2004

User:

EvinMcKinney

Test Method:

SW8260B

Prep Method:

SW5030

Leach Method:

NONE

Test Batch	Prep Batch	Leach Batch	Location	Matrix	Field Sample ID	Lab Sample ID	Test Date and Time	Sample Type
PERY41130A	0411304p1r	NA	LABQC	WQ		CCV1078348	11/30/2004 12:55:00P	CV1
	0411304p1r	NA	LABQC	WQ		LCS1845211	11/30/2004 2:15:00PM	BS1
	0411304p1r	NA	LABQC	WQ	·	MB1845211	11/30/2004 2:46:00PM	L81
	0411304p1r	NA	FIELDQC	WQ	TRIP BLANK	0411354-05	11/30/2004 3:46:00PM	TB1
	0411304p1r	NA	D-12	WG	D-12GW001	0411354-0 1	11/30/2004 4:18:00PM	N1
	0411304p1r	NA	D-13	WG	D-13GW001	0411354-02	11/30/2004 4:49:00PN	N1
•	0411304p1r	NA	D-13	WG	D-13FD001	0411354-03	11/30/2004 5:21:00PM	FD1
	0411304p1r	NA	D-16	WG	D-16GW001	0411354-04	11/30/2004 5:52:00PM	N1
	0411304p1r	NΑ	D-16	. WG	D-16GW001	0411354-04	11/30/2004 7:01:00PN	MS1
	0411304p1r	NA	D-16	WG	D-16GW001	0411354-04	11/30/2004 7:32:00PM	SD1

Detected Results

Facility:

SWMU 58

Event:

2004 10 SWMU 58 Vertical Profile Borings

Reference:

ISSS-539-01

SDG: 0411354

Volatile Organic Compounds by Capillary GC/MS

Test/Leach	<u>Matrix</u>	Field Sample ID	<u>Type</u>	<u>Analyte</u>	<u>RL</u>	Lab Result	Qualified Result	<u>Units</u>	Reason
SW8260B/NONE	WG	D-13FD001	FD	Chloroform	1.0	0.20 J	0.20 J	UG/L	TR
SW8260B/NONE	WG	D-13GW001	N	Chloroform	1.0	0.19 J	0.19 J	UG/L	TR
SW8260B/NONE	WQ	TRIP BLANK	TB	Methylene Chloride	2.0	0.21 J	0.21 J	UG/L	TR
SW8260B/NONE	WQ	TRIP BLANK	TB	Toluene	1.0	0.26 J	0.26 J	UG/L	TR

QC Outliers

Facility:

SWMU 58

Event:

2004 10 SWMU 58 Vertical Profile Borings 9T9H213C

Reference:

SDG 0411354

						Warning	Control	
Test/Leach	QCElement	<u>Sample</u>	Type Dil'n	Analyte	Result Units	<u>Limits</u>	Limits Qualifier Rea	son Cmnt.
SW8260B/NONE	Trip Blk. Cont.	TRIP BLANK	TB1 1.00	Methylene Chloride	0.21 UG/L	< 0.128	< 2 U / None K3	
SW82608/NONE	Trip Blk. Cont.	TRIP BLANK	TB1 1.00	Toluene	0.26 UG/L	< 0.119	< 1 U/None K3	

Qualified Results

Facility:

SWMU 58

Event:

2004 10 SWMU 58 Vertical Profile Borings

Reference:

ISSS-539-01

SDG: 0411354

Volatile Organic Compounds by Capillary GC/MS

Test/Leach	Matrix	Field Sample ID	Type	<u>Analyte</u>	<u>RL</u>	Lab Result	Qualified Result	<u>Units</u>	Reason
SW8260B/NONE	WG	D-13FD001	FÐ	Chloroform	1.0	0.20 J	0.20 J	UG/L	TR
SW8260B/NONE	WG	D-13GW001	N	Chloroform	1.0	0.19 J	0.19 J	UG/L	TR
SW8260B/NONE	WQ	TRIP BLANK	тв	Methylene Chloride	2.0	0.21 J	0.21 J	UG/L	TR
SW8260B/NONE	WQ	TRIP BLANK	TB	Toluene	1.0	0.26 J	0.26 J	UG/L	TR

DATA MANAGEMENT NARRATIVE

Laboratory ID: 0411354

Data Submission

The data submission process incorporates a series of stored procedures designed to identify valid value (VVL), logical (LE), and project specific errors (PSE) in electronic data deliverables (EDD). Automated data review (ADR) is most efficient when data generators correct all errors. Dependent primarily upon the electronic reporting capabilities of the data generator, the severity of the logical and project specific errors listed below have been reduced to warnings. A warning log is generated with each data submission and is presented as an attachment to this report. A brief explanation of each error encountered for this data set and the potential impact on data quality is summarized below.

Project Specific Error (PSE) spPSE01L_Invalid_Units_QC

This PSE occurs when laboratory quality control samples are reported with units of percent as opposed to true values. This inconsistency does not affect data quality, unless the submittal is scheduled for delivery to the AFCEE in accordance with the ERPIMS 4.0 specification. Automated data review can be performed for laboratory QC when units are reported in percent or in concentration units. However, to avoid this warning on future submittals, the laboratory would need to report these values in units of concentration (i.e., ug/L).

2. Logical Error (LE) spLE01_QAPPFLAGS_F

This LE warning occurs when there are positive results less than the RL and associated QAPPFLAGS are not "F". This requirement is only necessary if the project is an AFCEE project or if the data is to be submitted to ERPIMS. To avoid this warning in the future, apply QAPPFLAGS of "F" whenever the detected result is less than the RL.

A detailed description of the stored procedures utilized during the data submission process is provided as an attachment to this report (Submission Warnings).

Submission Warnings

Facility:

SWMU 58

Data Generator:

ECEN

File Name:

W:\2004\0411354\0411354.LB1

PSE

Query Name	Finding	Record Count
spPSE01L_Invalid_Units_QC	ANMCODE is SW8260B; LCHMETH is NONE; Matrix Class is W; SACODE/PRCCODE is CV/ORG; UNITS is PERCENT	21
	ANMCODE is SW8260B; LCHMETH is NONE; Matrix Class is W; SACODE/PRCCODE is MS/ORG; UNITS is PERCENT	4
	ANMCODE is SW8260B; LCHMETH is NONE; Matrix Class is W; SACODE/PROCODE is MS/STD; UNITS is PERCENT	3
	ANMCODE is SW82608; LCHMETH is NONE; Matrix Class is W; SACODE/PROCODE is BS/ORG; UNITS is PERCENT	4
	ANMCODE is SW8260B; LCHMETH is NONE; Matrix Class is W; SACODE/PRCCODE is SD/STD; UNITS is PERCENT	3
	ANMCODE is SW8260B; LCHMETH is NONE; Matrix Class is W; SACODE/PROCODE is BS/STD; UNITS is PERCENT	3
	ANMCODE is SW8260B; LCHMETH is NONE; Matrix Class is W; SACODE/PRCCODE is N/STD; UNITS is PERCENT	9
	ANMCODE is SW82608; LCHMETH is NONE; Matrix Class is W; SACODE/PRCCODE is SD/ORG; UNITS is PERCENT	4
	ANMCODE is SW82608; LCHMETH is NONE; Matrix Class is W; SACODE/PRCCODE is LB/STD; UNITS is PERCENT	3
	ANMCODE is SW8260B; LCHMETH is NONE; Matrix Class is W; SACODE/PRCCODE is CV/STD; UNITS is PERCENT	3
	ANMCODE is SW8260B; LCHMETH is NONE; Matrix Class is W; SACODE/PRCCODE is TB/STD; UNITS is PERCENT	3
	ANMCODE is SW8260B; LCHMETH is NONE; Matrix Class is W; SACODE/PRCCODE is FD/STD; UNITS is PERCENT	3
WL		
Query Name	<u>Finding</u>	Record Count
spLE01_QAPPFLAG\$_F	PARVQ is TR; PARVAL is 0.2620; RL is 1.0000; QAPPFLAGS is J	1

PARVQ is TR; PARVAL is 0.1930; RL is 1.0000; QAPPFLAGS is J

PARVQ is TR; PARVAL is 0.2070; RL is 2.0000; QAPPFLAGS is J PARVQ is TR; PARVAL is 0.1950; RL is 1.0000; QAPPFLAGS is J

January 04, 2005 11:27:38AM

1

1

Submission Warnings

SWMU 58

Facility: Data Generator:

ECEN

File Name:

W:\2004\0411354\0411354.LB1

Total Record Count:

189


Error Count:

0

Warning Count:

67

January 04, 2005 11:27:38AM





406 West South Jordan Parkway, Suite 300 . South Jordan, Utah 84095 . (801) 572-5999 . Fax (801) 572-9069

Memorandum

To: Dean Reynolds, TEAD; Larry McFarland, TEAD

Copy: Maryellen Mackenzie, USACE; Carl Cole, USACE; Doug Mackenzie,

USACE; Richard Jirik, Parsons

From: Jan Barbas, Parsons; Jeff Bigelow, Parsons

Date: Monday October 18, 2004

Subject: TEAD SWMU-58 RFI - Waste Management

This letter is to recommend disposition of the 18 drums summarized in Table One, attached. The waste was generated in association with the drilling of well D-12.

Eighteen drum of saturated soil cutting waste was generated and one sample was taken for each five drums. Therefore four samples were taken and labeled IDW04 – IDW07. Samples were analyzed for TCLP VOCs. Analysis was conducted by Ecology and Environment, Inc. Lancaster NY, a Utah Certified laboratory.

Results have been received as data packages and electronic data deliverables. Parsons has reviewed the data and found QC to be acceptable. Analytical results and case narrative are attached in portable document format.

Listed Wastes Analysis:

Tetrachloroethylene (PCE) and Benzene were detected in two of the four samples. PCE is not generally present in the northeast boundary plume. Although PCE is generally nondetect in C-33, a few sporadic trace (<1 ug/L) detections have occurred over the years. PCE has not been detected in C-26 or in the D-series wells. PCE does not appear to be a plume constituent. Benzene has not been detected in C-33, C-26 or in the D-series wells, and is not a plume constituent.

Therefore there is no reason to associate the detections of PCE or Benzene with a known source or any activity of TEAD. The source of PCE and Benzene in these samples is unknown.

Characteristic Wastes Analysis:

The waste is known to be primarily soil. Therefore generator's reasonable knowledge may be used to exclude the characteristics of ignitability, reactivity and corrosivity.

No analytes were detected in excess of TCLP limits (PCE and Benzene were detected below TCLP limits). Therefore no characteristic waste codes (40 CFR Part 261.24) should be applied.

Disposition:

Parsons recommends that this waste be returned to the site for disposal on the ground surface.

Parsons will arrange to dispose of the waste per your written instructions.



analytical services center

International Specialists in Environmental Analysis



4493 Walden Avenue, Lancaster, New York 14086 Tel: 716/685-8080, 800/327-6534 • Fax: 716/685-0852 • Email: asc@ene.com

October 13, 2004

Jan Barbas
Parsons Engineering Science, Inc.
406 W. South Jordan Pkwy.
Suite 300
South Jordan, Utah 840953944

RE: Tooele RCRA Phase II Work Order No.: 0409250

Dear Jan Barbas,

Analytical Services Center received 4 samples on Thursday, September 23, 2004 for the analyses presented in the following report.

The ASC certifies that the test results in this report meet all requirements of NELAC for which it holds certification except as noted in this narrative and/or as flagged in the report.

The ASC is accredited in the Fields of Testing Potable water (SDWA), Solid and Chemical Materials (Solid Hazardous Wastes, RCRA), Water (CWA and other non-potable water) and Air and Emissions. Its primary accrediting authorities are New York State Department of Health and Florida Department of Health. The particular analytes/methods certified may be ascertained by requesting the laboratory's current certificates from your laboratory Project Manager.

You will receive an invoice under separate cover.

E & E will retain the samples addressed in this report for 30 days, unless otherwise instructed by the client. If additional storage is requested, the storage fee is \$1.00 per sample container per month, to accrue until the client authorizes sample destruction.

This report is not to be reproduced, except in full, without the written approval of the laboratory.

Sincerely,

Project Manager

CC:

Enclosures as noted



Analytical Services Center
International Specialists in Environmental Analysis
Lancaster New York 14086

Fax: (716) 685-0852

Laboratory Results

NYS ELAP ID#:

10486

CLIENT:

Parsons Engineering Science, Inc.

Project:

Tooele RCRA Phase II

Lab Order:

0409250

Date Received: 9/23/2004 **Work Order Sample Summary**

	•			_
Lab Sample ID	Client Sample ID	Alt. Client Id	Collection Date	
0409250-01A	IDW04		9/15/2004 9:00:00 AM	
0409250-01B	IDW04		9/15/2004 9:00:00 AM	
0409250-02A	IDW05		9/15/2004 2:00:00 PM	
0409250-02B	IDW05		9/15/2004 2:00:00 PM	
0409250-03A	IDW06		9/20/2004 9:00:00 AM	
0409250-03B	IDW06		9/20/2004 9:00:00 AM	
0409250-04A	IDW07		9/21/2004 9:00:00 AM	
0409250-04B	IDW07		9/21/2004 9:00:00 AM	
	• •			



Analytical Services Center

International Specialists in Environmental Analysis

Lancaster New York 14086

Phone: (716) 685-8080

Fax: (716) 685-0852

Laboratory Results

Phone:

NYS ELAP ID#:

(716) 685-8080

10486

Order:

0409250

nt:

Parsons Engineering Science, Inc.

ject:

Tooele RCRA Phase II

DATES SUMMARY REPORT

		· · · · · · · · · · · · · · · · · · ·	·····	······································	·	<u> </u>				
3) Sample ID (CLIENT)	Matrix	Test Name	Collection Date	Received Date	HT (Days) / HT Expire	Analyzed* - Analysis/Bato	hID Туре	DF	#Analytes	F
250-01B IDW04	Soil	TCLP Ext for VOCs by M 1311	9/15/2004 9:00:00 AM	9/23/2004 10:45:00 AM	14:C 9/29/2004 9:00:00 AM	9/28/2004 9:14:40 AM 20040	3814 NA	NA	NA	
		TCLP Volatile Organic Compounds by Method 8260B			14:T 10/14/2004 5:02:29 PM	10/6/2004 6:01:00 PM 1938	141 SAMP	' 10	10	
3) Sample ID (CLIENT)	Matrix	Test Name	Collection Date	Received Date	HT (Days) / HT Expire	Analyzed* - Analysis/Batc	hID Type	DF	#Analytes	F
250-028 IDW05	Soil	TCLP Ext for VOCs by M 1311	9/15/2004 2:00:00 PM	9/23/2004 10:45:00 AN	1 14:C 9/29/2004 2:00:00 PM	9/28/2004 9:14:40 AM 20040	3814 NA	ŅΑ	ŅΑ	_
		TCLP Valatile Organic Compounds by Method 82606			14:T 10/14/2004 5:02:29 PM	10/6/2004 6:31:00 PM 1038	142 SAMF	' 10	10 .	
3) Sample ID (CLIENT)	Matrix	Test Name	Collection Date	Received Date	HT (Days) / HT Expire	Analyzed* - Analysis/Bate	ыл Туре	DF	#Analytes	F
250-03B IDW06	Sall	TCLP Ext for VOCs by M 1311	9/20/2004 9:00:00 AM	9/23/2004 10:45:00 AN	14:C 10/4/2004 9:00:00 AM	9/28/2004 9:14:40 AM 20040	3814 NA	NA	NA	_
		TCLP Volatile Organic Compounds by Method 8260B			14:T 10/14/2004 5:02:29 PM	19/6/2004 7:02:00 PM 1038	143 SAMF	2 10	10	
3) Sample ID (CLIENT)	Matrix	Test Name	Collection Date	Received Date	HT (Days) / HT Expire	Analyzed* - Analysis/Bate	bID Type	DF	#Analytes	F
250-04B IDW07	Soll	TCLP Ext for VOCs by M 1311	9/21/2004 9:00:00 AM	9/23/2004 10:45:00 AM	1 14:C 10/5/2004 9:00:00 AM	9/28/2004 9:14:40 AM 20040	3814 NA	NA	NA	_
		TCLP Volatile Organic Compounds by Method 8260B			14:T 10/14/2004 5:02:29 PM	10/6/2004 7:32:00 PM 1038	144 SAMP	10	10	ı

irom: C-Collection / R- Receipt(VTSR) / P-Prep / T-TCLP Prep

nalyzed" reflects the analysis date and time or injection time for analytical tests. For preparation tests "Analyzed" reflects the start of the preparation except when "AFCEE criteria used"; flag indicates date time of completion of the preparation.

TCLP/SPLP Extractions and subsequent preparation tests..."Analyzed" reflects the date of TCLP/SPLP Extraction/preparation. For Re-extracted (RE) samples: Preparation tests completed dates reflects extraction from the original sample leacheste unless an "RE" Sample exisits for the extraction (tumble) test.



Analytical Services Center

International Specialists in Environmental Analysis

Lancaster New York 14086

ecology and environment, inc. Phone: (716) 685-8080

Fax: (716) 685-0852

Laboratory Results

NYS ELAP ID#:

10486

Client:

Parsons Engineering Science, Inc.

Project:

Tooele RCRA Phase II

Work Order:

0409250

Method References

GCMS Volatiles

TCLP VOCs by Method 8260B

Test Methods for Evaluating Solid Waste: Physical/Chemical Methods. 3rd ed. 1986. Volumes.1A, 1B, 1C & Volume 2. (Includes all Updates). U.S. Environmental Protection Agency, Office of Solid Waste and Emergency Response.

SAMPLE RECEIPT RECORDS

age	
σ	

Parsons Point of Conta Jan Barbas 406 W. South Jordan Pan av **CHAIN OF CUSTODY** Project Name: Topele industrial Area contractor: Parsons - SLC **PARSONS** Suite 300 Project Manager: TEAD Ed Staes hstallation: South Jordan, Utah 84095. 525 COC ID: (801) 572-5999 FAX (801) 572-90tg Sample Coordinator: Jeff Bigelow Shallow Soil Sampling Sample Program:

iste (C) L Lecation (C) La Sample (C)	Metroc	Type Sa	mpi vo Loggaje	Logime Logged By	Beg Depin	End Depth Total Conts
IDW IDW04 IDW04	SO G	N	1 9/15/04	01:00 JJB	0	0 4
EATAYSIS LITTLE BEAT TO BE SEEN T	Cooler No Com	AE Lot		Remarks:		
VOCM ECEN	IDWOI 4			Ipu	Sample	for drains

PARSIVZ0425701 PARSIVZ0425901-04

Relinquished by (Signature)	Date/Time	Received by (Signature)	Date/Time
Low White	9(22/04 /1:30		
DEUD 9-23-0	4 10105		

Parsons Point of Contact: Jan Barbas **CHAIN OF CUSTODY** Project Name: Topele Industrial Area Contractor: Parsons - SLC 406 W. South Jordan Parkway Suite 300 **PARSONS** Project Manager: Ed Staes Installation: TEAD South Jordan, Utah 84095 (801) 572-5999 FAX (801) 572-9069 COC ID: Shallow Soil Sampling 526 Sample Coordinator: Jeff Bigelow Sample Program:

Site D	Location ID	Sample ID	Matrix	Method	Туре	Sample No.	Log Oate	Log Time	Logged By	Beg Depin	End. Depth	Total Conts
IDW	IDW05	1 D W05	so	G	N	1	9/15/04	14:00	JJB	0	0	4/
	Analysis	Lab M	Cooler	No Conte	AB Lot	EBIO	TELO	Remarks:				
VOCM		ECEN	IDWO!	4	 -	_	-	T	nw s	amale .	for dry	ac.

PARSINZO425408-07 PARSINZO426401-02

Relinquished by (Signature)	Date/Time	Received by (Signature)	Date/Time
Jan Mys	9/22/04 11:30		
skilled	9-23-04 10:2-		

Ø
Ω
ወ
∞

Parsons Point of Contact: Jan Barbas Parsons - SLC HAIN OF CUSTODY Tocele Industrial Area Project Name: Contractor: 406 W. South Jordan Parkway Suite 300 **PARSONS** Ed Staes TEAD Project Manager: Installation: South Jordan, Utah 84095 (801) 572-5999 FAX (801) 572-9069 COC ID: 528 Shallow Soil Sampling Sample Program: Sample Coordinator: Jeff Bigelow

Site D	Location ID	Sample ID	Matrix	Memod	Туре	Sample No.	Log Date	Log Time Logged E	ly Beg Debin	End Depin	Total Conts
IDW	IDW06	IDW06	so	G	N	1	9/20/04	09:00 JJB	0	0	4
	Analysis	Lab	Cooler	No. Conts	AB Lot	EB Lot	TBLot	Remarks:			
VOCM		ECEN	IDWOI	4			~		, ,		

I'm sample for drams:

PARSNZ0426403-06 PARSNZ0426501

Relinquished by (Signature)	Date/Time	Received by (Signature)	Date/Time		
he he	9/22/04 11:30				
bhillo	8-23-04 10:25				

യ
Ω
Ð
9

Parsons Point of Contact: Jan Barbas Project Name: Parsons - SLC **CHAIN OF CUSTODY** Tooele Industrial Area Contractor: 406 W. South Jordan Parkway Suite 300 PARSONS. Project Manager: Ed Staes TEAD Installation: South Jordan, Utah 84095 (801) 572-5999 FAX (801) 572-9069 COC ID: 529 Shallow Soll Sampling Jeff Bigelow Sample Program: Sample Coordinator:

Site D	Locationic	Sample D	Matrix	Method	Type	Sample No.	Log Date	Log Time	Logged By	Beg (Depth	End Depth	Total Conts.
IDW	IDW07	IDW07	so	G	N	1	9/21/04	09:00	JJB	0	0	4
	Analysis	ĽáK	Cooler	No Conta	AB Lot	EB Lot	TB Lot	Remarks:				
VOCM		ECEN	IDNO	4/	 .	4.	•		· - : a			i

IDW sample for chruns:

PARSINZ 04 26502-03

Relinguished by (Signature)	Date/Time	Received by (Signature)	Date/Time
We hall	9/12/04 11:30		
prulle	9-23-04 10:24		
<u> </u>			
			"



Cooler Receipt Form

No. of Packages:		Date Received:	9/22/14			
Package Receipt No.:	11 K2 C	Project or Site Name:	Talle			
Client:	4528 Possons		10000			
	110301					
A. Peliminary Exa	mination and Receipt Phase	<u> </u>		Gir	cle Oi	ne l
	a airbill or packing slip?			Yes	No	NA
Circle carrier here	e and print airbill number below: Fed Ex	Airborne Client Other_				7100000
Shipped as high	hazard or dangerous goods?			Yes	No	NA
2. Did cooler(s) have cus	stody seals?			Yes	(B	NA
Were custody seals ur	nbroken and intact on receipt?			Yes	No ((AM
 Were custody seals do 	ated and signed?	-	 	Yes	No	(MA)
How was package sec	cured? D Not secured AFiberglass	Таре 🗆				
	<u> </u>					
B. Unpacking Phas	se				··· · · ·	
-	4. a_2 3-04 Cooler(s) op	sened by: Drelle	0			
6. Date cooler(s) opened	u. 1	(Signature)				
	lank vial included inside cooler(s)?		· _ · · · · · · · · · · · · · · · · · ·	Yes	No	NA
	ease Record Temperature Vial or Cooler	•		-	Server	Sus <u>ers</u> ne
	Temp G Airbill No.	Hemp, C	Authil No.		emp:	#CHI
8457 2785 4314	4.0					
						-
		*If temperature is outs	ide of acceptable ran	ne prena	ma a D	M
Thermometer No.: 23	Correction Factor: 0.0	Notification form indic				
8. Were the C-O-C forms				Yes	No	NA
C-O-C forms numbers						
1	material used in cooler(s)?	• 6		Yes	No	NA
Type of material:	□ Vermiculite □ Bubble Wrap	① Other				
L	ed, what was the means (type ice) of cooling	used: (Wet) Dry De	Nue □ Other			NA
<u> </u>	ealed in separate plastic bags?			Yes	No	NA .
	ve unbroken and in good condition?			Yes	No	NA
13. Interim storage area i	ir not logged:	00	0			
In: Date <u>9-2</u>	13-04 Time 11:30	Signature DKull	<u>ی</u>	 .		
Out: Date	Time	Signature	· .	:		
			· · · · · ·			
		<u> </u>				
C. Login Phase Samples Logged in By Sign	pature: All	Date:	alia late			
<u>L</u>	pels complete (e.g. date, time preserved)?	OSIC.	7/27/07	<i>(</i> *9	No	NA
t	filled out groperly in black ink and signed?			<i>109</i>	No	NA NA
Į.	gree with containers received?			129	No	NA NA
	tainers used for the tests requested?			(E)	No	NA.
	servatives listed on the sample labels?			15	No	NA
	ple volume sent for the tests requested?	·		(B)	No	NA

20. Were all volatile samples received without headspace?

^{*}Prepare a PM Notification form (F-051).

RESULTS SUMMARY



Analytical Services Center

International Specialists in Environmental Analysis

4493 Walden Avenue

Lancaster, New York 14086

Laboratory Kesuns

NYS ELAP ID#: 10486

(716) 685-8080 Phone:

Client: Parsons Engineering Science, Inc.

Lab Order: 0409250

TCLP VOLATILE ORGANIC COMPOUNDS BY METHOD 8260B

Tooele RCRA Phase II

Collection Date: 9/15/2004 9:00:00 AM % Moist:

Lab ID: 0409250-01B

Project:

Sample Type: SAMP

Matrix: Soil

Test Code: 1_1311_8260B_L

Client Sample ID: IDW04

Alt. Client ID:

Method: SW8260B Prep Method: SW1311

Analyte	Result	Q	RL	Units	DF	Date Analyzed	Run Batch ID	Analys
1,1-Dichloroethene	NĐ	•	0.0500	mg/L	10	10/6/2004 6:01:00 PM	ROBERT_041006A	RMJ
1,2-Dichloroethane	ND		0.0500	mg/L	10			
2-Butanone	ND		0.100	mg/L	10			
Benzene	0.00741	j	0.0500	mg/L	10			
Carbon tetrachloride	ND		0.0500	mg/L	10		•	
Chlorobenzene	ND		0.0500	mg/L	10			
Chloroform	ND:		0.0500	mg/L	10			
Tetrachloroethene	0.0105	J	0.0500	mg/L	10			
Trichioroethene	ND		0.0500	mg/L	10			
Vinyl chloride	, ND		0.100	mg/L	10			
Surr:1,2-Dichloroethane-d4	103 -		82 - 124	%REC	10	10/6/2004 6:01:00 PM F	ROBERT_041006A	RMJ
Surr:4-Bromofluerobenzene	111		87 - 115	%REC	10			
Surr:Toluene-d8	108		85 - 115	%REC	10			

Definitions:

* - Recovery outside QC limits

DF - Dilution Factor

H - Value Exceeds Maximum Contaminant Level

N - Single Column Analysis

NP - Petroleum Partero is not present

B - Analyte found in Method blank

DNI - Did not fgaite

J - Estimated value

NC - Not Calculated P - Post Spike Recovery outside fimits

M - Matrix Spike Recovery outside firsts

D - Diluted due to maxisix or extended target compounds

E - Result above quantitation limit (high standard or ICP linear range).

ND - Not Detected at the Reporting Limit



Alialytical per vices center

International Specialists in Environmental Analysis

4493 Walden Avenue

TCLP VOLATILE ORGANIC COMPOUNDS BY METHOD 8260B

Lancaster, New York 14086

Laboratory Nesuits

NYS ELAP ID#: 10486

(716) 685-8080

Pren Method: SW1311

Client: Parsons Engineering Science, Inc.

Lab Order: 0409250

Tooele RCRA Phase II

Client Sample ID: IDW05

Method: SW8260B

Alt. Client ID:

Collection Date: 9/15/2004 2:00:00 PM % Moist:

Lab ID: 0409250-02B

Project:

Sample Type: SAMP

Matrix: Soil

Test Code: 1_1311_8260B_L

TOLI TOLATICL ORGANIO OC	ALL COMPS DI	MICT.	JD 0200D	me	uiou	31102000	riep meniou: 3%	1311
Analyte	Result	Q	RL	Units	DF	Date Analyzed	Run Batch ID	Analyst
1,1-Dichloroethene	ND		0.0500	mg/L	10	10/6/2004 6:31:00 PM	ROBERT_041006A	RMJ
1,2-Dichloroethane	ND		0.0500	mg/L	10			
2-Butanone	ND		0.100	mg/L	10			
Benzene	ND		0.0500	mg/L	10			
Carbon tetrachloride	ND		0.0500	mg/L	10			
Chlorobenzene	ND		0.0500	mg/L	10			
Chloroform	ND		0.0500	mg/L	10		•	
Tetrachloroethene	0.00603	J	0.0500	mg/L	10			
Trichloroethene	ND		0.0500	mg/L	10			
Vinyl chloride	ND		0.100	mg/L	10			
Surr:1,2-Dichloroethane-d4	- 101		82 - 124	%REC	10	10/6/2004 6:31:00 PM	ROBERT_041006A	RMJ
Surr:4-Bromofluorobenzene	115		87 - 115	%REÇ	10			
Surr:Toluene-d8	110		85 - 115	%REC	10	_		

Definitions:

NP - Petroleum Pattern is not present

DNI - Did not Ignite

J - Estimated value

NC - Not Calculated

P - Post Spike Recovery outside limits

^{* -} Recovery outside QC limits

DF - Dilution Factor

H - Value Exceeds Maximum Contaminuat Level

N - Single Column Analysis

B - Apulyte found in Method Nank

D - Diluted due to maxinix or extended target compounds

E - Result above quantitation limit (high standard or ICP linear range).

M - Matrix Spike Recovery outside limits

ND - Not Detected at the Reporting Limit



Lab Order: 0409250

Lab ID: 0409250-03B

Client:

Project:

Analytical Del vices Center

International Specialists in Environmental Analysis

Sample Type: SAMP

4493 Walden Avenue

Parsons Engineering Science, Inc.

Tooele RCRA Phase II

Lancaster, New York 14086

Laboratory Results

NYS ELAP ID#:

(716) 685-8080

Prep Method: SW1311

Client Sample ID: IDW06

Ait. Client ID:

Method: SW8260B

Collection Date: 9/20/2004 9:00:00 AM % Moist:

Phone:

TCLP VOLATILE ORGANIC COMPOUNDS BY METHOD 8260B

Matrix: Soil

Test Code: 1_1311_8260B_L

Analyte	Result	Q	RL	Units	DF	Date Analyzed Run Batch ID	Analysi
1,1-Dichloroethene	ND		0.0500	mg/L	10	10/6/2004 7:02:00 PM ROBERT_041006A	RMJ
1,2-Dichloroethane	ND		0.0500	mg/L	10		
2-Butanone	ND		0.100	mg/L	10		
Benzene	ND		0.0500	mg/L	10		
Carbon tetrachloride	ND		0.0500	mg/L	10		
Chlorobenzene	ND		0.0500	mg/L	10		
Chloroform	ND		0.0500	mg/L	10		
Tetrachloroethene	ND		0.0500	mg/L	10		
Trichloroethene	ND		0.0500	mg/L	10		
Vinyl chloride	ND		0.100	mg/L	10		
Surr:1,2-Dichloroethane-d4	102		82 - 124	%REC	10	10/6/2004 7:02:00 PM ROBERT_041006A	RMJ
Surr:4-Bromofluorobenzene	107		87 - 115	%REC	10		
Surr:Toluene-d8	109		85 - 115	%REC	10		

Definitions:

* - Recovery outside QC limits

DF - Dilution Factor

H - Value Exceeds Maximum Contaminant Level

N - Single Column Auslysis

NP - Petroleum Pattern is not present

B - Analyte found in Method blank

DNI - Did not Ignite

J - Estimated value

NC - Not Calculated

P - Post Spike Recovery outside limits

D - Diluted due to maxiria or extended target compounds

E - Result above quantitation limit (high standard or ICP finear range).

M - Matrix Spike Recovery outside limits

ND - Not Desected at the Reporting Limit



Analytical octaices center

International Specialists in Environmental Analysis

4493 Walden Avenue

Lancaster, New York 14086

Laboratory Acsults

NYS ELAP ID#:

10486 (716) 685-8080

Client:

Parsons Engineering Science, Inc.

Client Sample ID: IDW07

Lab Order: 0409250

Alt. Client ID:

Project:

Tooele RCRA Phase II

Collection Date: 9/21/2004 9:00:00 AM % Moist:

Lab ID: 0409250-04B

Sample Type: SAMP

Matrix: Soil

Test Code: 1_1311_8260B_L

TCLP VOLATILE ORGANIC COMPOUNDS BY METHOD 8260B

Method: SW8260B

Prep Method: SW1311

Analyte	Result Q	RL	Units	DF	Date Analyzed Run Batch I	D Analysi
1,1-Dichloroethene	ND	0.0500	mg/L	10	10/6/2004 7:32:00 PM ROBERT_041006	A RMJ
1,2-Dichloroethane	ND	0.0500	mg/L	10		
2-Butanone	ND	0.100	mg/L	10		-
Benzene	ND	0.0500	mg/Ĺ	10		
Carbon tetrachloride	ND	0.0500	mg/L	10		
Chlorobenzene	ND	0.0500	mg/L	10		
Chloroform	ND.	0.0500	mg/L	10		
Tetrachloroethene	ND	0.0500	mg/L	10		
Trichloroethene	ND	0.0500	mg/L	10		
Vinyl chloride	NĎ	0.100	mg/L	10		
Surr:1,2-Dichloroethane-d4	100	82 - 124	%REC	10	10/6/2004 7:32:00 PM ROBERT_041006/	A RMJ
Surr:4-Bromofluorobenzene	109	87 - 115	%REC	10		
Surr:Toluene-d8	110	85 - 115	%REC	10	•	

Definitions:

NP - Petroleum Pottern is not present

DNI - Did not Ignite

P - Post Spike Recovery outside limits

^{* -} Recovery outside QC limits

DF - Dilution Factor

H - Value Exceeds Maximum Contaminant Level

N - Single Column Analysis

B - Analyte found in Method blank

J - Estimated value

NC - Not Calculated

D - Diluted due to maximix or extended target compounds

E - Result above quantitation limit (high standard or ICP linear range).

M - Matrix Spike Recovery outside firmits

ND - Not Detected at the Reporting Limit



WASTE MATERIAL PROFILE SHEET

Clean Harbors Profile No. CH80421

A. GENERAL INFORM					GE	NERATOR PROP	ILE No. CH80421			
GENERATOR CODE (Assigned by Clean Harbors) ADDRESS Tooele Army Depot		8)	TO0469		GE	GENERATOR NAME Tocele Army Depot CITY Tocele STATE UT ZIP 84074 PHONE:				
	Assigned by Clean Herbors South Jordan Parkwa		PAR1392 300		CU CIT	STOMER NAME: Y South Jord e	Parsons Engineerin			
B. WASTE DESCRIPTI	ON						<u></u>		<u>-</u>	
WASTE DESCRIPTION	N: Drilling So	əll								
	'ING WASTE (Please provi off-site monitoring we		description	of process gene	rating waste)					
C. PHYSICAL PROPER										
PHYSICAL STATE SOLID WITHOUT F POWDER MONOLITHIC SOLI LIQUID WITH NO S	Đ		1	R OF PHASES/ 2 DLUME (Approx.)	3 TOP MIDE		VISCOSITY (if liquid pres 1 - 100 (e.g. WATER) 101 - 500 (e.g. MOTOR 501 - 10,000 (e.g. MOL	OIL)	COLOR Brown to Bi	
LIQUID/SOLID MIXT							> 10,000		<u> </u>	
% FREE LIQUID			ODOR		BOI	LING POINT	MELTING POINT		RGANIC CARBON	
% SETTLED SO % TOTAL SUSP			L			<= 85 °F > 95 °F	< 140 °F	<= 19 1-9%	6	
SLUDGE	ENDED GOZI		MIL	RONG		101 - 129 °F	140-200 °F	>= 10	%	
GAS/AEROSOL						>= 130 °F	□ > 200 °F	1	,,	
FLASH POINT	pH	Lenzois	Describe			ASH		1		
< 73 °F	pπ <= 2		8 (e.g. Gas	•		< 0.1	> 20	BTU/	L#3 < 2,000	
73 - 100 °F	2.1 - 6.9		1.0 (e.g. Et			0.1 - 1.0	✓ Unknown		2,000-5,000	
101 -140 °F	7 (Neutral)	☑ 1.0	(e.g. Water)		1.1 - 5.0			5,000-10,000	
141 -200 °F 7.1 - 12.4 1.0			-1.2 (e.g. Antifreeze)			5.1 - 20.0	Actual:		> 10,000	
> 200 °F	>= 12.5	> 1.	2 (e.g. Meti	hylene Chtoride)	1			Actua	ıl	
Actual:	Actual:	1				VAPOR PRESSI	JRE (for fiquids only)	: m:	n Hg	
used, please supply an M	he complete composition of ISDS. Please do not use ab	breviations	i.)				vidual components are accep	table. If a tra	de name is	
CHEMICAL			- MAX	MOU	CHEMIC	AL		N - MAX	<u>MOU</u>	
Benzene Solf			0 7.000	PPB %						
Tetrachloroethene			- 100.000							
1 en acino contene		0.000	10.000	PPB						
İ										
ANY METAL OBJECT	IS PRESENT? YES	⊠ NG								



Clean Harbors Profile No. CH80421

E. CONSTITUENTS - Are these values based on testing or knowledge? ■ Knowledge ✓ Testing If constituent concentrations are base on analytical testing, analysis must be provided. If based on knowledge, basis of knowledge must be provided below. RCRA REGULATED METALS TOTAL REGULATORY TCLP OTHER METALS MIN MAX UOM LEVEL (mg/l) DDM mg/l ALUMINUM D004 ARSENIC 5.0 ANTIMONY D005 BARIUM 100.0 BERYLLIUM D006 CADMIUM 1.0 CALCIUM D007 CHROMIUM 5.0 COPPER LEAD D008 5.0 MAGNESIUM MERCURY D009 0,2 **MOLYBDENUM** SELENIUM D010 1.0 NICKEL SILVER D011 5.0 POTASSIUM SILICON SODIUM THALLIUM **VOLATILE COMPOUND** TOTAL REGULATORY TCLP TIN LEVEL (mg/l) mg/i mag VANADIUM D018 BENZENE 0.007 0.5 ZINC D019 **CARBON TETRACHLORIDE** 0.5 CHLOROBENZENE D021 100.0 D022 CHLOROFORM 6.0 D028 1.2-DICHLOROETHANE 0.5 NON-METALS MIN MAX UOM D029 1,1-DICHLOROETHYLENE 0.7 BROMINE D035 METHYL ETHYL KETONE 200.0 CHLORINE D039 **TETRACHLOROETHYLENE** 0.011 0.7 FLUORINE D049 TRICHLOROETHYLENE 0.5 **IODINE** D043 VINYL CHLORIDE 0.2 SULFUR RCRA SEMI-VOLATILE COMPOUND TOTAL REGULATORY **TCLP** LEVEL (mg/l) ppm mg/l OTHER NON-METALS MIN MAX UOM o-CRESOL D023 200.0 DG24 m-CRESO1 200.0 **AMMONIA** D025 REACTIVE SULFIDE p-CRESOI 200.0 D026 CRESOL (TOTAL) 200.0 CYANIDE-TOTAL CYANIDE AMENABLE D027 1.4-DICHLOROBENZENE 7.5 D030 CYANIDE REACTIVE 2.4-DINITROTO! LIENE 0.13 **HEXACHLOROBENZENE** D032 0 13 D033**HEXACHLOROBUTADIENE** 0.5 D034 HEXACHLOROFTHANE OTHER CHEMICALS 3.0 MIN MAX UOM NITROBENZENE D036 2.0 PHENOL D037 PENTACHLOROPHENOL 100,0 Total Petroleum Hydrocarbons D038 **PYRIDINE** 5.0 D041 2,4,5-TRICHLOROPHENOL 400.0 2.4.6-TRICHLOROPHENOL D042 2.0 OTHER RCRA PESTICIDES AND HERBICIDE REGULATORY TCLP TOTAL **HOCs PCBs** LEVEL (mg/l) ppm mg/l D012 ENDRIN **M** NONE 0.02 M NONE D013 LINDANE 0.4 < 1000 PPM <50 PPM D014 METHOXYCHLOR 10.0 >= 1000 PPM >= 50 PPM D015 TOXAPHENE 0.5 D016 2.4-D 10.0 IF PCBS ARE PRESENT, IS THE D017 2.4.5-TP (SILVEX) WASTE REGULATED BY TSCA 1.0 D020 CHLORDANE 0.03 49 CFR 761? D031 HEPTACHLOR 0.008 Ø NO YES (AND ITS EPOXIDE) **ADDITIONAL HAZARDS** DOES THIS WASTE HAVE ANY UNDISCLOSED HAZARDS OR PRIOR INCIDENTS ASSOCIATED WITH IT, WHICH COULD AFFECT THE WAY IT SHOULD BE HANDLED? ⊠no YES (If yes, explain) **ASSESTOS** INFECTIOUS, PATHOGENIC, OR ETIOLOGICAL AGENT REDUCING AGENT **DEA REGULATED SUBSTANCES** OXIDIZER SHOCK SENSITIVE DIOXIN OSHA REGULATED CARCINOGENS SPONTANEOUSLY IGNITES WITH AIR **EXPLOSIVE** PESTICIDE THERMALLY SENSITIVE HERBICIDE **POLYMERIZABLE** WATER REACTIVE FUMING / SMOKING WASTE RADIOACTIVE NONE OF THE ABOVE



Clean Harbors Profile No. CH80421


F. REGUL/	ATORY ST	TATUS				·		
YES	NO	USEPA HAZARDOUS WASTE?						
YES	Мио	DO ANY STATE WASTE CODES A	PPLY?					
YES	NO	IS THIS WASTE PROHIBITED FRO LDR CATEGORY: This is sub	OM LAND DISPOSAL WITH	OUT FURTHER TREA	TMENT PER	40 CFR PART 268?		
YES YES		VARIANCE INFO: IS THIS A WASTEWATER PER 40 (IF ANY WASTE CODES D001, D002 NON-WASTEWATERS, OR D018- E	2, D003 (OTHER THAN REAC 1043 APPLY, ARE ANY UND	ERLYING HAZARDOUS	EACTIVE SUL S (UHCs) PRE	FIDE), D004-D0011, D012-D SENT ABOVE UNIVERSAL	1017 TREATMEN	
YES YES	NO NO	DOES TREATMENT OF THIS WAS IS THIS WASTE SUBJECT TO CA' IF YES, SPECIFY POINT SOURCE	STE GENERATE A F006 OR FEGORICAL PRETREATME	RF019 SLUDGE? ENT DISCHARGE STA				
YES		IS THIS WASTE REGULATED UND RECOVERY, OR PETROLEUM REF	ER THE BENZENE NESHAP INERY PROCESS?)	RULES? (IS THIS WA	STE FROM A	CHEMICAL MANUFACTURI	NG, COKE B	Y-PRODUCT
YES YES YES YES	MINO	DOES THIS WASTE CONTAIN VO DOES THE WASTE CONTAIN GRI DOES THIS WASTE CONTAIN AN 77 KPa (11.2PSIA)?	EATER THAN 20% OF ORG ORGANIC CONSTITUENT	ANIC CONSTITUENT	S WITH A VA FORM HAS A	POR PRESSURE >= .3KPA VAPOR PRESSURE GRE	\ (.044 PSIA) ATER THAN	?
	_	IS THIS CERCLA REGULATED (SU		<u></u>	<u>-</u> -		<u> </u>	
G. D.O.T IN US D.O	T. DESC	ON: (Include proper shipping name, h RIPTION: Hazardous waste, soli	azard class and ID number). d, n.o.s., (PCE, Benzene	e) , 9, NA3077, PG II	ii			
ESTIMA	TED SHII LIQUID (ON REQUIREMENTS PMENT FREQUENCY: ON OR BULK SOLID PLEASE INICATE THE		MONTHLY LOADS PER SHIPPIN	QUARTERL'	CY	OTHER	-
	<u>1-20</u>	CONTAINERS/SHIPMENT	GALLONS/SHIPMENT:	LIGOID	GAL.	BULK S SHIPMENT UOM:	SOLID TON	YARD
	ER TYPE BIC YARD	:	FROM TANKS: TANK FROM DRUMS VEHICLE TYPE:	SIZE	GAL.	PER SHIPMENT: (STORAGE CAPACI VEHICLE TYPE:).00 MIN	0.00MAX TON/YD
	LET E TANK IER:		VAC TRUCK TANK TRUCK			DUMP TRAILER ROLL OFF BOX		
_	JM SIZE:		RAILROAD TANK CAR CHECK COMPATIBLE ST	•		INTERMODAL ROL	LOFF BOX	
CONTAINI STE FIBE	EL ER	RIAL:	STEEL RUBBER LINED	STAINLESS STEEL FIBERGLASS LINE		OTHER		
PLA: OTH	STIC IER		OTHER					
SPECIAL SPECIFIC		T AL RESTRICTIONS OR REQUESTS:						·
		HANDLING REQUIREMENTS IS OR REQUESTS:	see attached analysis					
. BIENNIAL	/ ANNUA	L REPORTING INFORMATION			·	· ·		
SIC CODE	9711	SOURCE COE	E A69 F	ORM CODE B30	01	ORIGIN CODE	2	
REPRESE		SAMPLE HAS BEEN SUPPLIE	YES VNO	SAMPLED BY	DATE	E SAMPLED	WHERE SE	NT
		IFICATION						
submitted a	are repres ors the a	Ill information submitted in this and at entative of the actual waste. If Clean Uthority to amend the profile, as Clean DRIZED SIGNATURE	Harbors discovers a discrep Harbors deems necessary,	sancy during the appro-	val process. G	certify that any samples tenerator grants		DATE
		RS USE ONLY ITATIVE COMPLETING PROFILE:_					<u> </u>	

UNIFORM HAZARDOUS WASTE MANIFEST	1. Generator's US EPA (1773213320894	ID No.	Manifest Document No.	2. P	age 1 Info	mation In	the shaded area i by Federal law.
. Generator's Name and Mailing Address		- 12-2-1 - 2-11	****	A. St	ate Manifest	Documen	<u>, </u>
Rosele Army Depot Environm Building 8, Attn: Dean Rey	molds. Toomie.	JMTE-CS-E HT 84074			ate Generato		
Generator's Phone (435) 8333				B. St	ale dellerato	1910	grifika a jerak
Transporter 1 Company Name	6.	US EPA ID			ate Transpor		i i egi egi
Transporter 2 Company Name	6.	000624247 US EPAID I			ansporter's P ate Transport		5)843-7802
(1905, 4 P	71. £ 99 [· · · · · · · · · · · · · · · · · · ·		ensporter's P		Territoria de la gr
Designated Facility Name and Site Address		US EPA ID	Number:		ate Facility's		
lean Harbors Aragonite Fa 1500 N. Aprees Road	icities many probability				cility's Phone		german, en en en en en en en en en en en en en
gagonite, UT 84029	ery]	981552177	:		301) 323		
1. US DOT Description (Including Proper SI			ner) 12. Cont		13. Total Quantity	14. Unit Wt/Vol	Waste No.
				1,750	Quantity	est	F001,F002
Hazardous Wasre Soli NA3077, PG 111	d, N.O.S., (PCE	, Benzene) 9,			P	F005
MASOFF, TG III		· · · · ·		dia			
	·		i turitu.		• •		
		<u> </u>					
	and the second						
,					.*		
5. Special Handling Instructions and Addit Exergency Contact - Took	2ST01-07 ional Information	2640[-06 Lre Depar	26501-03	33.	3-2015		
6. GENERATOR'S CERTIFICATION: I hereby declar proper shipping name and are classified, packed, according to applicable international and national if I am a large quantity generator, I certify that economically practicable and that I have select future threat to human health and the environmenthe best waste management method that is available.	re that the contents of this cons, marked, and labeled, and are in government regulations. It I have a program in place to total the practicable method of ment; OR, if I am a small que	signment are fully a in all respects in pi o reduce the volu f treatment, stora intity generator, 1	me and toxicity of ge, or disposal our have made a good	ansport b waste ge	ny highway nerated to the	high minim	izee the precent an
Printed/Typed Name	garanta da kanana da kanana da kanana da kanana da kanana da kanana da kanana da kanana da kanana da kanana da Kanana da kanana da kanana da kanana da kanana da kanana da kanana da kanana da kanana da kanana da kanana da k	Signature			_ in the second		Month Day Yea
7. Transporter 1 Acknowledgement of Rec	ceipt of Materials	North All The C	e to the company of the control of t	171 × 4	. :		MAN HA
Printed/Typed Name: 3.36. verderstage:	Programme Commence of the St.	Signature :	والمتناف فالمجاولة	d March	and the second	Van Taga	Month Day Ye
2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2. 2			Coloques Colonia		5,4 1 1 1	····	
3. Transporter 2 Acknowledgement of Rec				•			Month Day Yea
	· · · · · · · · · · · · · · · · · · ·	Signature					1
Transporter 2 Acknowledgement of Rec Printed/Typed Name Discrepancy Indication Space		er er erek se	er en en de generale Grand de generale			Maria Maria	
Transporter 2 Acknowledgement of Rec Printed/Typed Name Discrepancy Indication Space	and the selection	e e e e e e e e e e e e e e e e e e e	er diser _{en} e e	, 450, 4°.	tita svija i utili. V		

Style F15 LASELMASTER \$ (800) 621-5808 www.lebelmaster.com

EPA Form 8700-22 (Rev. 9-88) Previous editions are obsolete.







406 West South Jordan Parkway, Suite 300 . South Jordan, Utah 84095 . (801) 572-5999 . Fax (801) 572-9069

Memorandum

To:

Dean Reynolds, TEAD; Larry McFarland, TEAD

Copy:

Maryellen Mackenzie, USACE; Carl Cole, USACE; Doug Mackenzie,

USACE; Richard Jirik, Parsons; Jeff Bigelow, Parsons

From:

Jan Barbas, Parsons

Date:

Wednesday, November 17, 2004

Subject:

TEAD SWMU-58 RFI - Waste Management

This letter is to recommend disposition of the contents of the Baker tank summarized in Table One. The waste was generated in association with equipment decontamination and development of wells D-12, D-13 and D-16.

The Baker tank sample was labeled IDW11. IDW11 was analyzed for total VOCs. Analysis was conducted by Ecology and Environment, Inc, Lancaster NY, a Utah Certified laboratory.

Results have been received as data packages and electronic data deliverables. Parsons has reviewed the data and found QC to be acceptable. Analytical results and case narrative are appended.

Listed Wastes Analysis:

Benzene at 0.590 μ g/L, ethylbenzene at 23.3 μ g/L, m,p-xylenes at 90.8 μ g/L, naphthalene at 2.22 μ g/L, o-xylene at 45.3 μ g/L, methylene chloride 330 μ g/L, and toluene at 2970 μ g/L were detected. As a result it is recommended that the waste be classified as hazardous F001, F002 and F005 listed wastes.

Characteristic Wastes Analysis:

The waste is known to be primarily water. Therefore generator's reasonable knowledge may be used to exclude the characteristics of ignitability, reactivity and corrosivity.

No constituents were detected in excess of TCLP limits. Therefore no characteristic waste codes should be applied.

Land Disposal Restrictions Analysis:

Methylene chloride and toluene exceed land disposal restriction limits for wastewaters.

Disposition:

Parsons recommends that this waste be processed through the TEAD wastewater treatment facility.

Parsons will arrange to dispose of the waste per your written instructions.



From: McFarland, Larry [larry.mcfarland@us.army.mil]

Sent: Thursday, November 18, 2004 7:15 AM

To: Barbas, Jan; Bigelow, Jeff; colec@emh2.tooele.army.mil; reynoldd@emh2.tooele.army.mil;

doug.d.mackenzie@usace.army.mil; Jirik, Richard; mcfarlal@emh2.tooele.army.mil;

Maryellen.Mackenzie@usace.army.mil

Cc: Kubacki, Steve

Subject: RE: TEAD Phase II RFI Waste Management - Baker Tank

Richard

Based our discussions earlier this week concerning the disposal of the decon and development water from from monitoring wells D-12, D-13, and D-16 you indicated that analysis of the water detected toluene and methylene chloride. Based on this discussion TEAD concurred with your recommendation to dispose of the water at the Ground Water Treatment Plant. On 11/17/04, the TEAD Environmental Office received a copy of the analytical which listed other contaminants in addition to those we had discussed earlier. Based on the analysis provided, the Ground Water Treatment Plant is not permitted to treat all of these constituents. As we are not permitted to treat all of the detected contaminants, the water CAN NOT be disposed of at the treatment facility. Parsons should make arrangement to dispose of the water offsite.

Larry McFarland
Environmental Office, SJMTE-C5-E0
1 Tooele Army Depot, Building 8
Tooele, Utah 84074-5003
Phone (435) 833-3235 Fax (435) 833-2839
larry.mcfarland@us.army.mil
mcfarlal@emh2.tooele.army.mil



Analytical Services Center

International Specialists in Environmental Analysis
4493 Walden Avenue
Lancaster, New York 14086

Laboratory Results

NYS ELAP ID#: 10486 Phone: (716) 685-8080

Client:

PARSONS ENGINEERING SCIENCE, INC.

Project:

Tooele RCRA Phase II

Lab Order:

0411048

CASE NARRATIVE

A trip blank labeled IDWTB4 was received with the IDW12 sample (COC 910). It was not analyzed per Jan Barbas' direction on November 3, 2004.

GCMS VOLATILES

A DB 624 column and a trap packed with OV-1, Tenax, silica gel and activated charcoal was used for the volatile analysis.

Sample Analysis

The volatile samples were determined to be at a pH of 1.

The sample was analyzed within hold time.

Sample IDW12 exceeded the calibration range for methylene chloride and toluene. It was reanalyzed at a 100-fold dilution and both sets of results are reported.

Calibration and Tunes

All initial and continuing calibrations were acceptable.

Manual integrations were not required.

QC

All surrogate recoveries were within acceptable limits.

All blank analyses were acceptable.

All laboratory control sample recoveries were acceptable.

All internal standard area responses were acceptable.

Tony Bogolin

Project Manager

November 16, 2004



Analytical Services Center

International Specialists in Environmental Analysis

Lancaster, New York 14086-

Phone: (716) 685-8080

Fax: (716) 685-0852

Laboratory Results

NYS ELAP ID#:

Phone: (716) 685-8080

b Order:

0411048

ent:

Parsons Engineering Science, Inc.

>ject:

Tooele RCRA Phase II

DATES SUMMARY REPORT

B) Sample ID (CLIENT)	3.4-1-1	7					
b) sample in (Cinei(1)	Matrix	Test Name	Collection Date	Received Date	BT (Days) / HT Expire	Analyzed* - Analysis/BatchiD	Type DF #Analytes F
1048-01A 1DW12	Water Lo	w Level VOCs by Method 8260B	11/2/2004 2:30:00 PM	11/3/2004 8:50:00 A	M 14:C 11/16/2004 2:30:00 PM 1	1/13/2004 8:33:00 AM 1060865	SAMP 1 21

From: C-Collection / R- Receipt(VTSR) / P-Prep / T-TCLP Prep

nalyzed" reflects the analysis date and time or injection time for analytical tests. For preparation tests "Analyzed" reflects the start of the preparation except when "AFCEE criteria used"; flag indicates date time of completion of the preparation.

TCLP/SPLP Extractions and subsequent preparation tests..."Analyzed" reflects the date of TCLP/SPLP Extraction/preparation. For Re-extracted (RE) samples: Preparation tests completed dates reflects extraction from the original sample leacheste unless an "RE" Sample exists for the extraction (tumble) test.

S Version #: 041116_1400

Printed: Tuesday, November 16, 2004 4:05:48 PM



Analytical Services Center
International Specialists in Environmental Analysis Lancaster, New York 14086-

ecology and environment, inc. Phone: (716) 685-8080

Fax: (716) 685-0852

Laboratory Results

NYS ELAP ID#:

10486

Client:

Parsons Engineering Science, Inc.

Project:

Tooele RCRA Phase II

Work Order:

0411048

Method References

GCMS Volatiles

Parsons, Tooele - VOCs, Low Level by GCMS Method 8260B

Test Methods for Evaluating Solid Waste: Physical/Chemical Methods, 3rd ed. 1986. Volumes, IA, IB, IC & Volume 2. (Includes all Updates). U.S. Environmental Protection Agency, Office of Solid Waste and Emergency Response.

CHAI	OF CUSTODY	·		Tooele Industrial Area Contractor:			Parsons - SLC		rsons Point of Cor W. South Jordan		es .	
	PARSONS			Ed Staes		Installation:		TEAD		Suite 300 South Jordan, Utah 84095		
COCI	D: 909	Sample C	oordinator	Jeff Bigel	elow Sample Program: Shallow Soil Sam			· ·				
Site ID	Location ID	Sample ID	Matrix	Method	Туре	Sample No.	Log Date	Log Time	Logged By	Beg. Depth	End. Depth	Total Conts.
	IDW12	IDW12	ww	В	N	1	11-2-04	14:30	JJR	 	·····	خ ا
	Analysis	Lab	Cooler	No. Conts	AB Lot	EB Lot	TB Lot	Remarks:	<u> </u>	d	- J-, -, -,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	J
voc		ECEN	-4	3	-		11020401		IDW:	Sample	fin	

Buker Pank PARSNZ 0426801 (Well Development + Decontamination back for Vells D-12, D-13, and D-16

Refinquished by (Signature)	Date/Time	Received by (Signature)	Date/Time
19 Mil	11-2-09 16:00	Rfall	11-3-04 8:50
O My May	7 th 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		and the state of t
:		!	• • • • • • • • • • • • • • • • • • •
		For the first temperature of the control of the con	· · · · · · · · · · · · · · · · · · ·

CHAIN OF CUSTODY	Project Name:	Tooele Industrial Area	Contractor:	Parsons - SLC	Parsons Point of Contact: Jan Barbas 406 W. South Jordan Parkway
PARSONS	Project Manager:	Ed Staes	Installation:	TEAD	Suite 300 South Jordan Utah 84095
COC ID: 910	Sample Coordinator:	Jeff Bigelow	Sample Program:	Shallow Soll Sampling	(801) 572-5999 FAX (801) 572-9069

Site ID Location ID	Sample ID	Matrix	Method	Туре	Sample No.	Log Date	Log Time	Logged By	Beg. Depth	End. Depth	Total Conts.
IDWTB4	IDWTB4	WQ	NA NA	TB	1	11-2-04	14:30	TJB		:	
Analysis	Lab	Cooler	No. Conts	AB Lot	EB Lot	TB Lot	Remarks;		·		
VOC	ECEN	4	1				1 4.	a- 1	11	()	•

Associated with wask mater Sample IDW/L

Relinquished by (Signature)

Date/Time

Received by (Signature)

Date/Time

1/2-04 /6:00

Date/Time

1/2-04 8:50



Cooler Receipt Form

ecology and environment line.							
No. of Packages:			Date Received:				
Package Receipt No.:	14894		Project or Site Name:	11-3-04			
Client:	37 . 2			<u> </u>			
L	- FOX SOAS		<u> </u>			· · ·	
A Paliminany Evan	nination and Da						
Did coolers come with	nination and Rec	eipt Phase	· · · · · · · · · · · · · · · · · · ·			irde 0	
(and print airbill numbe	r below Fed Ev	irbome Client Other	405	Yes	No	NA
ž	azard or dangerous go	1	abovite Citetic Ottes	de			
2. Did cooler(s) have cus					Yes	NO_	NA NA
	broken and intact on re	ceint?			(Yes)	No	NA
Were custody seals da					\cong	No	NA
5. How was package seco		d () Fiberglass T	ape o Plantu		Yes	No	NA
		- 1.50.3000					
D Hannation Di			· · · · · · · · · · · · · · · · · · ·				
B. Unpacking Phas	<u>e</u>	<u> </u>		· · · · · · · · · · · · · · · · · · ·			
6. Date cooler(s) opened:	11-3-04	Cooler(s) open	ed by:Dfcul	U.V			
	nk vial included inside o	cooler(s)?	(Signature)		7 700		7
			emperature for Each Cool	or Dange (30 - 600)	Yes	No	NA
Alibil No.	Temp Cal-	Amilena	Lempac .	er, Kange (2° - 8°C)			avere tem
84572785 419	4 6.0			AUDICAO.		temp	id G
- 103 TI	5			<u> </u>			
				· · · · · · · · · · · · · · · · · · ·	- -		
Thermometer No.: 00			*if temperature is outs	ide of acceptable mus			
X3	Correction	r Factor: O. O	Notification form indic	ating affected contain	iers. Je, prepa	are a P	'M'I
8. Were the C-O-C forms					Yes	No	NA
C-O-C forms numbers i							
Was enough packing m					Yes	No	NA
Type of material:			□ Other	 			
10. If cooling was required			ed: □Wet □Dry □B	lue D Other			ŅΑ
11. Were all containers sea		=			Yes	No	NA
12. Did all containers arrive		condition?			Yes	No	NA
13. Interim storage area If	not logged:			· · · · · · · · · · · · · · · · · · ·		<u> </u>	
In: Date	Time	Sig	nature				
Out: Date	Time	Sic	mature				
				·		· -	-
	·						
C. Login Phase					<u> </u>	 -	$\overline{}$
Samples Logged in By Signa	1/1 1/	ely	Date:	11/3/	54		
14. Were all container label					(Yes)	No	NA
15. Were all C-O-C forms fi					E	No	NA
16. Did the C-O-C form agr					res)	No	NA
17. Were the correct contain				<u> </u>	(Pes)	No	NA
18. Were the correct preser				<u> </u>	(es)	No	NA
19. Was a sufficient sample	volume sent for the tes	ts requested?			(Z)		-

20. Were all volatile samples received without headspace?

^{*}Drenace a DM Motification form (E-AS1)



Analytical Services Center

International Specialists in Environmental Analysis

4493 Walden Avenue

Laucaster, New York 14086

Laboratory Results

NYS ELAP ID#: 10486

Phone: (716) 685-8080

Client:

Parsons Engineering Science, Inc.

Lab Order: 0411048

Project: Tooele RCRA Phase II Client Sample ID: IDW12

Alt. Client ID:

Collection Date: 11/2/2004 2:30:00 PM % Moist:

Lab ID: 0411048-01A

Sample Type: SAMP

Matrix: Water

Test Code: C_8260B_5030B_LL_W_018

LOW LEVEL VOCS BY METHOD 8260B

Method: SW8260B

Prep Method: SW5036B LL

Analyte	Result	Q	RL	Units	DF	Date Analyzed	Run Batch ID	Analyst
1,1,1-Trichtoroethane	ND		1.00	μg/L		11/13/2004 8:33:00 AM	1749-5 0-4-1-9	
1,1,2-Trichloroethane	ND		1.00	μg/L	1	11713/2004 B.33.00 AM	LINUS_841113A	MRD
1.1-Dichtoroethane	ND		1.00	μg/L	•			
1.1-Dichloroethene	ND		1.00	μg/L	1			
,2-Dichloroethane	ND		1.00	μg/L	,			
,2-Dichloropropane	ND		1.00	μg/L	,			
Senzene	0.590	J	1.00	μg/L				
arbon tetrachloride	ND	•	1.00	μg/L	1			
hloroethane	ND		1.00	μg/L				
hioroform	ND		1.00	μg/L				
is-1,2-Dichloroethene	ND		1.00	μg/L	. 1			
thylbenzene	23.3		1.00	μg/L				
n,p-Xylene	90.8		1.00	μg/L	•			
lethylene chloride	332	Ε	2.00	μg/L	1			
laphthalene	2.22	_	1.00	μg/L			•	
-Xylene	45.3		1.00	μg/L				
etrachloroethene	ND		1.00	μg/L				
cluene	736	E	1.00	μg/L	1			
ans-1,2-Dichlorcethene	ND	_	1.00	μg/L	1			
richloroethene	ND		1.00	μg/L	1		•	
finyl chloride	ND		1.00	μg/L	1			
Surr:1,2-Dichloroethane-d4	99		70 - 130	%REC	1	11/13/2004 8:33:00 AM LI	NUS DATITA	MRD
Surr:4-Bromofluorobenzene	93		70 - 130	%REC	1		100_24111000	שחואו
SumToluene-d8	96		70 - 130	%REC	1			

Definitions:

NP - Petroleum Pattern is not present

^{* -} Recovery outside QC firms

DF - Dilution Factor

H - Value Exceeds Maximum Contaminant Level

N - Single Column Analysis

B - Analyte found in Method blank

DNI - Did not fgnite

J - Estimated value

NC - Not Calculated P - Post Spike Recovery outside limits

D - Diluted due to maxisis or extended target compounds

B - Result above quantitation first (high stendard or ICP linear range).

M - Matrix Spike Recovery outside limits

ND - Not Detected at the Reporting Limit

R - RPD outside recovery limits



International Specialists in Environmental Analysis

4493 Walden Avenue

Lancaster, New York 14086

Lauviawiy ixomio

NYS ELAP 1D#: 10486

Phone: (716) 685-8080

Client: Parsons Engineering Science, Inc.

Lab Order: 0411048

Project: Tooele RCRA Phase II

Client Sample ID: IDW12

Alt. Client ID:

Collection Date: 11/2/2004 2:30:00 PM % Moist:

Lab ID: 0411048-01A

Sample Type: DL

Matrix: Water

Test Code: C_8260B_5030B_LL_W_018

OWAL	CVCi	MODE	ĐУ	METHOD	90000
LUWL	.E.Y.E.L	VUUS	BY	MEIBUU	82606

X.S	-44-	
	othe	

SW8260B

Prep Method: SW5030B_LL

Analyte	Result	Q	RL	Units	DF	Date Analyzed	Run Batch ID	Analyst
1,1,1-Trichloroethane	ND		100	μg/L	100	11/14/2004 6:12:00 PM	LINUS_041114B	MRD
1,1,2-Trichloroethane	ND		100	μg/L	. 100			
1,1-Dichloroethane	ND		100	μg/L	100			
1,1-Dichlorcethene	ND		100	μg/L	100			
1,2-Dichloroethane	NĐ		100	μg/L	100			
1,2-Dichloropropane	В		100	μg/L	100			
Benzene	. ND		100	<i>μ</i> g/L	100			
Carbon tetrachloride	. ND		100	μg/L	100			
Chloroethane	ND		100	μg/L	100			
Chloroform	ND		100	μg/L	100			
cis-1,2-Dichloroethene	ND	•	100	μg/L	100			
Ethylbenzene	ND		100	μg/L	100			
m,p-Xylene	61.8	j	100	μg/L	100			
Methylene chloride	330		200	μg/L	100			
Naphthalene	ND		100	μg/L	100			
o-Xylene	23.4	j	100	μg/L	100			
Tetrachloroethene	ND		100	μg/L	100			
Toluene	2970		100	μg/L	100	•		
trans-1,2-Dichloroethene	ND		100	<i>μ</i> g/L	100			
Trichloroethene	ND		100	μg/L	100			
Vinyl chloride	ND		100	μg/L	100			
Surr.1,2-Dichlorgethane-d4	103		70 - 130	%REC	100	11/14/2004 6:12:00 PM L	NUS_041114B	MRD
Surr:4-Bromofluorobenzene	98		70 - 130	%REC	100			
Surr:Toluene-d8	91		70 - 130	%REC	100			

Definitions:

NP - Petrolimum Pattern is not present

[.] Recovery outside QC limits

DF - Dilution Factor

H - Value Exceeds Maximum Continuinant Level

N - Single Column Analysis

B - Anelyte found in Method blank

DNI - Did not Ignite

J - Estimated value

NC - Not Calculated

P - Post Spike Recovery outside limits

D - Diluted due to maximix or extended target compounds

E - Result above quantitation limit (high standard or ICP linear range).

M - Matrix Spike Recovery outside fimits

ND - Not Detected at the Reporting Limit

R - RPD outside recovery limits



CleanHarbors* WASTE MATERIAL PROFILE SHEET

ENVIRONMENTAL SE	RVICES, NC.		Clean Ha	ırbo	rs Profil	e No. CH83	3147	
		s)	TO0469	GE		FILE No. CH83147 Tooele Army Depot STATE t	UT ZIP {	34074
· ·	signed by Clean Harbors) South Jordan Parkway		PAR1392	CU	JSTOMER NAME: TY South Jord	PHONE: Parsons Engineerii ian STATE &		
	Purge wate	de detailed	decon water DI2, D13 d description of process generalination of drill rig equip	3 , D 1	6			
. PHYSICAL PROPERTI	IES (at 25C or 77F)			-				 ,- <u></u>
HYSICAL STATE SOLID WITHOUT FRI POWDER MONOLITHIC SOLID ☑ LIQUID WITH NO SO	EEE LIQUID DLIDS		NUMBER OF PHASES/LAY 1 2 3 % BY VOLUME (Approx.)	YERS TOP MIDE BOTT		VISCOSITY (If liquid pres 1 - 100 (e.g. WATER) 101 - 500 (e.g. MOTOR 501 - 10,000 (e.g. MOL > 10,000	R OIL)	COLOR <u>Clear/Wate</u>
LIQUID/SOLID MIXTU % FREE LIQUID % SETTLED SOLII % TOTAL SUSPEN SLUDGE GAS/AEROSOL	ID		ODOR INONE MILD STRONG Describe:		ILING POINT <= 95 °F > 95 °F 101 · 129 °F >= 130 °F	MELTING POINT < 140 °F 140-200 °F > 200 °F	TOTAL OF <= 19 1-9% >= 10	•
FLASH POINT < 73 °F 73 · 100 °F 101 · 140 °F 141 - 200 °F ✓ > 200 °F	pH <= 2 2.1 - 6.9 ✓ 7 (Neutral) 7.1 - 12.4 >= 12.5	< 0.4 0.8- 1.0-	FiC GRAVITY 0.8 (e.g. Gasoline) 3-1.0 (e.g. Ethanol) 0 (e.g. Water) 0-1.2 (e.g. Antifreeze) 1.2 (e.g. Methylene Chloride)	0.1 1.1 5.1		< 0.1 > 20 0.1 - 1.0 Unknown 1.1 - 5.0 5.1 - 20.0 Actual:		/LB < 2,000 2,000-5,000 5,000-10,000 > 10,000
ctual:	Actual:	<u> </u>			· · · · · · · · · · · · · · · · · · ·	URE (for liquids only)		m Hg
D. COMPOSITION (List the sed, please supply an MSI CHEMICAL	e complete composition of DS. Please do not use abb	breviations		and for de			ptable. If a tra	ade name is
Benzene Ethylbenzene m.p-Xylene Methylene chloride o-Xylene Taluene Water Napthalene		0.000 0.000 0.000 0.000 0.000 99.000	00 0.000 PPB 0 23.000 PPB 0 90.000 PPB 332.000 PPB 0 45.000 PPB 736.000 PPB 100.000 % 00 2.000 PPB					

ANY METAL OBJECTS PRESENT?

YES

☑ NO

If yes include dimension



Clean Harbors Profile No. CH83147

E. CONSTITUENTS -- Are these values based on testing or knowledge? Knowledge ☑ Testing If constituent concentrations are base on analytical testing, analysis must be provided. If based on knowledge, basis of knowledge must be provided below RCRA REGULATED METALS REGULATORY TOLP TOTAL OTHER METALS MIN MAX UOM LEVEL (mg/l) pom ma/l ALUMINUM D004 ARSENIC 5.0 ANTIMONY D005 BARIUM <u>BERYLLIUM</u> D006 CADMIUM CALCIUM CHROMIUM 5.0 D007 COPPER 8000 5.0 MAGNESIUM MERCURY D009 0.2 MOLYBDENUM SELENIUM D010 1.0 NICKEL 5.0 POTASSIUM SILICON SODIUM RCRA VOLATILE COMPOUND THALLIUM REGULATORY TCLP TOTAL LEVEL (mg/t) TIN ppm mg/i D018 .._....0.5 VANADIUM 0.0 CARBON TETRACHLORIDE 0.5 ZINC D021 CHLOROBENZENE 100 0 D022 CHLOROFORM6.0 D028 1.2-DICHLOROETHANE 0.5 NON-METALS MIN 1,1-DICHLOROETHYLENE 0.7 MOU D029 METHYL ETHYL KETONE 200.0 D035 BROMINE TETRACHLOROETHYLENE 07 D039 CHLORINE TRICHLOROETHYLENE 0.5 FLUORINE _____ D040 IODINE D043 0.2 SULFUR RCRA SEMI-VOLATILE COMPOUND REGULATORY TCLP TOTAL LEVEL (mg/l) mg/l ppm OTHER NON-METALS D023 MIN o-CRESOL MAX 200.0 UOM m-CRESOL D024 200.0 AMMONIA D025 o-CRESOL REACTIVE SULFIDE CRESOL (TOTAL) 200.0 CYANIDE-TOTAL D027 1.4-DICHLOROBENZENE 7.5 CYANIDE AMENABLE D030 2,4 DINITROTOLUENE 0.13 CYANIDE REACTIVE HEXACHLOROBENZENE 0.13 D032 D033 HEXACHLOROBUTADIENE 0.5 D034 HEXACHLOROETHANE ______3.0 _____ OTHER CHEMICALS MIN MAX UOM D036 NITROBENZENE 2,0 2,0 D037 PENTACHLOROPHENOL 100 0 D038 PYRIDINE Total Petroleum Hydrocarbons 5.0 D041 2.4,6-TRICHLOROPHENOL 2.0 OTHER RCRA PESTICIDES AND HERBICIDE REGULATORY TCLP TOTAL LEVEL (mg/l) mg/i ppm **HOCs PCBs** 0012 ☑ NÔNE **☑** NONE D0:3 0.4 < 1000 PPM <50 PPM D014 METHOXYCHLOR 10.0 >= 1000 PPM >= 50 PPM D015 TOXAPHENE 0.5 D016 2.4·D 10.0 IF PCBS ARE PRESENT, IS THE 0017 2.4.5-TP (SILVEX) 1.0 WASTE REGULATED BY TSCA D020 CHLORDANE 0.03 40 CFR 761? D031 0,008 MEPTACHLOR (AND ITS EPOXIDE) **☑** NO YES ADDITIONAL HAZARDS DOES THIS WASTE HAVE ANY UNDISCLOSED HAZARDS OR PRIOR INCIDENTS ASSOCIATED WITH IT, WHICH COULD AFFECT THE WAY IT SHOULD BE HANDLED? YES 🗹 NO (If yes, explain) ASBESTOS INFECTIOUS, PATHOGENIC. OR ETIOLOGICAL AGENT REDUCING AGENT DEA REGULATED SUBSTANCES OXIDIZER SHOCK SENSITIVE NIXOIC OSHA REGULATED CARCINOGENS SPONTANEOUSLY IGNITES WITH AIR EXPLOSIVE PESTICIDE THERMALLY SENSITIVE HERBICIOS POLYMERIZABLE WATER REACTIVE FUMING / SMOKING WASTE RADIOACTIVE NONE OF THE ABOVE



Clean Harbors Profile No. CH83147

F REGUL	ATORY ST	ATUS		· · · · · · · · · · · · · · · · · · ·			
✓ YE\$	МО	USEPA HAZARDOUS WASTE?					
		F001 F002 F003 F005			 · · · · · · · · · · · · · · · · · · 		
YE\$	ЙиО	DO ANY STATE WASTE CODES A	PPLY?				<u></u> .
₹¥EŞ	ОИ	IS THIS WASTE PROHIBITED FRE LDR CATEGORY: This is suit	OM LAND DISPOSAL WI	THOUT FURTHE	R TREATMENT F	PER 40 CFR PART 268?	
YES YES	☑ NO	THORETON LING, OR DUTO-	2, D003 (OTHER THAN RI D043 APPLY, ARE ANY U	NUERLYING HAZ	ARDOUS (UHCs)	SULFIDE), D004-D0011, D012-D017 PRESENT ABOVE UNIVERSAL TREATME	ENT
YES YES	Ñνο	IS THIS WASTE SUBJECT TO CA IF YES, SPECIFY POINT SOURCE	STE GENERATE A F006 TEGORICAL PRETREAT E CATEGORY LISTED IN	OR F019 SLUDG IMENT DISCHAR I 40 CER PART 4	SE? :GE STANDARDS	?	
YES	Ωνο	IS THIS WASTE REGULATED UND RECOVERY, OR PETROLEUM REF	ER THE BENZENE NESH	AP RULES? (IS T	HIS WASTE FRO	M A CHEMICAL MANUFACTURING, COKE	8Y-PRODUCT
YES	ØN0 ØN0	DOES THIS WASTE CONTAIN VO	C'S IN CONCENTRATIO	NS >=500 PPM?			
YES YES	٠. ق	77 KPa (11.2PSIA)?	ORGANIC CONSTITUE	PRGANIC CONST NT WHICH IN ITS	ITUENTS WITH A S PURE FORM HA	N VAPOR PRESSURE >= .3KPA (.044 PS AS A VAPOR PRESSURE GREATER THA	IA)? AN
YES	Дио	IS THIS CERCLA REGULATED (SI	UPERFUND) WASTE ?				
G. D.O.T IN US. D.C	FORMATI D.T DESC	ON: (Include proper shipping name, has a standard on the stand	hazard class and ID number uid, n.o.s., (Benzene,	er). Ethylbenzene, .	Xylenes, Methy	lene Chloride, Naphthalene, Toluen	e), 9,
H. TRANS	PORTATION SHIP	ON REQUIREMENTS PMENT FREQUENCY: ON	NE TIME WEEKLY	MONTHLY	' QUARTE	ERLY YEARLY MOTHER	
IF BUL	K LIQUID (OR BULK SOLID PLEASE INICATE TO			SHIPPING FREQU	JENCY	
	o	CONTAINERIZED CONTAINERS/SHIPMENT		LK LIQUID		BULK SOLID	
STORAG	≚ E CAPACI		GALLONS/SHIPMENT		00 Max GAL	SHIPMENT UOM; TON	YARD
	VER TYPE		FROM TANKS: TAN	NK SIZE	6,000 GAL.	PER SHIPMENT: 0.00 MIN	0.00 MAX
cu	BIC YARD	BOX	FROM DRUMS			STORAGE CAPACI	TONYO
PAI	LLET		VEHICLE TYPE:			VEHICLE TYPE:	
ΤQ	TE TANK		VAC TRUCK ☑TANK TRUCK			DUMP TRAILER	
CI	HER:					ROLL OFF BOX	
	UM SIZE:	i	RAILROAD TANK C			INTERMODAL ROLLOFF BOX	(
	ER MATE	RIAL:	CHECK COMPATIBLE	STORAGE MATE		OTHER	
Ø ST! FIB			☑RUBBER LINED	FIBERGLAS		OTHER	1
	STIC		DERAKANE	ET I ISCNOCA	35 EINCU		
	HER [OTHER	<u>'</u>]	
	REQUEST		<u> </u>			<u> </u>	
		L RESTRICTIONS OR REQUESTS:					
		IANDLING REQUIREMENTS S OR REQUESTS:					
	7	L REPORTING INFORMATION					
SIC COD			DE A09	FORM CODE	B119	ORIGIN CODE 2	
K SAMPLE			YES	SAMPLEC		PATE SAMPLED WHERE	SENT
		SAMPLE HAS BEEN SUPPLIE	Ø NO			THE STATE OF THE PERSON OF THE	QEI41
GENERAT(·		
300	ore reples	Il information submitted in this and at entative of the actual waste. If Clean (thority to amend the profile, as Clear) Harbors discovers a disc	repancy during the	e approval proces	islo certify that any samples s, Generator grants	
	AUTHC	RIZED SIGNATURE		ME (PRINT)	ou epancy.	TITLE .	DATE
OR CLEA	N HARBO	RS USE ONLY					
		TATIVE COMPLETING PROFILE:_			_		
						_	

***	- /		177 3	1 #		(12-pitch) typewriter.
Please I	ntini at n	UNA I	a-orm o	egianaa t	AT HEA AN AHIA	112-Dii22) tuzowiiiat

Form	Approved.	OMB No.	205020000

ļ		Generator's Name and Mailing Address	tini dia	notice; or a				Number			
]	To	ocie Army Depot Environme	Circles Care	117 7	make the second religion to the	te Manifest Document Number te Generator's ID te Transporter's ID nsporter's Phone (435) 843-7802 te Transporter's ID nsporter's Phone te Facility's ID stillty's Phone 1) 323-8100 131					
	Bu 4. (ilding 8, Atta: Dean Royne Generator's Phone (A 15000) 1212222	ICA CISTA	B & State Generator's ID							
ļ		Transporter 1 Company Name	119 EDA ID Numbe		c. s	tate Transporte	's ID	CANAL SALES			
li	7.	- · ·		3r				Markey and the San			
li	9. 1							Carlotte Carlotte St. St. 1997. St. 1997. St. 1997. St. 1997. St. 1997. St. 1997. St. 1997. St. 1997. St. 1997 Additional St. 1997. St. 1997. St. 1997. St. 1997. St. 1997. St. 1997. St. 1997. St. 1997. St. 1997. St. 1997.			
	Cl	eau Harbors Aragonite Fac	ility					1.			
				[]Ne							
	Āŗ	agonite, UT 84029	OTD981552177	140.0	2000	200	-				
6	11.	US DOT Description (Including Proper Sh	ipping Name, Hazard Class and ID Number)	1		Total	anot required by Federal law. Set Document Number Setor's ID Se				
E	a.	Hazardous Waste Liqu	ld, n.o.s (Benzene,	NO.	уре	Quantity		F001,F002			
E				1		1.01	P				
R		Naptholene, Toluene),	9, NA3082, PGIII	3.34	TT						
7	ъ.	1				· · · ·	1 44				
R			THE CONTRACTOR OF CASE								
	C.						1				
İ				1 in			`[
		La la la la la la la la la la la la la la	province the above on a	1775	1		<u> </u>				
	d.		: .			•					
	J.	Additional Descriptions for Materials Liste	d Above	HI W	K. He	indling Codes to	r Waste	s Listed Above			
1			$ u \mapsto u \cdot v \cdot v \cdot v \cdot v \cdot v \cdot v \cdot v \cdot v \cdot v \cdot$								
	a	1. C88314/5 — Decom and U	Agrobaeuc Macet N=1/2		N/	H9.4Z04.	468	70/			
			$p = \frac{1}{2} \left(\frac{1}{2} \left(\frac{1}{2} \right) \right)$.							
	15.	Special Handling Instructions and Additi	onal Information	College number Newson	7.48.78		<u> </u>	KANTA KANTA			
		and the state of the state of the state of	Autor Marian								
	ř,		The state of the s	(435)	833	-2015					
İ	16		A TITLY Depot Environmental, Office, SUNTS-CS ED 18 State Generator's ID 18 State Generator's ID 18 State Generator's ID 18 State Generator's ID 18 State Transporter ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State Transporter's ID 18 State								
	10.	proper shipping name and are classified, packed,	marked, and labeled, and are in all respects in proper of	ondition for te	ansport	by highway					
		If I am a large quantity generator, I certify that	I have a program in place to reduce the volume are	d toxicity of	wasie d	enerated to the di	orea I h	ave determined to be			
		economically practicable and that I have selec-	ted the practicable method of treatment, storage, or	disposal curr	ently a	vailable to me whi	ch minim	izes the present and			
	_			Office Section	100	aliye da William	1.5				
╁		1 1	ng ting ting ang taong taong ang ang ang ang ang ang ang ang ang a			را در المداري الاراد الرائع و ما الراب المستميل المستميل		Month Day Year			
Ţ	17.					4					
R		Printed/Typed Name, 3 - Control Section Name	Signature	. ,		na na na na		Month Day Year			
4250		the think of the state of the s	<u>Com</u> naigh in gairtíneach a chomhaigh an tha an in agus aigh an tha an ig	Almong Free	-~-	4					
Ŕ	18.	. Transporter 2 Acknowledgement of Rec	eipt of Materials about the fit to some to be also.	el tion de l'A	es (gares	and the final					
Ë		Printed/Typed Name	Signature of the state of the s	submerting	a fibraj	North Commence of the	as ng lu	Month Day Year			
н	19	Discrepancy Indication Space	A second			<u></u>					
F		and the state of the state state was the state of	is well professional and a second section		30.00	Company to the	,				
F		 Section of the property of the Control	enda i kentik teta derakta saki terbahan dia ini ang menjeben ang	er og greker to	17ti - M	and A. and India, 1975	• • • • • •	· -			
Ļ	20	Facility Owner or Operator: Certification	of receipt of hazardous materials covered by	this manife	et ava	ent as neted in	degree I have determined to be hich minimizes the present and my waste generation and select Month Day Year Month Day Year Month Day Year Month Day Year				
ţ		Printed/Typed Name									
					96 (B)	4-1-6-1-					

Style F15 LABELI ASTER (800) 621-5808 www.fabelmaster.com

EPA Form 8700-22 (Rev. 9-88) Previous editions are obsolete.



	Ples				·							
ĺ	Ā	UNIFORM HAZARDOUS		A ID No	SIE A.	·	Form Approved.	OMB No. :	2050-0039.			
	T	WASTE MANIFEST	MANIFEST UT3213820894 Document No. 21 Pago 1 Information in the shaded alex so and Mailing Address Depot Environmental Office, SJMT2-CS EO, Atten: Dear Reynoldu, Toosele, UT 84074 B. State Canacterior ID Revision of the Company of the									
١		3. Generator's Name and Mailing Address	· · · · · · · · · · · · · · · · · · ·		<u> 18. t.A. 8. 3</u> 1. a - Agil 19. a							
1		Building 8. Attn: Bean Ray	ental Office.	SJATE-CS EO,	ing. Geografisangs							
	$\ \ $	4. Generator's Phone (435) 833-3	504 Alda	UI 84074		B. S	tate Generator	s ID				
	5. Transporter 1 Company Name											
I	7. Transporter 2 Company Name CAT00624247 D. Transporters Phone (435) 843-7802											
l	1 L	<u> </u>	ger i ver vije i	1 .	91	ES	tate Transporte	r's ID 🔻	and and the second of the second			
١		Class Harbore Against A. P.	s 10.	US EPA ID Numb	er !	G: State Facility's ID						
١	П	11000 R. Apteus Road her but	ignical and a second of the se	-			2 - 40 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 -					
	-	Aragonite, UT 84029			() o tribaliji.							
Į,	·	1. US DOT Description (Including Proper Shi			12. Conta	iners	13.	1 14	ariani Destrict Inc. 198			
	- 4	Hazardous Waste Liqui	d. c.o.a. (80	13 97 - 14 17 17 17 17 17 17 17 17 17 17 17 17 17	No.	Туре	Quantity	Wi/Vol	rest the contract of			
,	E	I them's the stantie, whiches,	Methylone Ch	Present day	and internal		A 100 100 100 100 1	1				
1	1	naprhalene, roluene),9	NA3082, PG	III		FT.	a a compression de la compression de la compression de la compression de la compression de la compression de l La compression de la compre	1				
F	<u>'</u>	1	ing series and the series of t						4.04			
	ŀ			<u></u>			,					
	°	1 1 1 2 2 2 2 2 2					eran eran eran eran eran eran eran eran	†	Service Control			
İ	L	Carlotte Company	And the second s			[4.20					
ľ	d							╀┈┤	SALANES TEST			
ı	l		territere et la companya de la companya de la companya de la companya de la companya de la companya de la comp			[
	J	Additional Descriptions for Materials Listed	Above	A Section	e.careare	K. Ha	Aller Color to	1910 - 1	100			
		a; CH831478 - Decon and D	velopment Whi	or <i>D-J</i> _		100			Marie Comment of the			
				- 13 KB		\mathcal{L}	4 <i>pSN</i> Z(54Q	6801 🗟			
1	L		The state of the s	·· 10-16				dya saya.				
١	"	Special Handling Instructions and Addition	al Information	Manufactures		·	ran aministra	<u>artinan art</u>	Marija Marija ar Milja			
		As the property of the second second	Army Depot Fi	re Department	(435)3	332	015					
Ì	Ļ			et en en en en	ĸ							
	"	 GENERATOR'S CERTIFICATION: I hereby declare to proper shipping name and are classified, packed, ma 	hat the contents of this contribed, and labeled, and labeled, and labeled.	signment are fully and accur	ately describ	ed above	a by					
l		If I am a large quantity generates I apply to a	to the ball of a Bridge of the California	こうさんさい 多数の	V I 38 1 1/2 4	A 5 3 5 5						
		AND A WILLIAM OF THE STREET STREET OF THE PROPERTY OF THE PROP	H 100 Hilliam a		-L-255 001101	TOY DYD	INVESTIGATION OF WARRIED	3 minimir	e determined to be			
	-	and the management metrico many available	to me and that I can afford	Commence of the state of the	de a good fa	ith effor	t to minimize my	waste ge	neration and select			
Z	L	mage to the state of the state	grafic glancia a la .	Signature	or Tile April Agriff Holey	ar en en en en en en en en en en en en en	angi awaya ito s	M				
1	17	. Transporter 1 Acknowledgement of Receip	t of Materials						44 1			
ì		Printed/Typed Name	4	Signature	rivid Tanasanan	<u>r kan</u> Galamata	المستقدية والمستقدين والتراث	M	onth Day Year			
	18	Transporter 2 Acknowledgement of Receip	t of Materials	<u> </u>	1-2-44 to	· · · · · · · ·			4111			
	-	Printed/Typed Name And Brown State (1997)	A \$16 de sua you filtree	Signature seminers	<u> Strand (1. 1.)</u> Wildelicher	g (a)	arens. Kallessagar - Ja	·	onth Dec 16			
┧	19	Discrepancy Indication Space		<u>L</u>		<u> </u>			Jay Year			
		The state of the s					9 () () ()					
1		and the state of the second of the state of the second	rake to a reflective evening	and a second	and the same of th	وليان ماند م (المانات ال	e v severala Receptoriza	errore Granda				
ļ	20	Facility Owner or Operator: Certification of	receipt of hazardous n	naterials covered by th	is manifoct	AVES C	ton materials	Information in the shaded areas is not required by Federal law. Intest Document Number Interactor's ID Insporter's ID Insp				
			eriteta (j. 1864). Er	Signature	- mannest	exceb:	as noted in Ite		onth Day Voca			
<u>l</u>		LABELI ASTER @ (800) 621-5808 WARN INDOMESTICA			Territoria		residente (s.	i^				

e plint or type. (Form designed for use on elite	12-pitch) typewriter.)				Form Approved. OM	B No. 205	50-0039.		
UNIFORM HAZARDOUS WASTE MANIFEST	1. Generator's US EPA ID	Docur	nent No.	2. Pa of	age 1 Informa	ition in t iquired	he shaded by Federal	area: law.	
. Generator's Name and Mailing Address		Pallegor Commission of the Commission	4 in 189 j	A. Ste	ate Manifest Doc	cument	Number		
locale Army Depot Environ	mental Office, SJ	ITE-CS-EO		945	446 25 5 4	- 1 - 2			
milding 8, Attn: Dean Reg Generator's Phone (435) 833-	molds, Tooele, V	r.84074	GANGA.	او در در .	ate Generator's				
Transporter 1 Company Name	6.	US EPA ID Numbe	r:	C. St	ate Transporter	s ID	4 (A)		
MP Environmental	CALU	0624247			ansporter's Pho				
Transporter 2 Company Name	8, 111	US EPA ID Numbe		E. State Transporter's ID					
	White I have	<u>, , , , , , , , , , , , , , , , , , , </u>			ansporter's Pho		THE WAY		
Designated Facility Name and Site Add lean Harbors Aragonite F		US EPA ID Numbe			tate Facility's ID	San San San	San San San San San San San San San San		
1600 N. Aptees Road ragonite, UT 84029	talification of a second	81552177			acility's Phone			- 14 - 15 - 14	
1. US DOT Description (Including Proper		:	12. Contain	ners	13. Total	14. Unit Wt/Vol	Waste	No,	
(TRIAT)			No.	ype	Quantity	est.	F001.F	<u>aa2</u>	
Hazardous Waste Liq Ethylbenzene, Xylene	s, Methylane Chlo	ride,	001	TŢ		P	F003,F		
Napthalene, Toluene)	, 9, NA3082, PG 1	11	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	1,1		} `	a segretaria.	2000 2000	
All and the second	en Praem A Comment				forther in	-	1400		
<u> </u>							130 Sept. 1	. 35	
			[:].						
1. 机新加油基础 (1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	the graph of the second test of the				1 1 1 1 1		State Broken		
							7		
a. CH831478 - Decom-and	Development Water) 33 7) 2/2		p	MEDITOF	Val	le_		
15. Special Handling Instructions and Administration and Administratio	cela Army Depot Finding that the contents of this consider, marked, and labeled, and are in that I have a program in place the elected the practicable method or comment. OR, If I am a small que	ignment are fully and acc n all respects in proper of n reduce the volume an f treatment, storage, or initity generator, I have re	curately description for transition for transition for transition of the discussion	bed ab	ove by t by highway generated to the d				
Printed/Typed Name	eriari kanan dan kebua	Signature	To the second se		an pagara gift		Month Da		
Larry Maranta	r CL	Trens,	172-	1000	مسكوك والمتعارض والمتعارض	·	17 5		
17. Transporter 1 Acknowledgement of	Receipt of Materials	Signature	<u> </u>	<u> </u>	<u> </u>		Month Da	av	
	en arginere et al. <u>7 ja</u>	1 1 to	1	رسد	ر است. است به مجمود ارزیم	· ·			
18. Transporter 2 Acknowledgement of	Receipt of Materials	Signature (Material)	anterior has di	11.	<u>establija storija.</u> Turinista	15 10	Month Da	<u>-</u> -	
Printed/Typed Name	inggrammed separate a soften exc	Signature (1838)	ar tylketitle. •)	. 2 1 1 1	is the state of th	. 11.12.41	IWOMIN D	ау <u>1</u>	
19. Discrepancy Indication Space		en de la companya de la companya de la companya de la companya de la companya de la companya de la companya d La companya de la companya de la companya de la companya de la companya de la companya de la companya de la co	•	· .		٠.			
20. Facility Owner or Operator: Certifica	0. Facility Owner or Operator: Certification of receipt of hazardous materials covered by this manifest except as noted in Item 19.								
Printed/Typed Name	· 	Signature /				7.	Month D	ay 1	
and the second of the second of the second	200 su — Japan Kush e SVI	The Shaking in Life 3			A 772 F		<u> </u>	Ш	

Style F15 LABEL ASTER (800) 621-5808 www.labelmaster.com

EPA Form 8700-22 (Rev. 9-88) Previous editions are obsolete.